

## LIST OF TABLES

Figure No.	CHAPTER	Page No.
<b><i>CHAPTER 1: ZnO based Varistor Ceramics - An Introduction</i></b>		
1.1.	Timeline of the proposed conduction model in ZnO varistor [after Eda (1989)].	8
1.2.	Roles of additives in ZnO varistors [after K. Eda (1989)]	10
1.3.	The parameters of a typical ZnO [Najafi (2012)]	22
<b><i>CHAPTER 2: Literature Review</i></b>		
2.1.	Summary of Varistor parameters for ZnO-V <sub>2</sub> O <sub>5</sub> ceramics sintered at 900 °C.	34
2.2.	Electrical properties and density of prepared ceramics	37
<b><i>CHAPTER 4: Synthesis and Characterization Methods</i></b>		
4.1.	Material used	52
<b><i>CHAPTER 5: Electrical and structural characterization of Nb<sub>2</sub>O<sub>5</sub> doped ZnO-V<sub>2</sub>O<sub>5</sub> varistor ceramics sintered at different temperatures.</i></b>		
5.1.	Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 850°C for 3h	74
5.2.	Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 900°C for 3h	74
5.3.	Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 950°C for 3h	74
5.4.	Lattice parameters, percentage theoretical density (T.D) and crystallite size D (nm) for (002) of Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 850 °C.	80

5.5.	Lattice parameters, percentage theoretical density (T.D) and crystallite size D (nm) of Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 900 °C.	80
5.6.	Lattice parameters, percentage theoretical density (T.D) and crystallite size D (nm) of Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 950 °C.	81
5.7.	Summary of electrical results obtained for Nb <sub>2</sub> O <sub>5</sub> doped ZnO-V <sub>2</sub> O <sub>5</sub> materials sintered at 850 °C	100
5.8.	Summary of electrical results obtained for Nb <sub>2</sub> O <sub>5</sub> doped ZnO-V <sub>2</sub> O <sub>5</sub> - materials sintered at 900 °C	101
5.9.	Summary of electrical results obtained for Nb <sub>2</sub> O <sub>5</sub> doped ZnO-V <sub>2</sub> O <sub>5</sub> materials sintered at 950 °C	102
5.10.	Summary of fitted electrical parameter obtained from EIS software measured at 50 °C for Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 850 °C.	120
5.11.	Summary of fitted electrical parameter obtained from EIS software measured at 150 °C for Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 850 °C.	121
5.12.	Summary of fitted electrical parameter obtained from EIS software measured at 250 °C for Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 850 °C.	121
5.13.	Summary of Fitted Electrical parameter obtained from EIS software measured at 50 °C for Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 900 °C.	122
5.14.	Summary of fitted electrical parameter obtained from EIS software measured at 150 °C for Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 900 °C.	122
5.15.	Summary of fitted electrical parameter obtained from EIS software measured at 250 °C for Nb <sub>2</sub> O <sub>5</sub> doped samples sintered at 900 °C.	122

- 5.16. Summary of fitted electrical parameter obtained from EIS software measured at 50 °C for Nb<sub>2</sub>O<sub>5</sub> doped samples sintered at 950 °C. 123
- 5.17. Summary of fitted electrical parameter obtained from EIS software measured at 150 °C for Nb<sub>2</sub>O<sub>5</sub> doped samples sintered at 950°C. 123
- 5.18. Summary of fitted electrical parameter obtained from EIS software measured at 250 °C for Nb<sub>2</sub>O<sub>5</sub> doped samples sintered at 950°C. 124
- 5.19. Activation energies calculated from the Arrhenius plot at low and high frequency region for the samples sintered at 850 °C. 130
- 5.20. Activation energies calculated from the Arrhenius plot at low and high frequency region for the samples sintered at 900 °C. 130
- 5.21. Activation energies calculated from the Arrhenius plot at low and high frequency region for the samples sintered at 950 °C. 130

***CHAPTER 6: Electrical and structural characterization of MnO doped ZnO - V<sub>2</sub>O<sub>5</sub> - Nb<sub>2</sub>O<sub>5</sub> varistor ceramics sintered at different temperatures.***

- 6.1. Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 850 °C for 3 h 139
- 6.2. Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 900 °C for 3 h 139
- 6.3. Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 950 °C for 3 h. 139
- 6.4. Lattice parameters, percentage theoretical density (T.D) and crystallite size D (nm) MnO doped ZnO-V<sub>2</sub>O<sub>5</sub>-Nb<sub>2</sub>O<sub>5</sub> varistor sintered at 850 °C. 141

6.5.	Lattice parameters, percentage theoretical density (T.D) & crystallite size D (nm) for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> varistor sintered at 900 °C	142
6.6.	Lattice parameters, percentage theoretical density (T.D) & crystallite size D (nm) for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> varistor sintered at 950 °C	143
6.7.	Summary of electrical results obtained for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> varistors sintered at 850 °C	165
6.8.	Summary of electrical results obtained for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> varistors sintered at 900 °C	166
6.9.	Summary of Electrical Results obtained for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> materials sintered at 950 °C	168
6.10.	Summary of fitted electrical parameter obtained from EIS software for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> materials sintered at 850 °C and measured at 50 °C.	180
6.11.	Summary of fitted electrical parameter obtained from EIS software for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> materials sintered at 850 °C and measured at 150 °C.	180
6.12.	Summary of fitted electrical parameter obtained from EIS software for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> materials sintered at 850 °C and measured at 250 °C.	180
6.13.	Summary of fitted electrical parameter obtained from EIS software measured at 50 °C for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> samples sintered at 900 °C.	185
6.14.	Summary of fitted electrical parameter obtained from EIS software measured at 150 °C for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> samples sintered at 900 °C.	185
6.15.	Summary of fitted electrical parameter obtained from EIS software measured at 250 °C for MnO doped ZnO-V <sub>2</sub> O <sub>5</sub> -Nb <sub>2</sub> O <sub>5</sub> samples sintered at 900 °C.	185

- 6.16. Summary of fitted electrical parameter obtained from EIS software measured at 50 °C for MnO doped ZnO-V<sub>2</sub>O<sub>5</sub>-Nb<sub>2</sub>O<sub>5</sub> samples sintered at 950 °C. 189
- 6.17. Summary of fitted electrical parameter obtained from EIS software measured at 150 °C for MnO doped ZnO-V<sub>2</sub>O<sub>5</sub>-Nb<sub>2</sub>O<sub>5</sub> samples sintered at 950 °C. 189
- 6.18. Summary of fitted electrical parameter obtained from EIS software measured at 250 °C for MnO doped ZnO-V<sub>2</sub>O<sub>5</sub>-Nb<sub>2</sub>O<sub>5</sub> samples sintered at 950 °C. 189
- 6.19. Activation energies calculated from the Arrhenius plot at low and high frequency region for the temperature range below and above 150 °C for the samples sintered at 850 °C. 195
- 6.20. Activation energies calculated from the Arrhenius plot at low and high frequency region for the temperature range below and above 150°C/200°C for the samples sintered at 900 °C. 196
- 6.21. Activation energies calculated from the Arrhenius plot at low and high frequency region for the temperature range below and above 150°C/200°C for the samples sintered at 950 °C. 196

***CHAPTER 7: Electrical and Structural Characterization of ZrO<sub>2</sub> doped ZnO – V<sub>2</sub>O<sub>5</sub> – Cr<sub>2</sub>O<sub>3</sub> Varistor Ceramics Sintered at Different Temperatures.***

- 7.1. Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 850 °C for 3 h. 201
- 7.2. Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 900 °C for 3 h. 201
- 7.3. Summary of samples composition and their nomenclature, sintered density 'ρ' and average grain size for samples sintered at 950 °C for 3 h. 201

- 7.4. Lattice parameters, percentage theoretical density (T.D) and 205  
crystallite size D (nm) for (002) of ZrO<sub>2</sub> doped samples sintered  
at 850°C.
- 7.5. Lattice parameters, percentage theoretical density (T.D) and 205  
crystallite size D (nm) for (002) of ZrO<sub>2</sub> doped samples sintered  
at 900 °C.
- 7.6. Lattice parameters, percentage theoretical density (T.D) and 205  
crystallite size D (nm) for (002) of ZrO<sub>2</sub> doped samples sintered  
at 950 °C.
- 7.7. Summary of electrical results obtained for ZrO<sub>2</sub> doped ZnO- 227  
V<sub>2</sub>O<sub>5</sub>-Cr<sub>2</sub>O<sub>3</sub> samples sintered at 850 °C
- 7.8. Summary of electrical results obtained for ZrO<sub>2</sub> doped ZnO- 229  
V<sub>2</sub>O<sub>5</sub>-Cr<sub>2</sub>O<sub>3</sub> samples sintered at 900 °C
- 7.9. Summary of Electrical Results obtained for ZrO<sub>2</sub> doped ZnO- 231  
V<sub>2</sub>O<sub>5</sub>-Cr<sub>2</sub>O<sub>3</sub> samples sintered at 950°C
- 7.10. Summary of fitted electrical parameter obtained from EIS 243  
software for ZrO<sub>2</sub> doped samples sintered at 850 °C and  
measured at 50 °C.
- 7.11. Summary of fitted electrical parameter obtained from EIS 243  
software for ZrO<sub>2</sub> doped samples sintered at 850 °C and  
measured at 150 °C.
- 7.12. Summary of fitted electrical parameter obtained from EIS 243  
software for ZrO<sub>2</sub> doped samples sintered at 850 °C and  
measured at 250 °C.
- 7.13. Summary of fitted electrical parameter obtained from EIS 247  
software measured at 50 °C for ZrO<sub>2</sub> doped samples sintered at  
900 °C.
- 7.14. Summary of fitted electrical parameter obtained from EIS 247  
software measured at 150 °C for ZrO<sub>2</sub> doped samples sintered at  
900 °C.

- 7.15. Summary of fitted electrical parameter obtained from EIS software measured at 250 °C for ZrO<sub>2</sub> doped samples sintered at 900 °C. 247
- 7.16. Summary of fitted electrical parameter obtained from EIS software measured at 50 °C for the samples sintered at 950 °C. 251
- 7.17. Summary of fitted electrical parameter obtained from EIS software measured at 150 °C for the samples sintered at 950 °C. 251
- 7.18. Summary of fitted electrical parameter obtained from EIS software measured at 250 °C for the samples sintered at 950 °C. 252
- 7.19. Activation energies calculated from the Arrhenius plot at low and high frequency region for the temperature range below and above 150 °C for the samples sintered at 850 °C. 258
- 7.20. Activation energies calculated from the Arrhenius plot at low and high frequency region for the temperature range below and above 150°C for the samples sintered at 900 °C. 258
- 7.21. Activation energies calculated from the Arrhenius plot at low and high frequency region for the temperature range below and above 150°C for the samples sintered at 950 °C. 258