

## LIST OF FIGURES

	<b>Page No.</b>
<b>1.1</b> A schematic diagram of a typical biofilter	<b>6</b>
<b>3.1</b> Biofiltration Set-up with accessories in our laboratory	<b>34</b>
<b>3.2</b> Schematic set-up for the biofilter column	<b>35</b>
<b>4.1</b> Variation of removal efficiency with change in inlet concentration of BTX and gas flow rates	<b>38</b>
<b>4.2</b> Influence of Benzene loading rate on elimination capacity and removal efficiency of biofilter	<b>41</b>
<b>4.3</b> Influence of Toluene loading rate on elimination capacity and removal efficiency of biofilter	<b>41</b>
<b>4.4</b> Influence of Xylene loading rate on elimination capacity and removal efficiency of biofilter	<b>42</b>
<b>4.5</b> Influence of BTX loading rate on elimination capacity and removal efficiency of biofilter	<b>45</b>
<b>4.6</b> Determination of Michaelis–Menten kinetic constants of benzene, toluene, and xylene	<b>47</b>
<b>5.1</b> Variation of removal efficiency with change in inlet concentration of MEK, Toluene and Xylene gas flow rates	<b>51</b>
<b>5.2</b> Influence of MEK loading rate on elimination capacity and removal efficiency of biofilter	<b>53</b>
<b>5.3</b> Influence of Toluene loading rate on elimination capacity and removal efficiency of biofilter	<b>54</b>

<b>5.4</b>	<b>Influence of Xylene loading rate on elimination capacity and removal efficiency of biofilter</b>	<b>54</b>
<b>5.5</b>	<b>Variation of Elimination Capacity and Removal Efficiency with total MTX loading rates</b>	<b>57</b>
<b>5.6</b>	<b>Determination of Michaelis-Menten constant for MEK, Toluene and Xylene degradation</b>	<b>58</b>
<b>6.1</b>	<b>Variation of RE with change in inlet concentration of styrene with operating days</b>	<b>63</b>
<b>6.2</b>	<b>Variation of removal efficiency, elimination capacity with inlet load of styrene</b>	<b>64</b>
<b>6.3</b>	<b>Determination of Michaels-Menden kinetic constants for styrene</b>	<b>65</b>
<b>7.1</b>	<b>Variation of RE with change in inlet concentration of styrene with operating days</b>	<b>70</b>
<b>7.2</b>	<b>Variation of removal efficiency, elimination capacity with inlet load</b>	<b>72</b>
<b>7.3</b>	<b>The surface morphology of biofilter media before (a) and after inoculation (b) using Scanning Electron Microscope (SEM)</b>	<b>73</b>

\*\*\*\*\*