

LIST OF TABLES

Table 3.1: Refined structural parameters obtained from the Rietveld refinement of the room temperature structure of $\text{La}_{0.5}\text{Ca}_{0.5}\text{MnO}_3$ samples calcined at 600 °C, 800 °C and 1400 °C [100].

Table 3.2: Refined structural parameters obtained from the Rietveld refinement of the room temperature structure of $\text{Nd}_{0.5}\text{Ca}_{0.5}\text{MnO}_3$ calcined at 700 °C, 900 °C and 1100 °C [101].

Table 3.3: Refined structural parameters obtained from the Rietveld refinement of the room temperature structure of $\text{Nd}_{0.5}\text{Ca}_{0.5}\text{MnO}_3$ calcined at 700 °C, 900 °C and 1100 °C [102].

Table 3.4: Generalized S_{HKL} strain parameters of bulk and nanocrystalline LCMO, NCMO and PCMO ceramics [127].

Table 4.1: Rietveld structural parameters for bulk (C13) $\text{Nd}_{0.5}\text{Sr}_{0.5}\text{MnO}_3$ ceramics at room temperature using space groups *Imma* [154].

Table 4.2: Rietveld structural parameters for bulk (C13) $\text{Nd}_{0.5}\text{Sr}_{0.5}\text{MnO}_3$ ceramics at 13K using coexisting *P2₁/m+Imma* space groups [155].