

---

---

## List of Figures

Fig. 1.1 Foam cement insulation board	3
Fig. 1.2 Kiln furnitures made of various materials	4
Fig. 1.3 Porous ceramics for combustion application	4
Fig. 1.4 Light weight space mirrors with porous SiC used as a support for dense polished SiC reflecting layer	5
Fig. 1.5 Ceramic catalyst substrate for catalyst and adsorbent supports	7
Fig. 1.6 Ceramic foam filters for metal filtration	8
Fig. 1.7 Ceramic foam filters for fluid filtration	9
Fig. 1.8 Engineering porous materials for fuel cell applications	10
Fig. 1.9 Porous ceramics for humidity sensor	11
Fig. 1.10 Porous HA eyeball implant and its microstructure	12
Fig. 2.1 Representative fabrication process of porous ceramics	15
Fig. 2.2 Replica processing routes used for the production of porous ceramics	17
Fig. 2.3 Porous hydroxyapatite obtained from the coral structure	19
Fig. 2.4 Transversal view of a highly oriented SiC porous ceramic obtained after infiltration of a wood template with Si gas	20
Fig. 2.5 Sacrificial template processing route used for the production of porous ceramics	22
Fig. 2.6 Direct foaming processing routes used for the production of porous ceramics	24
Fig. 4.1 Effect of sucrose binder content on green density of as pressed and dried alumina compacts	36
Fig. 4.2 Variation in flexural strength of as pressed and dried alumina compacts as a function of sucrose binder content	38
Fig. 4.3 Fractured surface of fine alumina samples with 4.8, 7.2 (optimum) and 9.6 wt% sucrose binder	39
Fig. 4.4 Drilled green alumina samples prepared with sucrose content 1.8, 2.4, 3, wt% (left) and 3.6, 4.8, 6, 7.2 wt% (right)	40
Fig. 4.5 SEM micrograph of the drilled surface of green alumina sample fabricated with 7.2 wt% (optimum) sucrose content	40

Fig. 4.6 IR spectrum of sucrose binder	41
Fig. 4.7 (a) Thermogravimetric analysis and (b) Differential thermal analysis of sucrose binder in air	41
Fig. 4.8 Variation of porosity of sintered alumina compacts prepared with fine and coarse alumina powder as a function of sucrose binder content	42
Fig. 5.1 Schematic diagram showing organic burnout schedule during heat treatment of samples	52
Fig. 5.2 Schematic diagram showing firing schedule of alumina samples	52
Fig. 5.3 Flow chart for fabrication of porous alumina	53
Fig. 5.4 Sintered samples fabricated with 10, 20 and 30 wt% rice husk	53
Fig. 5.5 TG analysis of RH powder and sucrose in air atmosphere	55
Fig. 5.6 X-ray diffraction pattern of residue (RHA) left after heat treatment of RH powder at 1000°C	56
Fig. 5.7 (a) Cracking and bending in samples with 30 and 40 wt%, (b) bursting of 30 wt% RH sample in to powder after drying at 100 °C/24 h and (c) alumina samples with 10 and 20 wt% RH heated at 5 °C/min	58
Fig. 5.8 Flexural strength of green samples	60
Fig. 5.9 (a) Drilling of green samples and (b) fracture surface of samples after strength testing	61
Fig. 5.10 Sample Al <sub>420-600</sub> RH <sub>10</sub> before and after firing	61
Fig. 5.11 Density of sintered samples as a function of size of rice husk in the composition	62
Fig. 5.12 XRD patterns of a porous alumina compacts Al <sub>&lt;sup&gt;75&lt;/sup&gt;</sub> RH <sub>20</sub> _SS <sub>20</sub> and Al <sub>180-355</sub> RH <sub>40</sub> _SS <sub>20</sub> fabricated using RH and sucrose and sintered at 1700°C	64
Fig. 5.13 (a) Fracture and (b) cut surface of sandwich structure	65
Fig. 6.1 Effect of RH content for various sizes of RH powder on porosity of porous alumina compacts	69
Fig. 6.2 SEM micrograph of sintered porous alumina compacts fabricated using (a) 10, (b) 20, (c) 30 and (d) 40 wt% RH (75-180 μm average size) powder	71
Fig. 6.3 SEM micrograph of a porous alumina compacts showing large elongated pores and fine pores	71

Fig. 6.4 Effect of RH content on average pore size of porous alumina compacts	73
Fig. 6.5 SEM micrograph of sintered porous alumina compacts fabricated using 20 wt% RH powder with (a) <75, (b) 75-180, (c) 180-355, (d) 355-420 and (e) 420-600 $\mu\text{m}$ size	74
Fig. 6.6 Normalized vol (cc/g) histogram in $\mu\text{m}$ for samples with compositions (a) $\text{Al}_{75-180}\text{RH}_{10}\text{SS}_{20}$ (b) $\text{Al}_{75-180}\text{RH}_{20}\text{SS}_{20}$ (c) $\text{Al}_{75-180}\text{RH}_{30}\text{SS}_{20}$ and (d) $\text{Al}_{75-180}\text{RH}_{40}\text{SS}_{20}$	76
Fig. 6.7 Effect of (a) porosity and (b) pore size on flexural strength of porous alumina compacts	78
Fig. 6.8 Effect of (a) porosity and (b) pore size on compressive strength of porous alumina compacts	80
Fig. 6.9 Effect of (a) porosity and (b) pore size on elastic modulus of porous alumina compacts	80
Fig. 6.10 Effect of (a) porosity and (b) pore size on hardness of porous alumina samples	81
Fig. 7.1 Effect of RH content and RH size on porosity and thermal conductivity of porous alumina compacts	91
Fig. 7.2 Variation of RH size and RH content on pore size and thermal conductivity of porous alumina compacts	91
Fig. 7.3 Schematic representation of three different types of pore connectivity for developed porous ceramics (a) 3-0 connectivity (b) (i) and (ii) 3-3 connectivity with varying extent of interconnection & (c) 0-3 connectivity	94
Fig. 7.4 Effective thermal conductivity as a function of porosity for analytical prediction and experimental measurements	95
Fig. 7.5 Effective thermal conductivity as a function of pore size for analytical prediction and experimental measurements	96
Fig. 7.6 Retained flexural strength as a function of severity of quench (temperature difference in quenching) for porous alumina with varying porosity	98
Fig. 7.7 Effect of composition on flexural strength before and after thermal quenching	99
Fig. 8.1 Variation of dielectric constant of porous alumina samples as a function of frequency at different temperatures with porosities (a) 2% (b) 39% (c) 61%	111

Fig. 8.2 Variation of dielectric constant of porous alumina samples as a function of frequency with increasing in porosity at (a) room temperature(b) 200°C and (c) 500°C	115
Fig. 8.3 Variation of dielectric constant of porous alumina samples as a function of frequency for different pore size at (a) room temperature (b) 200°C and (c) 500°C	117
Fig. 8.4 Variation of loss tangent of porous alumina samples as a function of frequency at different temperatures with porosities (a) 2% (b) 39%	118
Fig. 8.5 Variation of loss tangent of porous alumina samples as a function of frequency with increasing in porosity at (a) room temperature(b) 200°C and (c) 500°C	121
Fig. 8.6 Variation of loss tangent of porous alumina samples as a function of frequency for different pore size at (a) room temperature (b) 200°C and (c) 500°C	122
Fig. 8.7 Comparison of dielectric constant between the experimental results and Maxwell-Garnet model of the porous alumina ceramics with different amount and pore size of rice husk at room temperatures	124
Fig. 8.8 Experimental results for individual samples and fits to the models discussed in section 8.2.2 (Eqn 8.12)	125
Fig. 9.1 Schematic of the set-up used for measuring gas permeability	132
Fig. 9.2 Set up for measurement of gas permeability of porous ceramics	133
Fig. 9.3 Variation of pressure drop with nitrogen gas flow at fixed pressure across porous alumina compacts	135
Fig. 9.4 Pressure drop as a function of flow rate for predicted results and experimental results	135
Fig. 9.5 Variation of flow rate with total porosity for various nitrogen gas at different pressure across porous alumina compacts	136
Fig. 9.6 Variation of (a) Darcian permeability $k_1$ and (b) non-Darcian permeability $k_2$ with porosity of porous alumina compacts	137
Fig. 9.7 Variation of (a) Darcian permeability $k_1$ and (b) non-Darcian permeability $k_2$ with pore size of porous alumina compacts	137