

---

## LIST of FIGURES

### FIGURES

	<b>Page No.</b>
<b>Chapter I</b>	<b>Introduction and Literature Review</b>
	1-40
Fig. 1.1	Working principle of fuel cell
Fig. 1.2	1
Fig. 1.3	Polarization curve of fuel cell
Fig. 1.3	2
Fig. 1.4	Working principle of SOFC
Fig. 1.4	8
Fig. 1.5	Planer SOFC
Fig. 1.5	9
Fig. 1.6	Tubular SOFC
Fig. 1.6	10
Fig. 1.6	Temperature dependence of electrical conductivity of oxide ion electrolytes
Fig. 1.6	14
Fig. 1.7	Crystal structure of ceria
Fig. 1.7	17
Fig. 1.8	EDXM spectra of a grain and grain boundary in $\text{CeO}_2:6 \text{ mol\% Gd}_2\text{O}_3$ sample.
Fig. 1.8	21
Fig. 1.9	Variation of association energy against the dopant concentration for various rare earth cation doped ceria
Fig. 1.9	23
Fig. 1.10	Log $\sigma T$ and Log A vs Ea plot of yttria-doped ceria
Fig. 1.10	24
Fig. 1.11	Log $\sigma T$ and Log A vs Ea plot of gadolinia-doped ceria
Fig. 1.11	25
Fig. 1.12	(a) TEM images and (b) SEM images of ceria/carbonate nanocomposites
Fig. 1.12	28
Fig. 1.13	Variation of ionic conductivity of composites electrolyte with carbonate compositions
Fig. 1.13	29
Fig. 1.14	Variation of conductivity with carbonate content at 650 °C
Fig. 1.14	30
Fig. 1.15	Electrical field at the interfaces between two constituent phase particles
Fig. 1.15	32
Fig. 1.16	Conducting highways at the interfaces of two phase particles resulting in interfacial superionic conduction
Fig. 1.16	33
Fig. 1.17	(a) Time dependence of electrical conductivity of GDC/(Li-K) <sub>2</sub> CO <sub>3</sub> composite at 600 °C in air under OCV condition (b) Evaluation of cell performances vs. time for ceria/carbonate composite electrolytes based SOFC at 550 °C
Fig. 1.17	34
Fig. 1.18	Basic building block for automobile APUs
Fig. 1.18	36
Fig. 1.19	500 W battery charging system concept
Fig. 1.19	37
Fig. 1.20	Portable SOFC system
Fig. 1.20	37
Fig. 1.21	Multi-ion conduction and advanced applications of ceria/ carbonates nanocomposites
Fig. 1.21	39

<b>Chapter III</b>	<b>Experimental Work</b>	<b>46-62</b>
Fig. 3.1	Flow chart for preparation of nitrates	48
Fig. 3.2	Flow chart for synthesis of ceria powders	49
Fig. 3.3	Flow chart of the preparation of nanocomposites	50
Fig. 3.4	Optimization of load	51
Fig. 3.5	NETZSCH Gerate Bau DTA/TGA	52
Fig. 3.6	Schematic diagram of X-ray diffractometer	54
Fig. 3.7	Working principle of FE-SEM	56
Fig. 3.8	Image of FEI NOVA NANOSEM	57
Fig. 3.9	Image of push rod dilatometer	58
Fig. 3.10	A schematic representation of impedance plot of a polycrystalline solid electrolyte with an equivalent circuit	61
Fig. 3.11	A schematic diagram of sample cell used in impedance measurements	61
<b>Chapter IV</b>	<b>La and Sr Co-Doped Ceria, <math>Ce_{1-x-y}La_xSr_yO_{2-\delta}</math> (Fixed Oxygen Vacancies) and its Nanocomposites</b>	<b>63-115</b>
Fig. 4.1	DTA/TGA plot of the ash of composition CLO15	65
Fig. 4.2	Powder X-ray diffraction patterns of sintered powders for various compositions (a) CLO15 (b) CL11S2(c) CL7S4 (d) CL3S6 in the system $Ce_{1-x-y}La_xSr_yO_{2-\{x/2+y\}}$	66
Fig. 4.3	Variation of lattice parameter as a function of $Sr^{2+}$ concentration in the system $Ce_{1-x-y}La_xSr_yO_{2-\{x/2+y\}}$	69
Fig. 4.4	SEM micrographs of various compositions (a) CLO15 (b) CL11S2 (c) CL7S4 (d) CL3S6 in the system $Ce_{1-x-y}La_xSr_yO_{2-\{x/2+y\}}$	70
Fig. 4.5	EDS spectrum of the composition CLO15 at three different points	71
Fig. 4.6	EDS spectrum of the composition CL7S4 at three different points	72
Fig. 4.7	Complex plane impedance plots of the composition CLO15 at different temperatures	74
Fig. 4.8	Complex plane impedance plots of the composition CL11S2 at different temperatures	77
Fig. 4.9	Complex plane impedance plots of the composition CL7S4 at different temperatures	80
Fig. 4.10	Complex plane impedance plots of the composition CL3S6 at different temperatures	83
Fig. 4.11	Brick layer model of polycrystalline material	86

Fig. 4.12	Arrhenius plots of all the compositions for the grain, grain boundaries and total ionic conductivity in the system $\text{Ce}_{1-x-y}\text{La}_x\text{Sr}_y\text{O}_{2-\delta}$	87
Fig. 4.13	DTA plots of all the CL7S4/LNCO nanocomposite powders	92
Fig. 4.14	XRD patterns of all the sintered powders: (a) CL7S4/35 LNCO (b) CL7S4/30 LNCO (c) CL7S4/20 LNCO and (d) CL7S4	93
Fig. 4.15	SEM micrograph of all the compositions (a) CL7S4: after polishing and thermal etching (b) CL7S4/20 LNCO: fractured sample (c) CL7S4/30 LNCO: fractured sample (d) CL7S4/35LNCO: fractured sample	95
Fig. 4.16	EDS spectrum of the composition CL7S4/35LNCO at two different points	96
Fig. 4.17	Thermal expansion curves for all the CL7S4/LNCO nanocomposites	97
Fig. 4.18	Complex plane impedance plots of the composition CL7S4/20LNCO at different temperatures	99
Fig. 4.19	Complex plane impedance plots of the composition CL7S4/30LNCO at different temperatures	102
Fig. 4.20	Complex plane impedance plots of the composition CL7S4/35LNCO at different temperatures	105
Fig. 4.21	Complex plane impedance plots of the composition LNCO at different temperatures	108
Fig. 4.22	Arrhenius plots of total conductivity for all the compositions	111
Fig. 4.23	Archie plot for the composite in the system CL7S4/LNCO	113
<b>Chapter V</b>	<b>La and Sr Co-Doped Ceria, <math>\text{Ce}_{0.85}\text{La}_{0.15-x}\text{Sr}_x\text{O}_{2-\delta}</math> and its Nanocomposites</b>	<b>116-159</b>
Fig. 5.1	Powder X-ray diffraction patterns of the sintered powders in the system $\text{Ce}_{0.85}\text{La}_{0.15-x}\text{Sr}_x\text{O}_{\{2-(0.075+x/2)\}}$ for (a) $x = 0.0$ , (b) $x = 0.025$ , (c) $x = 0.050$ and (d) $x = 0.075$	118
Fig. 5.2	Variation of lattice parameter with concentration of Sr in the system $\text{Ce}_{0.85}\text{La}_{0.15-x}\text{Sr}_x\text{O}_{\{2-(0.075+x/2)\}}$	119
Fig. 5.3	BFTEM images of the compositions (i) CLO15 (ii) CL125S025 (iii) CL10S5 (iv) CL075S075	121
Fig. 5.4	SEM micrographs of different compositions in the system $\text{Ce}_{0.85}\text{La}_{0.15-x}\text{Sr}_x\text{O}_{\{2-(0.075+x/2)\}}$ (a) CLO15 (b) CL125S025 (c) CL10S5 and (d) CL075S075	122
Fig. 5.5	EDS spectrum of the composition CL125S025 at three different points: (a) in the grain (b) at the grain boundary (c) at triple point	123

Fig. 5.6	Complex plane impedance plots of the composition CL125S025 at different temperatures	125
Fig. 5.7	Complex plane impedance plots of the composition CL10S5 at different temperatures	129
Fig. 5.8	Complex plane impedance plots of the composition CL075S075 at different temperatures	132
Fig. 5.9	Arrhenius plots for the grain, grain boundaries and total ionic conductivity in the system $\text{Ce}_{0.85}\text{La}_{0.15-x}\text{Sr}_x\text{O}_{\{2-(0.075+x/2)\}}$	136
Fig. 5.10	DTA plots of all the composite samples of CL125S025/LNCO	141
Fig. 5.11	Powder XRD patterns of various compositions (a)CL125S025 (b) CL125S025/20LNCO (c) CL125S025/30LNCO and (d) CL125S025/35LNCO sintered powders	142
Fig. 5.12	Thermal expansion curves for CL125S025/LNCO composites	143
Fig. 5.13	Scanning electron micrograph of all the fractured samples (a) CL125S025 (b) CL125S025/20LNCO (c) CL125S025/30LNCO and (d) CL125S025/35 LNCO	144
Fig. 5.14	EDS spectrum of the composition CL125S025/35LNCO at two different points	145
Fig. 5.15	Complex plane impedance plots of CL125S025/20LNCO at different temperatures	147
Fig. 5.16	Complex plane impedance plots of CL125S025/30LNCO at different temperatures	150
Fig. 5.17	Complex plane impedance plots of CL125S025/35LNCO at different temperatures	153
Fig. 5.18	Arrhenius plots of total conductivity for all the compositions	156
Fig. 5.19	Arhie plot of the system CL125S025/LNCO	158
<b>Chapter VI Sm and Sr Co-Doped Ceria and its Nanocomposites</b>	<b>160-205</b>	
Fig. 6.1	Powder XRD patterns of the sintered samples in the system $\text{Ce}_{1-x-y}\text{Sm}_x\text{Sr}_y\text{O}_{1.90}$ system with (a) SDC (b) 2SrSDC (c) 4SrSDC and (d) 6SrSDC	162
Fig. 6.2	Variation of lattice parameter with Sr content in the system $\text{Ce}_{1-x-y}\text{Sm}_x\text{Sr}_y\text{O}_{1.90}$	163
Fig. 6.3	SEM micrographs of thermally etched samples (a) SDC (b) 2SrSDC (c) 4SrSDC and (d) 6SrSDC	165
Fig. 6.4	EDS spectrum of the composition SDC at three different points	166
Fig. 6.5	EDS spectrum of the composition 2SrSDC at three different points	166

Fig. 6.6	Complex plane impedance plots of the composition SDC at different temperatures	168
Fig. 6.7	Complex plane impedance plots of the composition 2SrSDC at different temperatures	171
Fig. 6.8	Complex plane impedance plots of the composition 4SrSDC at different temperatures	174
Fig. 6.9	Complex plane impedance plots of the composition 6SrSDC at different temperatures	177
Fig. 6.10	Arrhenius plots for grains, grain boundaries and total conductivity of all the compositions in the system $\text{Ce}_{1-x-y}\text{Sm}_x\text{Sr}_y\text{O}_{1.90}$	182
Fig. 6.11	Plots of variation of activation energy with dopant concentration for $\text{Ce}_{1-x-y}\text{Sm}_x\text{Sr}_y\text{O}_{1.90}$ system	184
Fig. 6.12	DTA plots of all the samples in the system SSDC/LNCO	186
Fig. 6.13	Powder X-ray diffraction patterns of various compositions (a) Pure LNCO (b) SSDC (c) SSDC/20 LNCO (d) SSDC/30 LNCO (e) SSDC/35 LNCO	187
Fig. 6.14	Scanning electron micrograph of all the compositions (i) SSDC (ii) SSDC/20 LNCO (iii) SSDC/30 LNCO (iv) SSDC/35 LNCO	189
Fig. 6.15	EDS spectrum of the composition SSDC/35LNCO at two different points	190
Fig. 6.16	Thermal expansion curves for SSDC/LNCO composites	191
Fig. 6.17	Complex plane impedance plots of the composition SSDC/20LNCO at different temperatures	193
Fig. 6.18	Complex plane impedance plots of the composition SSDC/30 LNCO at different temperatures	196
Fig. 6.19	Complex plane impedance plots of the composition SSDC/35 LNCO at different temperatures	199
Fig. 6.20	Arrhenius plots of all the compositions in the system SSDC/LNCO	202
Fig. 6.21	Archie plot for SSDC/LNCO system	204
<b>Chapter VII</b>	<b>Ca and Sr co-doped ceria and its nanocomposites</b>	<b>206-248</b>
Fig. 7.1	DTA/TGA plots of the as prepared ash of composition CCO5	207
Fig. 7.2	Powder X-ray diffraction patterns of various compositions (a) CCO5 (b) CC5S2 (c) CC5S2 (d) CC5S3 sintered at 1350 °C	208
Fig. 7.3	SEM micrographs of various compositions (a) CCO5 (b) CC5S1 (c) CC5S2 (d) CC5S3 thermally etched at 1250 °C	210
Fig. 7.4	EDS spectrum of the composition CCO5 at three different points	211

Fig. 7.5	EDS spectrum of the composition CC5S2 at three different Points	211
Fig. 7.6	Complex plane impedance plots of the composition CCO5 at different temperatures	213
Fig. 7.7	Complex plane impedance plots of the composition CC5S1 at different temperatures	216
Fig. 7.8	Complex plane impedance plots of the composition CC5S2 at different temperatures	219
Fig. 7.9	Complex plane impedance plots of the composition CC5S3 at different temperatures	222
Fig. 7.10	Arrhenius plots of all the compositions in the system $\text{Ce}_{0.95-x}\text{Ca}_{0.05}\text{Sr}_x\text{O}_{1.95-x}$	226
Fig. 7.11	DTA plots of all the samples in the system CC5S2/LNCO	230
Fig. 7.12	Powder X-ray diffraction patterns of various compositions (a) CC5S2 (b) CC5S2 /20 LNCO (c) CC5S2 /30 LNCO and (d) CC5S2 /35LNCO	231
Fig. 7.13	Scanning electron micrograph of all the fractured samples (a) CC5S2 (b) CC5S2 /20 LNCO (c) CC5S2/30 LNCO and (d) CC5S2/35 LNCO	232
Fig. 7.14	EDS spectrum of the composition CC5S2/LNCO at two different points	233
Fig. 7.15	Thermal expansion curves for CC5S2/LNCO composites	234
Fig. 7.16	Complex plane impedance plots of the composition CC5S2/20LNCO at different temperatures	236
Fig. 7.17	Complex plane impedance plots of the composition CC5S2/30LNCO at different temperatures	239
Fig. 7.18	Complex plane impedance plots of the composition CC5S2/35LNCO at different temperatures	242
Fig. 7.19	Arrhenius plots of total conductivity for all the compositions	246
Fig. 7.20	Archie plot for the system CC5S2/LNCO	247
<b>Chapter VIII Mg and Sr co-doped ceria and its nanocomposites</b>		<b>249-297</b>
Fig. 8.1	Powder X-ray diffraction patterns of the sintered powders of compositions (a) CMO10 (b) CM8S2 (c) CM6S4 and (d) CM4S6 in the system $\text{Ce}_{0.90}\text{Mg}_{0.10-x}\text{Sr}_x\text{O}_{1.90}$	251
Fig. 8.2	SEM micrograph of the fractured samples in the system $\text{Ce}_{0.90}\text{Mg}_{0.10-x}\text{Sr}_x\text{O}_{1.90}$ for (a) CMO10 (b) CM8S2 (c) CM6S4 and (d) CM4S6	253

---

Fig. 8.3	EDX spectrum of the composition CMO10 at two different points: Spectrum 1 (in the grain) Spectrum 2 (at the grain boundary)	254
Fig. 8.4	EDX spectrum of the composition CM6S4 at two different points: (a) in the grain (b) at the grain boundary (c) at triple point	255
Fig. 8.5	Complex plane impedance plots of the composition CMO10 at different temperatures	257
Fig. 8.6	Complex plane impedance plots of the composition CM8S2 at different temperatures	261
Fig. 8.7	Complex plane impedance plots of the composition CM6S4 at different temperatures	265
Fig. 8.8	Complex plane impedance plots of the composition CM4S6 at different temperatures	269
Fig. 8.9	Arrhenius plots of all the compositions in the system $\text{Ce}_{0.90}\text{Mg}_{0.10-x}\text{Sr}_x\text{O}_{1.90}$	274
Fig. 8.10	DTA plots of all the composite samples (a) CM6S4/20LNCO (b) CM6S4/30LNCO and (c) CM6S4/35LNCO	279
Fig. 8.11	Powder X-ray diffraction patterns of all the compositions (a) CM6S4 (b) CM6S4/20 LNCO (c) CM6S4/30LNCO and (d) CM6S4/35LNCO	280
Fig. 8.12	Thermal expansion curves for CM6S4/LNCO composites	281
Fig. 8.13	SEM micrograph of all the sintered fractured samples (a) CM6S4 (b) CM6S4/20 LNCO (c) CM6S4/30 LNCO and (d) CM6S4/35 LNCO	282
Fig. 8.14	EDS spectrum of the composition CM6S4/35LNCO at two different points	283
Fig. 8.15	Complex plane impedance plots of the composition CM6S4/20LNCO at different temperatures	285
Fig. 8.16	Complex plane impedance plots of the composition CM6S4/30LNCO at different temperatures	288
Fig. 8.17	Complex plane impedance plots of the composition CM6S4/35LNCO at different temperatures	291
Fig. 8.18	Arrhenius plots of total conductivity for all the compositions	294
Fig. 8.19	Arhie plot for composites in the system CM6S4/LNCO	296