

References

- [1] A. F. Massardo, M. Santarelli, and R. Borchiellini, "Carbon exergy tax (CET): its impact on conventional energy system design and its contribution to advanced systems utilisation," *Energy*, 2003, vol. 28, no. 7, pp. 607–625.
- [2] G. P. Hammond, "Engineering sustainability: thermodynamics, energy systems, and the environment," *Int. J. Energy Res.*, 2004, vol. 28, no. 7, pp. 613–639.
- [3] E. Sciubba, "Exergo-economics: thermodynamic foundation for a more rational resource use," *Int. J. Energy Res.*, 2005, vol. 29, no. 7, pp. 613–636.
- [4] Q. Bao, T. Honda, S. El Ferik, M. M. Shaukat, and M. C. Yang, "Understanding the role of visual appeal in consumer preference for residential solar panels," *Renew. Energy*, 2017, vol. 113, pp. 1569–1579.
- [5] A. J. Appleby, "Fuel cell technology: Status and future prospects," *Energy*, 1996, vol. 21, no. 7–8, pp. 521–653.
- [6] N. Q. Minh, "Ceramic Fuel Cells," *J. Am. Ceram. Soc.*, 1993, vol. 76, no. 3, pp. 563–588.
- [7] W. R. Grove, "XXIV. On voltaic series and the combination of gases by platinum," London, Edinburgh, *Dublin Philos. Mag. J. Sci.*, 1839, vol. 14, no. 86–87, pp. 127–130.
- [8] W. Reitz, "Handbook of Fuel Cells: Fundamentals, Technology, and Applications , (Volume 1) W. Vielstich, A. Lamm, and H. A. Gasteiger (editors)," *Mater. Manuf. Process.*, 2007, vol. 22, no. 6, pp. 788–788.
- [9] A. J. Appleby, "Fuel cells and hydrogen fuel," *Int. J. Hydrogen Energy*, 1994, vol. 19, no. 2, pp. 175–180.
- [10] A. B. Stambouli and E. Traversa, "Solid oxide fuel cells (SOFCs): a review of an environmentally clean and efficient source of energy," *Renew. Sustain. Energy*

- Rev.*, 2002, vol. 6, no. 5, pp. 433–455.
- [11] T. Elmer, M. Worall, S. Wu, and S. B. Riffat, “Fuel cell technology for domestic built environment applications: State of-the-art review,” *Renew. Sustain. Energy Rev.*, 2015, vol. 42, pp. 913–931.
- [12] P. Kalra, R. Garg, and A. Kumar, “Solid Oxide Fuel Cell - A Future Source of Power and Heat Generation,” *Mater. Sci. Forum*, 2013, vol. 757, pp. 217–241.
- [13] C. O. Colpan, Y. Nalbant, and M. Ercelik, “4.28 Fundamentals of Fuel Cell Technologies,” in *Comprehensive Energy Systems, Com. Energy Systems*, 2018, pp. 1107–1130.
- [14] F. S. da Silva and T. M. de Souza, “Novel materials for solid oxide fuel cell technologies: A literature review,” *Int. J. Hydrogen Energy*, 2017, vol. 42, no. 41, pp. 26020–26036.
- [15] B. C. H. Steele and A. Heinzl, “Materials for fuel-cell technologies,” *Nature*, 2001, vol. 414, no. 6861, pp. 345–352.
- [16] Y. Mizutani, M. Tamura, M. Kawai, and O. Yamamoto, “Development of high-performance electrolyte in SOFC,” *Solid State Ionics*, 1994, vol. 72, pp. 271–275.
- [17] S. P. S. Badwal and K. Foger, “Solid oxide electrolyte fuel cell review,” *Ceram. Int.*, 1996, vol. 22, no. 3, pp. 257–265.
- [18] M. Hrovat, “Characterisation of $\text{LaNi}_{1-x}\text{Co}_x\text{O}_3$ as a possible SOFC cathode material,” *Solid State Ionics*, 1996, vol. 83, no. 1–2, pp. 99–105.
- [19] S. M. Haile, “Fuel cell materials and components***The Golden Jubilee Issue- Selected topics in Materials Science and Engineering: Past, Present and Future, edited by S. Suresh.,” *Acta Mater.*, 2003, vol. 51, no. 19, pp. 5981–6000.
- [20] J. Wu and X. Liu, “Recent Development of SOFC Metallic Interconnect,” *J. Mater. Sci. Technol.*, 2010, vol. 26, no. 4, pp. 293–305.

- [21] X. Zhou, N. Yan, K. T. Chuang, and J. Luo, "Progress in La-doped SrTiO₃ (LST)-based anode materials for solid oxide fuel cells," *RSC Adv.*, 2014, vol. 4, no. 1, pp. 118–131.
- [22] J. J. Alvarado Flores, M. L. Ávalos Rodríguez, G. Andrade Espinosa, and J. V. Alcaraz Vera, "Advances in the development of titanates for anodes in SOFC," *Int. J. Hydrogen Energy*, 2018, pp. 1-14.
- [23] S. P. S. Shaikh, A. Muchtar, and M. R. Somalu, "A review on the selection of anode materials for solid-oxide fuel cells," *Renew. Sustain. Energy Rev.*, 2015, vol. 51, pp. 1–8.
- [24] E. Grabowska, "Selected perovskite oxides: Characterization, preparation and photocatalytic properties-A review," *Appl. Catal. B Environ.*, 2016, vol. 186, pp. 97–126.
- [25] V. M. Goldschmidt, "Die Gesetze der Krystallochemie," *Naturwissenschaften*, 1926, vol. 14, no. 21, pp. 477–485.
- [26] A. S. Bhalla, R. Guo, and R. Roy, "The perovskite structure-a review of its role in ceramic science and technology," *Mater. Res. Innov.*, 2000, vol. 4, no. 1, pp. 3–26.
- [27] S. Chauhan, M. Kumar, S. Chhoker, and S. C. Katyal, "A comparative study on structural, vibrational, dielectric and magnetic properties of microcrystalline BiFeO₃, nanocrystalline BiFeO₃ and core-shell structured BiFeO₃@SiO₂ nanoparticles," *J. Alloys Compd.*, 2016, vol. 666, pp. 454–467.
- [28] Z. X. Chen, Y. Chen, and Y. S. Jiang, "Comparative Study of ABO₃ Perovskite Compounds. 1. ATiO₃ (A = Ca, Sr, Ba, and Pb) Perovskites," *J. Phys. Chem. B*, 2002, vol. 106, no. 39, pp. 9986–9992.
- [29] A. Rocca, A. Licciulli, M. Politi, and D. Diso, "Rare Earth-Doped SrTiO₃ Perovskite Formation from Xerogels," *ISRN Ceram.*, 2012, vol. 2012, pp. 1–6.

- [30] P. Kanhere and Z. Chen, “A Review on Visible Light Active Perovskite-Based Photocatalysts,” *Molecules*, 2014, vol. 19, no. 12, pp. 19995–20022.
- [31] C. Xu, D. Lin, and K. W. Kwok, “Structure, electrical properties and depolarization temperature of $(\text{Bi}_{0.5}\text{Na}_{0.5})\text{TiO}_3\text{--BaTiO}_3$ lead-free piezoelectric ceramics,” *Solid State Sci.*, 2008, vol. 10, no. 7, pp. 934–940.
- [32] K. H. L. Zhang et al., “Perovskite Sr-Doped LaCrO_3 as a New p-Type Transparent Conducting Oxide,” *Adv. Mater.*, 2015, vol. 27, no. 35, pp. 5191–5195.
- [33] I. Riess, “Mixed ionic–electronic conductors-material properties and applications,” *Solid State Ionics*, 2003, vol. 157, no. 1–4, pp. 1–17.
- [34] C. Pijolat, “Screen-printing for the fabrication of solid oxide fuel cells (SOFC),” in *Printed Films*, Elsevier, 2012, pp. 469–495.
- [35] V. Kharton and F. M. Marques, “Mixed ionic–electronic conductors: effects of ceramic microstructure on transport properties,” *Curr. Opin. Solid State Mater. Sci.*, 2002, vol. 6, no. 3, pp. 261–269.
- [36] R. Moos and K. H. Härdtl, “Electronic transport properties of $\text{Sr}_{1-x}\text{La}_x\text{TiO}_3$ ceramics,” *J. Appl. Phys.*, 1996, vol. 80, no. 1, pp. 393–400.
- [37] X. Li, H. Zhao, X. Zhou, N. Xu, Z. Xie, and N. Chen, “Electrical conductivity and structural stability of La-doped SrTiO_3 with A-site deficiency as anode materials for solid oxide fuel cells,” *Int. J. Hydrogen Energy*, 2010, vol. 35, no. 15, pp. 7913–7918.
- [38] S. Hui and A. Petric, “Electrical Properties of Yttrium-Doped Strontium Titanate under Reducing Conditions,” *J. Electrochem. Soc.*, 2002, vol. 149, no. 1, p. J1.
- [39] F. J. Lepe, J. Fernández-Urbán, L. Mestres, and M. L. Martínez-Sarrión, “Synthesis and electrical properties of new rare-earth titanium perovskites for SOFC anode applications,” *J. Power Sources*, 2005, vol. 151, pp. 74–78.

- [40] F. Gao, H. Zhao, X. Li, Y. Cheng, X. Zhou, and F. Cui, "Preparation and electrical properties of yttrium-doped strontium titanate with B-site deficiency," *J. Power Sources*, 2008, vol. 185, no. 1, pp. 26–31.
- [41] H. Zhao, F. Gao, X. Li, C. Zhang, and Y. Zhao, "Electrical properties of yttrium doped strontium titanate with A-site deficiency as potential anode materials for solid oxide fuel cells," *Solid State Ionics*, 2009, vol. 180, no. 2–3, pp. 193–197.
- [42] S. Maletic, D. Popovic, and J. Dojcilovic, "Dielectric measurements, Raman scattering and surface studies of Sm-doped SrTiO₃ single crystal," *J. Alloys Compd.*, 2010, vol. 496, no. 1–2, pp. 388–392.
- [43] T. Kolodiazhnyi and A. Petric, "The Applicability of Sr-deficient n-type SrTiO₃ for SOFC Anodes," *J. Electroceramics*, 2005, vol. 15, no. 1, pp. 5–11.
- [44] S. McIntosh and R. J. Gorte, "Direct Hydrocarbon Solid Oxide Fuel Cells," *Chem. Rev.*, 2004, vol. 104, no. 10, pp. 4845–4866.
- [45] G. Pudmich, "Chromite/titanate based perovskites for application as anodes in solid oxide fuel cells," *Solid State Ionics*, 2000, vol. 135, no. 1–4, pp. 433–438.
- [46] J. Lee, "Quantitative analysis of microstructure and its related electrical property of SOFC anode, Ni–YSZ cermet," *Solid State Ionics*, 2002, vol. 148, no. 1–2, pp. 15–26.
- [47] M. A. Haldane and T. H. Etsell, "Fabrication of composite SOFC anodes," *Mater. Sci. Eng. B*, 2005, vol. 121, no. 1–2, pp. 120–125.
- [48] B. C. H. Steele and R. M. Dell, "Materials for High-Temperature Fuel Cells [and Discussion]," *Philos. Trans. R. Soc. A Math. Phys. Eng. Sci.*, 1996, vol. 354, no. 1712, pp. 1695–1710.
- [49] R. Bove and S. Ubertini, "Modeling solid oxide fuel cell operation: Approaches, techniques and results," *J. Power Sources*, 2006, vol. 159, no. 1, pp. 543–559.

- [50] M. R. Pillai, I. Kim, D. M. Bierschenk, and S. A. Barnett, "Fuel-flexible operation of a solid oxide fuel cell with $\text{Sr}_{0.8}\text{La}_{0.2}\text{TiO}_3$ support," *J. Power Sources*, 2008, vol. 185, no. 2, pp. 1086–1093.
- [51] S. C. Singhal, "Solid oxide fuel cells for power generation," *Wiley Interdiscip. Rev. Energy Environ.*, 2014, vol. 3, no. 2, pp. 179–194.
- [52] S. Linderoth and A. Smith, "Worldwide SOFC Overview from a Scandinavian and a European Perspective," in *Advances in Solid Oxide Fuel Cells III*, Hoboken, NJ, USA: *John Wiley & Sons, Inc.*, 2009, pp. 1–13.
- [53] S. de Souza, "Reduced-Temperature Solid Oxide Fuel Cell Based on YSZ Thin-Film Electrolyte," *J. Electrochem. Soc.*, 1997, vol. 144, no. 3, p. L35.
- [54] J. Maček, B. Novosel, and M. Marinšek, "Ni–YSZ SOFC anodes—Minimization of carbon deposition," *J. Eur. Ceram. Soc.*, 2007, vol. 27, no. 2–3, pp. 487–491.
- [55] A. Atkinson et al., "Advanced anodes for high-temperature fuel cells," *Nat. Mater.*, 2004, vol. 3, no. 1, pp. 17–27.
- [56] J. Sfeir, J. van herle, and A. J. McEvoy, "Stability of calcium substituted lanthanum chromites used as SOFC anodes for methane oxidation," *J. Eur. Ceram. Soc.*, 1999, vol. 19, no. 6–7, pp. 897–902.
- [57] S. Zha, P. Tsang, Z. Cheng, and M. Liu, "Electrical properties and sulfur tolerance of $\text{La}_{0.75}\text{Sr}_{0.25}\text{Cr}_{1-x}\text{Mn}_x\text{O}_3$ under anodic conditions," *J. Solid State Chem.*, 2005, vol. 178, no. 6, pp. 1844–1850.
- [58] R. Mukundan, E. L. Brosha, and F. H. Garzon, "Sulfur Tolerant Anodes for SOFCs," *Electrochem. Solid-State Lett.*, 2004, vol. 7, no. 1, p. A5.
- [59] P. R. Slater, D. P. Fagg, and J. T. S. Irvine, "Synthesis and electrical characterisation of doped perovskite titanates as potential anode materials for solid oxide fuel cells," *J. Mater. Chem.*, 1997, vol. 7, no. 12, pp. 2495–2498.

- [60] Q. X. Fu, F. Tietz, and D. Stöver, “La_{0.4}Sr_{0.6}Ti_{1-x}Mn_xO_{3-δ} Perovskites as Anode Materials for Solid Oxide Fuel Cells,” *J. Electrochem. Soc.*, 2006, vol. 153, no. 4, p. D74.
- [61] J. R. Petrie, H. Jeen, S. C. Barron, T. L. Meyer, and H. N. Lee, “Enhancing Perovskite Electrocatalysis through Strain Tuning of the Oxygen Deficiency,” *J. Am. Chem. Soc.*, 2016, vol. 138, no. 23, pp. 7252–7255.
- [62] C. Sun and U. Stimming, “Recent anode advances in solid oxide fuel cells,” *J. Power Sources*, 2007, vol. 171, no. 2, pp. 247–260.
- [63] M. Singh, D. Kumar, and A. K. Singh, “Synthesis and structural studies on cerium substituted La_{0.4}Ca_{0.6}MnO₃ as solid oxide fuel cell electrode material,” 2018, p. 140068.
- [64] A. Trovarelli, “Catalytic Properties of Ceria and CeO₂-Containing Materials,” *Catal. Rev.*, 1996, vol. 38, no. 4, pp. 439–520.
- [65] Q. Fu, F. Tietz, D. Sebold, S. Tao, and J. T. S. Irvine, “An efficient ceramic-based anode for solid oxide fuel cells,” *J. Power Sources*, 2007, vol. 171, no. 2, pp. 663–669.
- [66] O. Marina, “Thermal, electrical, and electrocatalytical properties of lanthanum-doped strontium titanate,” *Solid State Ionics*, 2002, vol. 149, no. 1–2, pp. 21–28.
- [67] S. Hui, “Conductivity and stability of SrVO₃ and mixed perovskites at low oxygen partial pressures,” *Solid State Ionics*, 2001, vol. 143, no. 3–4, pp. 275–283.
- [68] D. Marrero-López, J. Peña-Martínez, J. C. Ruiz-Morales, D. Pérez-Coll, M. A. G. Aranda, and P. Núñez, “Synthesis, phase stability and electrical conductivity of Sr₂MgMoO_{6-δ} anode,” *Mater. Res. Bull.*, 2008, vol. 43, no. 8–9, pp. 2441–2450.
- [69] L. Yang, L. C. De Jonghe, C. P. Jacobsen, and S. J. Visco, “B-Site Doping and Catalytic Activity of Sr(Y)TiO₃,” *J. Electrochem. Soc.*, 2007, vol. 154, no. 9, p.

- B949.
- [70] C. D. Savaniu and J. T. S. Irvine, "Reduction studies and evaluation of surface modified A-site deficient La-doped SrTiO₃ as anode material for IT-SOFCs," *J. Mater. Chem.*, 2009, vol. 19, no. 43, p. 8119.
- [71] P. E. Mason, L. I. Darvell, J. M. Jones, and A. Williams, "Comparative Study of the Thermal Conductivity of Solid Biomass Fuels," *Energy & Fuels*, 2016, vol. 30, no. 3, pp. 2158–2163.
- [72] Z. Xie, H. Zhao, T. Chen, X. Zhou, and Z. Du, "Synthesis and electrical properties of Al-doped Sr₂MgMoO_{6-δ} as an anode material for solid oxide fuel cells," *Int. J. Hydrogen Energy*, 2011, vol. 36, no. 12, pp. 7257–7264.
- [73] S. P. Jiang, L. Liu, K. P. Ong, P. Wu, J. Li, and J. Pu, "Electrical conductivity and performance of doped LaCrO₃ perovskite oxides for solid oxide fuel cells," *J. Power Sources*, 2008, vol. 176, no. 1, pp. 82–89.
- [74] N. Mahato, A. Banerjee, A. Gupta, S. Omar, and K. Balani, "Progress in material selection for solid oxide fuel cell technology: A review," *Prog. Mater. Sci.*, 2015, vol. 72, pp. 141–337.
- [75] J. Kilner and C. Waters, "The effects of dopant cation-oxygen vacancy complexes on the anion transport properties of non-stoichiometric fluorite oxides," *Solid State Ionics*, 1982, vol. 6, no. 3, pp. 253–259.
- [76] T. Ishihara, Ed., "Perovskite Oxide for Solid Oxide Fuel Cells", Boston, MA: Springer US, 2009.
- [77] A. Kulkarni et al., "Mixed ionic electronic conducting perovskite anode for direct carbon fuel cells," *Int. J. Hydrogen Energy*, 2012, vol. 37, no. 24, pp. 19092–19102.
- [78] M. T. Buscaglia, M. Viviani, V. Buscaglia, C. Bottino, and P. Nanni,

- “Incorporation of Er^{3+} into BaTiO_3 ,” *J. Am. Ceram. Soc.*, 2002, vol. 85, no. 6, pp. 1569–1575.
- [79] S. T. Aruna and A. S. Mukasyan, “Combustion synthesis and nanomaterials,” *Curr. Opin. Solid State Mater. Sci.*, 2008, vol. 12, no. 3–4, pp. 44–50.
- [80] L. L. Hench and J. K. West, “The sol-gel process,” *Chem. Rev.*, 1990, vol. 90, no. 1, pp. 33–72.
- [81] F. Deganello, G. Marci, and G. Deganello, “Citrate-nitrate auto-combustion synthesis of perovskite-type nanopowders: A systematic approach,” *J. Eur. Ceram. Soc.*, 2009, vol. 29, no. 3, pp. 439–450.
- [82] G. . Williamson and W. . Hall, “X-ray line broadening from filed aluminium and wolfram,” *Acta Metall.*, 1953, vol. 1, no. 1, pp. 22–31.
- [83] X. Zhou et al., “XRD-based quantitative analysis of clay minerals using reference intensity ratios, mineral intensity factors, Rietveld, and full pattern summation methods: A critical review,” *Solid Earth Sci.*, 2018, vol. 3, no. 1, pp. 16–29.
- [84] H. M. Rietveld, “Line profiles of neutron powder-diffraction peaks for structure refinement,” *Acta Crystallogr.*, 1967, vol. 22, no. 1, pp. 151–152.
- [85] H. M. Rietveld, “A profile refinement method for nuclear and magnetic structures,” *J. Appl. Crystallogr.*, 1969, vol. 2, no. 2, pp. 65–71.
- [86] J. Rodriguez-Carvajal, M. T. Fernandez-Diaz, and J. L. Martinez, “Neutron diffraction study on structural and magnetic properties of La_2NiO_4 ,” *J. Phys. Condens. Matter*, 1991, vol. 3, no. 19, pp. 3215–3234.
- [87] C. P. Khattak and D. E. Cox, “Profile analysis of X-ray powder diffractometer data: structural refinement of $\text{La}_{0.75}\text{Sr}_{0.25}\text{CrO}_3$,” *J. Appl. Crystallogr.*, 1977, vol. 10, no. 5, pp. 405–411.
- [88] S. K. Satpathy, N. K. Mohanty, A. K. Behera, B. Behera, and P. Nayak, “Electrical

- conductivity of Gd doped BiFeO₃-PbZrO₃ composite,” *Front. Mater. Sci.*, 2013, vol. 7, no. 3, pp. 295–301.
- [89] Raghvendra, R. K. Singh, and P. Singh, “Electrical conductivity of barium substituted LSGM electrolyte materials for IT-SOFC,” *Solid State Ionics*, 2014, vol. 262, pp. 428–432.
- [90] A. K. Jonscher, “Dielectric relaxation in solids,” *J. Phys. D. Appl. Phys.*, 1999, vol. 32, no. 14, pp. R57–R70.
- [91] I. M. Hodge, M. D. Ingram, and A. R. West, “Impedance and modulus spectroscopy of polycrystalline solid electrolytes,” *J. Electroanal. Chem. Interfacial Electrochem.*, 1976, vol. 74, no. 2, pp. 125–143.
- [92] N. Hirose and A. R. West, “Impedance Spectroscopy of Undoped BaTiO₃ Ceramics,” *J. Am. Ceram. Soc.*, 1996, vol. 79, no. 6, pp. 1633–1641.
- [93] R. Gerhardt, “Impedance and dielectric spectroscopy revisited: Distinguishing localized relaxation from long-range conductivity,” *J. Phys. Chem. Solids*, 1994, vol. 55, no. 12, pp. 1491–1506.
- [94] A. Feltz, “Perovskite forming ceramics of the system Sr_xLa_{1-x}Ti^{IV}_{x+y}Co^{II}_yCo^{III}_{1-x-2y}O₃ for NTC thermistor applications,” *J. Eur. Ceram. Soc.*, 2000, vol. 20, no. 14–15, pp. 2367–2376.
- [95] W. Mason and R. Wick, “Ferroelectrics and the Dielectric Amplifier,” *Proc. IRE*, 1954, vol. 42, no. 11, pp. 1606–1620.
- [96] K. Preis, O. Biro, P. Supancic, and I. Ticar, “FEM simulation of thermistors including dielectric effects,” *IEEE Trans. Magn.*, 2003, vol. 39, no. 3, pp. 1733–1736.
- [97] A. K. Rai, N. K. Singh, S. K. Acharya, L. Singh, and K. D. Mandal, “Effect of tantalum substitutions on microstructures and dielectric properties of calcium

- copper titanate ($\text{CaCu}_3\text{Ti}_4\text{O}_{12}$) ceramic,” *Mater. Sci. Eng. B*, 2012, vol. 177, no. 14, pp. 1213–1218.
- [98] A. R. West, T. B. Adams, F. D. Morrison, and D. C. Sinclair, “Novel high capacitance materials:- $\text{BaTiO}_3\text{:La}$ and $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$,” *J. Eur. Ceram. Soc.*, 2004, vol. 24, no. 6, pp. 1439–1448.
- [99] M. Viviani, M. . Buscaglia, V. Buscaglia, M. Leoni, and P. Nanni, “Barium perovskites as humidity sensing materials,” *J. Eur. Ceram. Soc.*, 2001, vol. 21, no. 10–11, pp. 1981–1984.
- [100] M. . Post, J. . Tunney, D. Yang, X. Du, and D. . Singleton, “Material chemistry of perovskite compounds as chemical sensors,” *Sensors Actuators B Chem.*, 1999, vol. 59, no. 2–3, pp. 190–194.
- [101] B. C. H. Steele and A. Heinzl, “Materials for fuel-cell technologies,” in *Materials for Sustainable Energy*, Co-Published with Macmillan Publishers Ltd, UK, 2010, pp. 224–231.
- [102] J. H. Kim, Y. Kim, P. A. Connor, J. T. S. Irvine, J. Bae, and W. Zhou, “Structural, thermal and electrochemical properties of layered perovskite $\text{SmBaCo}_2\text{O}_{5+d}$, a potential cathode material for intermediate-temperature solid oxide fuel cells,” *J. Power Sources*, 2009, vol. 194, no. 2, pp. 704–711.
- [103] S. L. and W. K. R. Uvic, K. Tolman, K. Chan, N. Lundy, “The Effect of A-Site Vacancies on Cell Volume and Tolerance Factor of Perovskites,” *John Wiley Sons*, Book, pp. 331–336, 2013.
- [104] K. Singh, J. Nowotny, and V. Thangadurai, “Amphoteric oxide semiconductors for energy conversion devices: a tutorial review,” *Chem. Soc. Rev.*, 2013, vol. 42, no. 5, pp. 1961–1972.
- [105] H. Muta, K. Kurosaki, and S. Yamanaka, “Thermoelectric properties of reduced

- and La-doped single-crystalline SrTiO₃,” *J. Alloys Compd.*, 2005, vol. 392, no. 1–2, pp. 306–309.
- [106] X. Liu, R. Hong, and C. Tian, “Tolerance factor and the stability discussion of ABO₃-type ilmenite,” *J. Mater. Sci. Mater. Electron.*, 2009, vol. 20, no. 4, pp. 323–327.
- [107] K. Uematsu, O. Sakurai, N. Mizutani, and M. Kato, “Electrical properties of La-doped SrTiO₃ (La: 0.1 to 2.0 at %) single crystals grown by xenon-arc image floating zone method,” *J. Mater. Sci.*, 1984, vol. 19, no. 11, pp. 3671–3679.
- [108] A. Rubano, D. Paparo, F. M. Granozio, U. Scotti di Uccio, and L. Marrucci, “Blue luminescence of SrTiO₃ under intense optical excitation,” *J. Appl. Phys.*, 2009, vol. 106, no. 10, p. 103515.
- [109] K. Fuji-ta, T. Katsura, and Y. Tainosho, “Electrical conductivity measurement of granulite under mid- to lower crustal pressure-temperature conditions,” *Geophys. J. Int.*, 2004, vol. 157, no. 1, pp. 79–86.
- [110] S. A. Howard, J. K. Yau, and H. U. Anderson, “Structural characteristics of Sr_{1-x}La_xTi_{3+δ} as a function of oxygen partial pressure at 1400 °C,” *J. Appl. Phys.*, 1989, vol. 65, no. 4, pp. 1492–1498.
- [111] U. Balachandran and N. G. Eror, “Solubility of Lanthanum in Strontium Titanate,” *J. Am. Ceram. Soc.*, 1981, vol. 64, no. 4, pp. 75-76.
- [112] R. D. Shannon, “Revised effective ionic radii and systematic studies of interatomic distances in halides and chalcogenides,” *Acta Crystallogr. Sect. A*, 1976, vol. 32, no. 5, pp. 751–767.
- [113] K. Gömann, G. Borchardt, A. Gunhold, W. Maus-Friedrichs, and H. Baumann, “Ti diffusion in La-doped SrTiO₃ single crystals,” *Phys. Chem. Chem. Phys.*, 2004, vol. 6, no. 13, pp. 3639–3644.

- [114] Q. Ma, F. Tietz, and D. Stöver, “Nonstoichiometric Y-substituted SrTiO₃ materials as anodes for solid oxide fuel cells,” *Solid State Ionics*, 2011, vol. 192, no. 1, pp. 535–539.
- [115] B. F. Flandermeyer, A. K. Agarwal, H. U. Anderson, and M. M. Nasrallah, “Oxidation-reduction behaviour of La-doped SrTiO₃,” *J. Mater. Sci.*, 1984, vol. 19, no. 8, pp. 2593–2598.
- [116] S. Hashimoto, F. W. Poulsen, and M. Mogensen, “Conductivity of SrTiO₃ based oxides in the reducing atmosphere at high temperature,” *J. Alloys Compd.*, 2007, vol. 439, no. 1–2, pp. 232–236.
- [117] D. Almond, G. Duncan, and A. West, “The determination of hopping rates and carrier concentrations in ionic conductors by a new analysis of ac conductivity,” *Solid State Ionics*, 1983, vol. 8, no. 2, pp. 159–164.
- [118] D. Almond and A. West, “Mobile ion concentrations in solid electrolytes from an analysis of a.c. conductivity,” *Solid State Ionics*, 1983, vol. 9–10, pp. 277–282.
- [119] D. P. Almond, C. C. Hunter, and A. R. West, “The extraction of ionic conductivities and hopping rates from a.c. conductivity data,” *J. Mater. Sci.*, 1984, vol. 19, no. 10, pp. 3236–3248.
- [120] P. Singh, O. Parkash, and D. Kumar, “Electrical conduction behaviour of perovskite oxide system BaSnNbO,” *Solid State Ionics*, 2005, vol. 176, no. 25–28, pp. 2167–2170.
- [121] P. Singh, O. Parkash, and D. Kumar, “DC conduction behaviour of niobium doped barium stannate,” *J. Mater. Sci. Mater. Electron.*, 2005, vol. 16, no. 3, pp. 145–148.
- [122] S. R. Elliott, “A.c. conduction in amorphous chalcogenide and pnictide semiconductors,” *Adv. Phys.*, 1987, vol. 36, no. 2, pp. 135–217.

- [123] A. Janotti, J. B. Varley, M. Choi, and C. G. Van de Walle, “Vacancies and small polarons in SrTiO₃,” *Phys. Rev. B*, 2014, vol. 90, no. 8, p. 85202.
- [124] W. S. Choi, H. K. Yoo, and H. Ohta, “Polaron Transport and Thermoelectric Behavior in La-Doped SrTiO₃ Thin Films with Elemental Vacancies,” *Adv. Funct. Mater.*, 2015, vol. 25, no. 5, pp. 799–804.
- [125] A. Ghosh and M. Sural, “Conductivity spectra of sodium fluorozirconate glasses,” *J. Chem. Phys.*, 2001, vol. 114, no. 7, pp. 3243–3247.
- [126] A. Ghosh and A. Pan, “Scaling of the Conductivity Spectra in Ionic Glasses: Dependence on the Structure,” *Phys. Rev. Lett.*, 2000, vol. 84, no. 10, pp. 2188–2190.
- [127] O. N. Verma, N. K. Singh, R. Raghvendra, and P. Singh, “Study of ion dynamics in lanthanum aluminate probed by conductivity spectroscopy,” *RSC Adv.*, 2015, vol. 5, no. 28, pp. 21614–21619.
- [128] D. L. Sidebottom, “Dimensionality Dependence of the Conductivity Dispersion in Ionic Materials,” *Phys. Rev. Lett.*, 1999, vol. 83, no. 5, pp. 983–986.
- [129] O. Raymond, R. Font, N. Suárez-Almodovar, J. Portelles, and J. M. Siqueiros, “Frequency-temperature response of ferroelectromagnetic Pb(Fe_{1/2}Nb_{1/2})O₃ ceramics obtained by different precursors. Part I. Structural and thermo-electrical characterization,” *J. Appl. Phys.*, 2005, vol. 97, no. 8, p. 84107.
- [130] Q. Ke, X. Lou, Y. Wang, and J. Wang, “Oxygen-vacancy-related relaxation and scaling behaviors of Bi_{0.9}La_{0.1}Fe_{0.98}Mg_{0.02}O₃ (La, Mg-codoped BiFeO₃) ferroelectric thin film,” *Phys. Rev. B*, 2010, vol. 82, no. 2, p. 24102.
- [131] R. Tang et al., “Dielectric relaxation, resonance and scaling behaviors in Sr₃Co₂Fe₂₄O₄₁ hexaferrite,” *Sci. Rep.*, 2015, vol. 5, no. 1, p. 13645.
- [132] E. Longo et al., “Density functional theory calculation of the electronic structure of

- Ba_{0.5}Sr_{0.5}TiO₃: Photoluminescent properties and structural disorder,” *Phys. Rev. B*, 2004, vol. 69, no. 12, p. 125115.
- [133] S. G. Lu et al., “Time-resolved photoluminescence of barium titanate ultrafine powders,” *J. Appl. Phys.*, 2006, vol. 99, no. 6, p. 64103.
- [134] R. Pązik, D. Hreniak, W. Stręk, A. Speghini, and M. Bettinelli, “Structural and luminescence properties of Eu³⁺ doped Ba_xSr_{1-x}TiO₃ (BST) nanocrystalline powders prepared by different methods,” *Opt. Mater. (Amst.)*, 2006, vol. 28, no. 11, pp. 1284–1288.
- [135] T. Hasegawa, M. Shirai, and K. Tanaka, “Localizing nature of photo-excited states in SrTiO₃,” *J. Lumin.*, 2000, vol. 87–89, pp. 1217–1219.
- [136] H. Okamura et al., “Photogenerated Carriers in SrTiO₃ Probed by Mid-Infrared Absorption,” *J. Phys. Soc. Japan*, 2006, vol. 75, no. 2, p. 23703.
- [137] L. M. Prócel, F. Tipán, and A. Stashans, “Mott-Wannier excitons in the tetragonal BaTiO₃ lattice,” *Int. J. Quantum Chem.*, 2003, vol. 91, no. 4, pp. 586–590.
- [138] W. F. Zhang, Z. Yin, M. S. Zhang, Z. L. Du, and W. C. Chen, “Roles of defects and grain sizes in photoluminescence of nanocrystalline SrTiO₃,” *J. Phys. Condens. Matter*, 1999, vol. 11, no. 29, pp. 5655–5660.
- [139] D. Emin, “Polarons,” Cambridge Univ. Press Cambridge, U.K, Book, 2013.
- [140] S. Shimomura, N. Wakabayashi, H. Kuwahara, and Y. Tokura, “X-Ray Diffuse Scattering due to Polarons in a Colossal Magnetoresistive Manganite,” *Phys. Rev. Lett.*, 1999, vol. 83, no. 21, pp. 4389–4392.
- [141] T. Suzuki, I. Kosacki, H. U. Anderson, and P. Colomban, “Electrical Conductivity and Lattice Defects in Nanocrystalline Cerium Oxide Thin Films,” *J. Am. Ceram. Soc.*, 2004, vol. 84, no. 9, pp. 2007–2014.
- [142] J. Sunarso, S. S. Hashim, N. Zhu, and W. Zhou, “Perovskite oxides applications in

- high temperature oxygen separation, solid oxide fuel cell and membrane reactor: A review,” *Prog. Energy Combust. Sci.*, 2017, vol. 61, pp. 57–77.
- [143] M. C. Verbraeken et al., “Modified strontium titanates: from defect chemistry to SOFC anodes,” *RSC Adv.*, 2015, vol. 5, no. 2, pp. 1168–1180.
- [144] Q. Ma, B. Iwanschitz, E. Dashjav, A. Mai, F. Tietz, and H. P. Buchkremer, “Electrochemical performance and stability of electrolyte-supported solid oxide fuel cells based on Y-substituted SrTiO₃ ceramic anodes,” *Solid State Ionics*, 2014, vol. 262, pp. 465–468.
- [145] A. Torabi and T. H. Etsell, “Electrochemical behavior of solid oxide fuel cell anodes based on infiltration of Y-doped SrTiO₃,” *J. Power Sources*, 2013, vol. 225, pp. 51–59.
- [146] P. Puengjinda, H. Muroyama, T. Matsui, and K. Eguchi, “Stability of solid oxide fuel cell anodes based on YST–SDC composite with Ni catalyst,” *J. Power Sources*, 2012, vol. 216, pp. 409–416.
- [147] X. Li, H. Zhao, F. Gao, Z. Zhu, N. Chen, and W. Shen, “Synthesis and electrical properties of Co-doped Y_{0.08}Sr_{0.92}TiO_{3-δ} as a potential SOFC anode,” *Solid State Ionics*, 2008, vol. 179, no. 27–32, pp. 1588–1592.
- [148] R. L. Snyder, “The Use of Reference Intensity Ratios in X-Ray Quantitative Analysis,” *Powder Diffr.*, 1992, vol. 7, no. 4, pp. 186–193.
- [149] K. C. Chen, E. J. Peterson, and D. J. Thoma, “HfCo₂ Laves phase intermetallics-part I: solubility limits and defect mechanisms,” *Intermetallics*, 2001, vol. 9, no. 9, pp. 771–783.
- [150] D. J. Cumming, J. A. Kilner, and S. Skinner, “Structural properties of Ce-doped strontium titanate for fuel cell applications,” *J. Mater. Chem.*, 2011, vol. 21, no. 13, p. 5021.

- [151] Y. Zhao and J. Zhang, "Microstrain and grain-size analysis from diffraction peak width and graphical derivation of high-pressure thermomechanics," *J. Appl. Crystallogr.*, 2008, vol. 41, no. 6, pp. 1095–1108.
- [152] Raghvendra and P. Singh, "Influence of Bi₂O₃ additive on the electrical conductivity of calcia stabilized zirconia solid electrolyte," *J. Eur. Ceram. Soc.*, 2015, vol. 35, no. 5, pp. 1485–1493.
- [153] P. Kumar, S. Presto, A. S. K. Sinha, S. Varma, M. Viviani, and P. Singh, "Effect of samarium (Sm³⁺) doping on structure and electrical conductivity of double perovskite Sr₂NiMoO₆ as anode material for SOFC," *J. Alloys Compd.*, 2017, vol. 725, pp. 1123–1129.
- [154] S. Fuentes, P. Muñoz, N. Barraza, E. Chávez-Ángel, and C. M. Sotomayor Torres, "Structural characterisation of slightly Fe-doped SrTiO₃ grown via a sol-gel hydrothermal synthesis," *J. Sol-Gel Sci. Technol.*, 2015, vol. 75, no. 3, pp. 593–601.
- [155] Y. Wang et al., "Enhancement of Seebeck coefficient for SrO(SrTiO₃)₂ by Sm substitution: Crystal symmetry restoration of distorted TiO₆ octahedra," *Appl. Phys. Lett.*, 2007, vol. 91, no. 24, p. 242102.
- [156] S. N. Panahi, H. Samadi, and A. Nemati, "Effect of Samarium Oxide on the Electrical Conductivity of Plasma-Sprayed SOFC Anodes," *JOM*, 2016, vol. 68, no. 10, pp. 2569–2573.
- [157] D. W. Johnson, L. E. Cross, and F. A. Hummel, "Dielectric Relaxation in Strontium Titanates Containing Rare-Earth Ions," *J. Appl. Phys.*, 1970, vol. 41, no. 7, pp. 2828–2833.
- [158] N. G. Eror and U. Balachandran, "Self-compensation in lanthanum-doped strontium titanate," *J. Solid State Chem.*, 1981, vol. 40, no. 1, pp. 85–91.

- [159] C. E. Bamberger, “Homogeneity Ranges of Phases $\text{Sr}_{4-x}\text{Ln}_{2x/3}\text{Ti}_4\text{O}_{12}$ (Ln = Sm to Lu) and $\text{Sr}_{1-y}\text{Eu}_y\text{TiO}_3$,” *J. Am. Ceram. Soc.*, 2005, vol. 80, no. 4, pp. 1024–1026.
- [160] J. Liu et al., “Influence of rare earth doping on thermoelectric properties of SrTiO_3 ceramics,” *J. Appl. Phys.*, 2013, vol. 114, no. 22, p. 223714.
- [161] R. K. Dwivedi, D. Kumar, and O. Parkash, “Valence compensated perovskite oxide system $\text{Ca}_{1-x}\text{La}_x\text{Ti}_{1-x}\text{Cr}_x\text{O}_3$ Part I Structure and dielectric behaviour,” *J. Mater. Sci.*, 2001, vol. 36, no. 15, pp. 3641–3648.
- [162] A. Peláiz-Barranco, J. D. S. Guerra, R. López-Noda, and E. B. Araújo, “Ionized oxygen vacancy-related electrical conductivity in $(\text{Pb}_{1-x}\text{La}_x)(\text{Zr}_{0.90}\text{Ti}_{0.10})_{1-x/4}\text{O}_3$ ceramics,” *J. Phys. D. Appl. Phys.*, 2008, vol. 41, no. 21, p. 215503.
- [163] S. Sen, R. N. Choudhary, and P. Pramanik, “Structural and electrical properties of Ca^{2+} -modified PZT electroceramics,” *Phys. B Condens. Matter*, 2007, vol. 387, no. 1–2, pp. 56–62.
- [164] Z. Chen, X. Shan, G. Li, N. Huang, H. Hao, and H. Liu, “Dielectric properties and relaxation behavior of Sm substituted SrTiO_3 ceramics sintered in nitrogen atmosphere,” *J. Mater. Sci. Mater. Electron.*, 2016, vol. 27, no. 10, pp. 10627–10633.
- [165] R. M. Katiliute et al., “Dielectric and Impedance Spectroscopy of BaSnO_3 and Ba_2SnO_4 ,” *Ferroelectrics*, 2014, vol. 464, no. 1, pp. 49–58.
- [166] S. Singh et al., “Structural and electrical conduction behaviour of yttrium doped strontium titanate: anode material for SOFC application,” *J. Alloys Compd.*, 2018, vol. 748, pp. 637–644.
- [167] B. Shri Prakash, S. Senthil Kumar, and S. T. Aruna, “Properties and development of Ni/YSZ as an anode material in solid oxide fuel cell: A review,” *Renew. Sustain. Energy Rev.*, 2014, vol. 36, pp. 149–179.

- [168] Y. Matsuzaki, “The poisoning effect of sulfur-containing impurity gas on a SOFC anode: Part I. Dependence on temperature, time, and impurity concentration,” *Solid State Ionics*, 2000, vol. 132, no. 3–4, pp. 261–269.
- [169] A. Faes, A. Hessler-Wyser, A. Zryd, and J. Van herle, “A Review of RedOx Cycling of Solid Oxide Fuel Cells Anode,” *Membranes (Basel)*, 2012, vol. 2, no. 3, pp. 585–664.
- [170] A. Atkinson et al., “Advanced anodes for high-temperature fuel cells,” in *Materials for Sustainable Energy*, Co-Published with *Macmillan Publishers Ltd*, UK, 2010, pp. 213–223.
- [171] S. Tao and J. T. S. Irvine, “Discovery and characterization of novel oxide anodes for solid oxide fuel cells,” *Chem. Rec.*, 2004, vol. 4, no. 2, pp. 83–95.
- [172] D. Neagu and J. T. S. Irvine, “Structure and Properties of $\text{La}_{0.4}\text{Sr}_{0.4}\text{TiO}_3$ Ceramics for Use as Anode Materials in Solid Oxide Fuel Cells,” *Chem. Mater.*, 2010, vol. 22, no. 17, pp. 5042–5053.
- [173] S. Hui and A. Petric, “Evaluation of yttrium-doped SrTiO_3 as an anode for solid oxide fuel cells,” *J. Eur. Ceram. Soc.*, 2002, vol. 22, no. 9–10, pp. 1673–1681.
- [174] P. Blennow, B. R. Sudireddy, A. H. Persson, T. Klemens, J. Nielsen, and K. Thydén, “Infiltrated SrTiO_3 : FeCr-based Anodes for Metal-Supported SOFC,” *Fuel Cells*, 2013, vol. 13, no. 4, pp. 494–505.
- [175] S. Hui and A. Petric, “Electrical conductivity of yttrium-doped SrTiO_3 : influence of transition metal additives,” *Mater. Res. Bull.*, 2002, vol. 37, no. 7, pp. 1215–1231.
- [176] Q. G. Hu, Z. Y. Shen, Y. M. Li, Z. M. Wang, W. Q. Luo, and Z. X. Xie, “Enhanced energy storage properties of dysprosium doped strontium titanate ceramics,” *Ceram. Int.*, 2014, vol. 40, no. 1, pp. 2529–2534.

- [177] Z. Shen, Y. Li, Q. Hu, W. Luo, and Z. Wang, "Dielectric properties of B-site charge balanced Dy-doped SrTiO₃ ceramics for energy storage," *J. Electroceramics*, 2015, vol. 34, no. 4, pp. 236–240.
- [178] E. David R. Lide, "CRC Handbook of Chemistry and Physics, 89th Edition (Internet Version)," CRC Press. Fr. Boca Raton, FL, 2009.
- [179] J. Liu et al., "Thermoelectric Properties of Dy-Doped SrTiO₃ Ceramics," *J. Electron. Mater.*, 2012, vol. 41, no. 11, pp. 3073–3076.
- [180] P. Wynblatt, G. S. Rohrer, and F. Papillon, "Grain boundary segregation in oxide ceramics," *J. Eur. Ceram. Soc.*, 2003, vol. 23, no. 15, pp. 2841–2848.
- [181] A. Zheltikov, "Impedance Spectroscopy: Theory, Experiment, and Applications Second Edition. Evgenij Barsoukov and J. Ross Macdonald (eds). John Wiley & Sons, Inc., Hoboken, New Jersey, 2005, pp. 595," *J. Raman Spectrosc.*, 2007, vol. 38, no. 1, pp. 122–122.
- [182] W. M. Merrill, R. E. Diaz, and N. G. Alexopoulos, "Extending the asymmetric Bruggeman effective medium theory to include scattering from small spherical inclusions," in IEEE Antennas and Propagation Society International Symposium. 1998 Digest. Antennas: Gateways to the Global Network. Held in conjunction with: USNC/URSI National Radio Science Meeting (Cat. No. 98CH36194), 1998, vol. 1, pp. 92–95.