

CONTENTS

TITLE PAGE	i
CERTIFICATE	iii
DECLARATION BY THE CANDIDATE	v
COPYRIGHT TRANSFER CERTIFICATE	vii
DEDICATION	ix
ACKNOWLEDGEMENTS	xi
CONTENTS	xv
LIST OF FIGURES	xxi
LIST OF SYMBOLS	xxv
ABBREVIATIONS	xxvii
PREFACE	xxix
1 INTRODUCTION AND LITERATURE REVIEW	1
1.1 Micro and Nano-Electromechanical Systems and Applications	1
1.1.1 Micro and nanomechanical resonators	2
1.1.2 Quality factor of mechanical resonators	3
1.1.3 Energy loss mechanisms in resonators	4
1.1.3.1 Air damping	4
1.1.3.2 Internal friction	5
1.1.3.3 Gas damping	5
1.1.3.4 Anchor losses	5
1.1.3.5 Thermoelastic damping	5

1.2	Classical and Non-Classical Continuum Theories	9
1.2.1	Modified couple stress theory	10
1.2.2	Nonlocal elasticity theory	11
1.3	Some Beam and Plate Theories	11
1.3.1	Euler-Bernoulli beam theory	11
1.3.2	Timoshenko beam theory	12
1.3.3	Kirchhoff plate theory	13
1.4	Thermoelasticity	14
1.4.1	Lord-Shulman (LS) thermoelasticity theory	16
1.4.2	Green-Naghdi (GN) thermoelasticity theory	17
1.4.3	Dual-phase-lag (DPL) thermoelasticity theory	18
1.4.4	Three-phase-lag (TPL) thermoelasticity theory	19
1.4.5	Thermoelasticity theory with a single delay term	19
1.4.6	Moore-Gibson-Thompson (MGT) thermoelasticity theory	20
1.5	Literature Review	20
1.6	Objective of the Thesis	31
2	THERMOELASTIC DAMPING ANALYSIS IN MICRO AND NANO- BEAM RESONATORS BASED ON HEAT CONDUCTION MODEL WITH A SINGLE DELAY TERM	33
2.1	Analysis of the Quality Factor of Microbeam Resonators Based on Heat Conduction Model with a Single Delay Term	33
2.1.1	Introduction ¹	33
2.1.2	Problem formulation	35
2.1.3	Unified heat conduction equation	36
2.1.4	Solution for thermoelastic damping	38
2.1.5	Numerical results and discussion	41
2.1.6	Conclusion	45
2.2	Thermoelastic Damping in Nanobeam Resonators Utilizing Entropy Generation Approach and Heat Conduction Model with a Single Delay Term	46
2.2.1	Introduction ²	46
2.2.2	Problem formulation	47
2.2.3	TED in nanobeam resonators	48
2.2.4	Solution for harmonic vibration	48
2.2.5	Entropy based method for TED	50
2.2.6	Numerical results and discussion	53

2.2.7	Conclusion	57
3	THERMOELASTIC DAMPING ANALYSIS IN MICRO AND NANO-BEAM RESONATORS CONSIDERING MOORE-GIBSON-THOMPSON THERMOELASTICITY THEORY	59
3.1	Thermoelastic Damping Analysis in Microbeam Resonators Based on Moore–Gibson–Thompson Generalized Thermoelasticity Theory	59
3.1.1	Introduction ³	59
3.1.2	Governing equations	61
3.1.3	Problem formulation	62
3.1.4	Initial and boundary conditions	65
3.1.5	Solution of the problem	65
3.1.6	Numerical results and discussion	68
3.1.7	Conclusion	76
3.2	Small-Scale Effect on Thermoelastic Vibration of Microbeam Considering Modified Couple Stress Theory and Moore-Gibson-Thompson Thermoelasticity Equation	78
3.2.1	Introduction ⁴	78
3.2.2	Problem formulation	79
3.2.2.1	Microbeam resonator and assumptions	79
3.2.2.2	The modified couple stress theory	79
3.2.2.3	The MGT thermoelasticity theory	80
3.2.2.4	Equation of motion of microbeam based on MCST	81
3.2.3	Solution for deflection and thermal moment of microbeam	83
3.2.4	Numerical results and discussion	85
3.2.4.1	Results validation	86
3.2.4.2	Effect of length-scale parameter	88
3.2.5	Conclusion	89
3.3	Surface Energy Effects on Thermoelastic Vibration of Nanomechanical Systems under Moore-Gibson-Thompson Thermoelasticity and Eringen’s Nonlocal Elasticity Theories	90
3.3.1	Introduction ⁵	90
3.3.2	Problem formulation	92
3.3.2.1	Beam deformation considering surface effects	92
3.3.2.2	The Euler-Bernoulli beam theory	93
3.3.2.3	Nonlocal elasticity theory in an Euler-Bernoulli beam	94

3.3.2.4	Equations of coupled thermoelasticity based on MGT theory	96
3.3.3	Solution for deflection and temperature	97
3.3.4	Numerical results and discussion	100
3.3.4.1	Small-scale effects	102
3.3.4.2	Surface energy effects	103
3.3.4.3	Effects of aspect ratios of the nanobeam	105
3.3.4.4	Influence of phase-lag time	106
3.3.5	Conclusion	108
4	SIZE-DEPENDENT THERMOELASTIC DAMPING ANALYSIS IN NANOBEAM RESONATORS BASED ON ERINGEN'S NON-LOCAL ELASTICITY AND MODIFIED COUPLE STRESS THEORIES	111
4.1	Introduction ⁶	111
4.2	Problem formulation	113
4.2.1	TED in Euler-Bernoulli nanobeam resonators	113
4.2.2	Coupled thermoelastic equations based on modified nonlocal couple stress (MNCS) theory	114
4.3	Solution of the problem	116
4.3.1	Solution for temperature field	116
4.3.2	Solution for quality factor	117
4.4	Results and discussion	120
4.4.1	Validation of results	121
4.4.2	Effects of nonlocal parameter on TED	122
4.4.3	Couple stress effect on TED	123
4.4.4	Influence of phase-lag parameter	124
4.5	Conclusion	126
5	RESPONSE OF DEFLECTION AND THERMAL MOMENT OF TIMOSHENKO MICROBEAMS CONSIDERING MODIFIED COUPLE STRESS THEORY AND DUAL-PHASE-LAG HEAT CONDUCTION MODEL	129
5.1	Introduction ⁷	129
5.2	Problem formulation	131
5.2.1	Governing equations for Timoshenko microbeam	131
5.2.2	The DPL heat conduction model	134

5.3	Solution of the problem	138
5.4	Results and discussion	140
5.5	Conclusion	148
6	THERMOELASTIC DAMPING ANALYSIS FOR SIZE-DEPENDENT MICROPLATE RESONATORS UTILIZING MODIFIED COUPLE STRESS THEORY AND THREE-PHASE-LAG HEAT CONDUCTION MODEL	151
6.1	Introduction ⁸	151
6.2	Formulation	152
6.2.1	The TPL heat conduction model	153
6.3	Solution of the problem	158
6.4	Results and discussion	162
6.5	Conclusion	172
7	SUMMARY OF THE THESIS AND FUTURE SCOPE	174
7.1	Summary	174
7.2	Future Scope	180
BIBLIOGRAPHY		182
PUBLICATIONS AND CONFERENCES		204

LIST OF FIGURES

1.1.1	Flow chart depicting the theory behind thermoelastic damping	6
2.1.1	Deformation of an Euler-Bernoulli beam.	35
2.1.2	(a) Thermoelastic damping versus ξ for aspect ratio 20. (b) Thermoelastic damping versus ξ for aspect ratio 25. (c) Thermoelastic damping versus ξ for aspect ratio 30.	43
2.1.3	TED versus h for aspect ratios 25 and 30 under TPL, GN-III, LS, and present models.	44
2.1.4	Effect of time delay parameter on TED versus normalized frequency for fixed aspect ratio 25.	45
2.2.1	Variation of Q^{-1}/Δ_E versus non-dimensional frequency ξ for fixed $k^* = 90$ and aspect ratio (a) $L/h = 25$ and (b) $L/h = 30$	54
2.2.2	Variation of Q^{-1}/Δ_E versus non-dimensional frequency ξ for fixed $k^* = 156$ and aspect ratio (a) $L/h = 25$ and (b) $L/h = 30$	55
2.2.3	Variation of Q^{-1}/Δ_E versus non-dimensional frequency ξ for fixed $k^* = 200$ and aspect ratio (a) $L/h = 25$ and (b) $L/h = 30$	55
2.2.4	Variation of Q^{-1}/Δ_E versus beam thickness h for (a) $k^* = 90$, (b) $k^* = 156$, and (c) $k^* = 200$	56
3.1.1	Simply supported microbeam subjected to a uniform load initially applied on the upper surface of the beam.	62
3.1.2	Variation of dimensionless deflection with respect to the dimensionless time for middle point of the beam.	70
3.1.3	Variation of the deflection difference ($\phi_0 - \phi$) with respect to the dimensionless time for middle point of the beam.	70
3.1.4	Variation of the dimensionless thermal moment with respect to the dimensionless time for the middle point of the beam.	71
3.1.5	Variation of the dimensionless deflection with respect to dimensionless time for varying dimensionless parameter k'_0 ($k'_0 \gg 1$, $k'_0 = 1$, $k'_0 \ll 1$).	71
3.1.6	Variation of the dimensionless thermal moment with respect to dimensionless time for varying dimensionless parameter k'_0 ($k'_0 \gg 1$, $k'_0 = 1$, $k'_0 \ll 1$).	72

3.1.7	Variation of the dimensionless deflection with respect to dimensionless time for different values of applied load on the upper surface of the beam.	72
3.1.8	Variation of the dimensionless deflection with respect to dimensionless time for different values of the beam length.	73
3.1.9	Variation of the dimensionless thermal moment with respect to dimensionless time for different values of the applied load on the upper surface of the beam.	74
3.1.10	Variation of the dimensionless thermal moment with respect to dimensionless time for different values of the beam thickness.	74
3.1.11	Variation of the dimensionless thermal moment with respect to dimensionless time for different values of the beam length.	75
3.1.12	Effects of phase-lags on the dimensionless thermal moment with respect to the dimensionless time of the beam.	75
3.2.1	Variation of deflection and thermal moment versus time under classical theory and MCST.	86
3.2.2	Variation of deflection and thermal moment under MGT, GN-III, and LS models.	87
3.2.3	Variation of deflection and thermal moment versus time for different values of length-scale parameter.	88
3.3.1	Simply supported nonlocal Euler-Bernoulli nanobeam with uniform load on the upper surface.	94
3.3.2	Responses of deflection and temperature versus time.	102
3.3.3	Responses of deflection and temperature versus time.	102
3.3.4	Effects of nonlocal parameter on deflection and temperature versus time.	103
3.3.5	Effects of surface residual tension and surface elastic modulus on deflection versus time.	104
3.3.6	Effects of surface residual tension and surface elastic modulus on temperature versus time.	105
3.3.7	Effects of aspect ratios on deflection versus time.	106
3.3.8	Effects of aspect ratios on temperature versus time.	106
3.3.9	Effects of phase-lag time on deflection and temperature versus time.	107
4.4.1	Variation of TED (Q^{-1}/Δ_E) under MNCS, nonlocal elasticity, MCST, and classical theories.	122
4.4.2	Effects of nonlocal parameter on TED by fixing material length-scale parameter as constant.	123
4.4.3	Effects of material length-scale parameter on TED by fixing nonlocal parameter as constant.	124
4.4.4	Effects of phase-lag time on TED under MNCS theory.	125

5.2.1	Geometry of Timoshenko microbeam (<i>a</i>) loading and the introduced coordinate system (<i>b</i>) cross-section of microbeam.	131
5.4.1	Response of normalized midspan deflection of microbeam w.r.t. dimensionless time considering classical theory and MCST for fixed $l/h = 0.3$	142
5.4.2	Response of normalized midspan deflection of microbeam w.r.t. dimensionless time considering MCST for LS, DPL, and Fourier heat conduction models for fixed $l/h = 0.3$	143
5.4.3	Response of normalized midspan thermal moment of microbeam w.r.t. dimensionless time considering classical theory and MCST for fixed $l/h = 0.3$	144
5.4.4	Response of normalized midspan thermal moment of microbeam w.r.t. dimensionless time considering MCST for LS, DPL, and Fourier heat conduction models for fixed $l/h = 0.3$	144
5.4.5	Response of normalized midspan deflection of microbeam w.r.t. dimensionless time considering MCST for varying aspect ratios (<i>a</i>) $l/h(l/h = 0, 0.4, 1)$ and (<i>b</i>) $l/h(l/h = 0.5, 1, 2)$	145
5.4.6	Response of normalized midspan thermal moment of microbeam w.r.t. dimensionless time considering MCST for varying aspect ratios (<i>a</i>) $l/h(l/h = 0, 0.3, 0.6)$ and (<i>b</i>) $l/h(l/h = 0, 5, 1, 2)$	145
5.4.7	Response of normalized midspan deflection of microbeam w.r.t. dimensionless time considering MCST for varying aspect ratio $L/h(L/h = 4, 6, 10)$ and for fixed $l/h = 0.3$	146
5.4.8	Response of normalized midspan thermal moment of microbeam w.r.t. dimensionless time considering MCST for varying aspect ratio $L/h(L/h = 4, 6, 10)$ and for fixed (<i>a</i>) $l/h = 0$, (<i>b</i>) $l/h = 0.3$, (<i>c</i>) $l/h = 0.6$	147
5.4.9	Effect of phase-lags on the normalized midspan thermal moment of microbeam w.r.t. dimensionless time considering MCST for fixed $l/h = 0.3$	147
6.2.1	Schematic diagram of a rectangular microplate.	153
6.4.1	Behavior of normalized frequency shift ($[Re(\omega) - \omega_0] / \omega_0 \Delta_E$) as a function of dimensionless variable ξ	163
6.4.2	Behavior of normalized frequency shift ($[Re(\omega) - \omega_0] / \omega_0 \Delta_E$) and normalized attenuation ($Im(\omega) / \omega_0 \Delta_E$) as a function of dimensionless variable ξ	164
6.4.3	Variation of TED in microplate resonator with different values of $\frac{l}{h}$ as a function of the dimensionless variable ξ for first mode ($m = 1, n = 1$).	165
6.4.4	Variation of TED in microplate resonator with different values of $\frac{b}{h}$ as a function of the dimensionless variable ξ for first mode ($m = 1, n = 1$).	165

6.4.5	Variation of TED in microplate resonator with different values of $\frac{L}{h}$ as a function of the dimensionless variable ξ for first mode ($m = 1, n = 1$).	166
6.4.6	Variation of TED as a function of dimensionless variable ξ for different values of phase-lag parameters in case of simply supported (SSSS) boundary condition for first mode ($m = 1, n = 1$).	166
6.4.7	Variation of TED as a function of dimensionless variable ξ for different values of phase-lag parameters in case of clamped-clamped (CCCC) boundary condition for first mode ($m = 1, n = 1$).	167
6.4.8	Variation of TED in microplate resonator with different values of $\frac{l}{h}$ as a function of the thickness h for first mode.	168
6.4.9	Variation of TED in microplate resonator with different values of b as a function of the thickness h for first mode.	169
6.4.10	Variation of TED in microplate resonator with different values of L as a function of the thickness h for first mode.	169
6.4.11	Variation of TED in microplate resonator with $l = 1 \mu m$ as a function of the thickness h for simply supported and clamped edges of the microplate for first mode.	170
6.4.12	Variation of TED in microplate resonator with different values of the microplate thickness h as a function of the length scale parameter l for first mode.	170