

## **Table of Contents**

List of Figures .....	xii
List of Tables .....	xxiii
List of Abbreviations .....	xxiv
Preface.....	xxv

### **Chapter 1: Introduction**

1.1 Global warming and energy security.....	1
1.1.1 Global warming and Climate change .....	1
1.1.1.1 Global warming.....	1
1.1.1.2 Climate change.....	2
1.1.1.3 Causes of climate change .....	3
1.1. 2 Energy security .....	3
1.2 Pollution control and green energy over fossil .....	4
1.3 Renewable energy and alternative energy solutions .....	5
1.4 Limitation/ problem with Renewable energy .....	6
1.5 Type of energy storage solutions.....	6
1.5.1 The battery is an alternating grid-scale energy storage solution....	8
1.5.2 Limitation of conventional metal-ion (Li-ion and Na -ion) battery.....	9
1.6 Parameters of performances for grid-scale energy storage .....	9
1.6.1 Redox flow battery technology for grid-scale energy storage application...	
10	
1.6.2 Metal-sulphur battery technology for grid-scale energy storage application...	
11	
1.6.3 Metal-air battery technology for grid-scale energy storage application....	13
1.6.3.1 Development of metal-air battery .....	14
1.6.3.2 Type Metal-air batteries .....	15
1.6.3.3 Metal anode and Working principle of the metal-air battery .....	16
1.6.3.4 Air cathode and role of cathode supported OER (Oxygen Evolution Reaction) and (Oxygen Reduction Reaction) ORR catalyst .....	17
1.6.3.4 .1 Overpotential .....	18
1.6.3.4 .2 Tafel slope .....	19
1.6.3.4 .3 Exchange current density ( $i_0$ ) .....	19

1.6.3.5 Survey of OER (Oxygen Evolution Reaction) and (Oxygen Reduction Reaction)ORR catalysts with different lattice structures .....	20
1.6.3.5.1 OER and ORR activity of transition/noble metal oxides .....	21
1.6.3.5.2 Role of $e_g$ electron on ORR/OER activity of Spinel and perovskite-type Oxide materials .....	21
1.6.3.5.3 Role of $e_g$ electron on ORR activity of Perovskites ( $\text{ABO}_3$ ) metal oxides .....	24
<b>1.7 Pseudocapacitors or Supercapacitors for grid-scale energy storage</b>	
Application .....	25
1.7.1 Development of pseudocapacitors.....	26
1.7.2 Classification of Pseudocapacitance .....	27
1.7.3 Psedocapative materials with different lattice structur.....	28
1.7.3.1 .1 $\text{Fe-O}_x$ redox mediator type materials .....	28
1.7.3.2 .2 $\text{VO}_x$ -based redox mediator type materials.....	29
1.7.3.3 .3 $\text{MnO}_x$ -based redox type materials .....	29
1.7.3.4 $\text{RuO}_2$ -based Redox mediator type materials .....	29
1.7.3.5 $\text{CoO}_x$ -based Redox mediator type materials.....	29
1.7.3.6 $\text{TiO}_2$ (B) cationic intercalation type materials .....	30
1.7.3.7 T- $\text{Nb}_2\text{O}_5$ cationic intercalation type materials .....	30
1.7.3.8 Perovskite Oxides anionic intercalation type materials.....	31
<b>1.8 Materials showing both OER/ORR catalysis and pseudocapacitance.....</b>	32
References .....	35

## **Chapter 2: Synthesis and Characterization Techniques**

2.1 Overview .....	49
2.2 Materials Synthesis techniques.....	49
2.2.1 Solid-state or Ceramic method .....	50
2.2.2 sol-gel auto combustion method.....	50
2.2.3 Co-precipitation method.....	51
2.3 Characterization Techniques .....	52
2.3.1 X-ray Diffraction (XRD).....	52
2.3.2 High-Resolution Scanning Electron Microscope (HR-SEM).....	54
2.3.3 High-Resolution Transmission Electron Microscope (HR-TEM).....	56

2.3.4 Thermogravimetric analysis (TGA).....	58
2.3.5 Fourier transform infrared (FTIR) spectroscopy.....	58
2.3.6 UV-Visible Spectrophotometer.....	60
2.3.7 Raman Spectroscopy.....	61
2.3.8 X-ray Photoelectron Spectroscopy (XPS).....	62
2.3.9 BET (Brunauer, Emmett, and Teller) specific surface area analysis.....	64
2.4 Electrode Fabrication and Cell Assembly.....	65
2.4.1 Electrode fabrication.....	65
2.4.2 Cell Assembly.....	66
2.4.3 Electrochemical characterization techniques.....	67
2.4.3.1 Linear sweep voltammetry (LSV).....	67
2.4.3.2 Cyclic voltammetry (CV).....	68
2.4.3.3 Chemical Kinetic of pseudocapacitors from cyclic voltammetry curve...	69
2.4.3.4 Charge-discharge (Chronopotentiometry).....	71
2.4.3.5 Electrochemical Impedance Spectroscopy (EIS).....	73
References.....	75

### **Chapter-3: Ni stabilized Rock-Salt structured CoO; Co<sub>1-x</sub>Ni<sub>x</sub>O: Tuning of e<sub>g</sub> electrons to Development a Novel OER Catalysts**

3.1 Introduction.....	79
3.2 Materials Synthesis and characterizations.....	80
3.2 .1 Electrochemical Studies.....	81
3.3 Results and Discussion.....	82
3.3.1 XRD and Crystal structure.....	82
3.3.2 SEM analysis.....	83
3.3.3 Fourier transform infrared spectroscopy (FTIR) analysis.....	84
3.3.4 X-ray photoelectron spectroscopy (XPS) analysis.....	84
3.3.5 Linear Swept voltammetry (LSV) and Electrochemical Impedance Spectroscopy (EIS) analysis 1M KOH electrolyte.....	85

3.3.6 Linear Swept voltammetry (LSV) and EIS measurements in different molar KOH electrolyte .....	87
3.3.7 Linear Swept voltammetry and EIS measurements in 5M KOH electrolyte .....	87
3.3.8 Comparative Tafel slope in 1M and 5M KOH.....	88
3.3.9 Showing stability of OER catalyst in 5M KOH.....	91
3.3.10 Role of eg electrons on OER and ORR catalyst.....	91
3.4 Conclusions.....	93
References.....	94

## **Chapter 4: Investigation of Role of Sr and Development of Superior Sr doped Hexagonal**

### **BaCoO<sub>3-δ</sub> Perovskite Bifunctional OER/ORR Catalyst in Alkaline Media**

4.1 Introduction .....	99
4.2 Materials Synthesis and characterization.....	100
4.2.1 Electrochemical Studies.....	101
4.3 Results and Discussion .....	102
4.3.1 Crystallographic characterization.....	102
4.3.2 Brunauer-Emmett-Teller (BET) analysis.....	104
4.3.3 Scanning Electron Microscopy (SEM) with Energy Dispersive X-Ray Analysis (EDX) analysis .....	104
4.3.4 Transmission electron microscopes (TEM) analysis .....	105
4.3.5 X-ray photoelectron spectroscopy (XPS) analysis.....	106
4.3.6 Temperature-dependent resistivity study.....	107
4.3.7 UV visible spectroscopy analysis.....	108
4.3.8 Electronic structure.....	108
4.3.9 Role of Sr doped in BaCoO <sub>3</sub> .....	110
4.3.10 Mott–Schottky and flat-band potential.....	110
4.3.11 Linear Sweep Voltammetry (LSV) analysis.....	111
4.3.12 EIS (Electrochemical impedance spectroscopy) analysis .....	113
4.3.13 Cyclic voltammetry perform in different concentration electrolytes.....	113

4.3.14 Stability perform cyclic voltammetry analysis .....	114
4.3.15 Stability test by chronoamperometric experiment.....	115
4.4 Conclusion.....	116
References.....	117

**Chapter 5:  $\text{La}_{0.5}\text{K}_{0.5}\text{CoO}_{3-\delta}$  ( $0 \leq x \leq 0.5$ ) Perovskite: A Novel Bifunctional OER catalyst and supercapacitive energy storage material**

5.1 Introduction .....	123
5.2 Materials Synthesis and characterizations .....	124
5.2.1 Electrode fabrication.....	125
5.2.2 Electrochemical Studies .....	126
5.2.2.1 Electrocatalysts measurement.....	126
5.2.2.2 Supercapacitors measurement.....	127
5.3 Results and discussions .....	127
5.3.1 Crystallographic characterization.....	127
5.3.2 FTIR spectra analysis.....	128
5.3.3 UV-vis absorption spectrum and bandgap analysis.....	130
5.3.4 BET surface area and pore sizeanalysis.....	130
5.3.5 XPS analysis.....	131
5.3.6 SEM analysis.....	132
5.3.7 TEM analysis.....	133
5.3.8 Strain-induced distortion of CoO <sub>5</sub> octahedra.....	134
5.3.9 Double-exchange of $\text{Co}^{3+}$ - $\text{O}^{2-}$ - $\text{Co}^{4+}$ .....	134
5.3.10 Co (3d)/O (2p) orbital overlap.....	135
5.3.11 Mott–Schottky plot.....	136
5.3.12 Linear Sweep Voltammetry (LSV) analysis.....	137
5.3.13 EIS (Electrochemical impedance spectroscopy) and Cdl value analysis	139
5.3.14 Chronoamperometric stability test.....	139
5.4 Electrochemical Charge Storage Behaviour in neutral $\text{Na}_2\text{SO}_4$ electrolyte....	140
5.4.1 Bifunctional OER catalyst and supercapacitive energy storage behavior....	140
5.4.2 Cyclic voltammetry study in neutral $\text{Na}_2\text{SO}_4$ electrolyte... ..	141
5.4.3 b value (Kinetics) in $\text{Na}_2\text{SO}_4$ aqueous electrolyte .....	143
5.4.4 Dunn method and Kinetics analysis.....	143

5.4.5 Charge discharge (plot V vs. time) analysis in Na <sub>2</sub> SO <sub>4</sub> aqueous electrolyte.....	145
5.4.6 EIS analysis in Na <sub>2</sub> SO <sub>4</sub> Aqueous electrolyte.....	146
5.4.7 Full cell (La <sub>0.5</sub> K <sub>0.5</sub> CoO <sub>3-δ</sub> // AC (Activated carbon) electrochemical Analysis in Na <sub>2</sub> SO <sub>4</sub> aqueous electrolyte.....	147
5.4.8 Full cell (La <sub>0.5</sub> K <sub>0.5</sub> CoO <sub>3-δ</sub> // AC (Activated carbon) EIS (Electrochemical Impedance Spectroscopy) analysis in Na <sub>2</sub> SO <sub>4</sub> aqueous electrolyte .....	148
5.4.9 Full cell (La <sub>0.5</sub> K <sub>0.5</sub> CoO <sub>3-δ</sub> // AC (Activated carbon) of specific energy vs. Specific power in Na <sub>2</sub> SO <sub>4</sub> aqueous electrolyte .....	149
5.5 Conclusions.....	150
References.....	151

## **Chapter 6: La<sub>1-x</sub>K<sub>x</sub>FeO<sub>3-δ</sub>: An anion intercalative pseudo-capacitive electrode for supercapacitors application**

6.1 Introduction.....	157
6.2 Materials Synthesis and characterizations.....	159
6.2.1 Electrochemical Studies .....	160
6.3 Results and Discussions .....	160
6.3.1 Crystallographic characterization.....	160
6.3.2 X-ray photoelectron spectroscopy (XPS) analysis .....	162
6.3.3 Brunauer-Emmett-Teller (BET) analysis.....	163
6.3.4 Scanning Electron Microscopy (SEM) with Analysis (EDX) and High- Resolution Transmission Electron Microscopes (HRTEM) analysis.....	164
6.3.5 Cyclic Voltammetry analysis.....	165
6.3.6 Determination of the Diffusion coefficient .....	167
6.3.7 Determination of b values and analysis .....	168
6.3.8 Dunn's plot analysis.....	170
6.3.9 Trassati's plot analysis.....	171
6.3.10 Chonoamperometry (charge-discharge).....	172
6.3.11 Electrochemical impedance spectroscopy (EIS) analysis.....	173
6.3.12 Two electrodes full cell test of La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> //AC (CV, charge-discharge, and cyclic stability).....	174
6.3.13 Electrochemical impedance spectroscopy of two electrodes	

(La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> //AC full cell) .....	176
6.3.14 Study of specific energy vs. specific power of full cell	
(La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> //AC full cell).....	177
6.4 Conclusions.....	178
References.....	179
<b>Chapter 7: Anhydrous NiC<sub>2</sub>O<sub>4</sub> Quantum dots: A superior pseudocapacitive electrode for large-scale energy storage applications in aqueous KOH and neutral Na<sub>2</sub>SO<sub>4</sub> electrolyte</b>	
7.1 Introduction.....	185
7.2 Material Synthesis and Characterizations.....	186
7.2.1 Preparation of Electrode.....	188
7.3 Results and Discussions.....	188
7.3.1 Crystallographic characterization.....	188
7.3.2 Thermo-gravimetric Analysis (TGA) and Differential thermal Analysis (DTA).....	190
7.3.3 Fourier transform infrared spectroscopy (FTIR) analysis .....	191
7.3.4 Brunauer-Emmett-Teller (BET) surface area analysis.....	192
7.3.5 Raman spectrum analysis.....	193
7.3.6 UV visible spectroscopy analysis.....	194
7.3.7 X-ray photoelectron spectroscopy (XPS) analysis.....	194
7.3.8 High-resolution scanning electron microscopy (HRSEM) analysis .....	196
7.3.9 High-resolution scanning electron microscopy (HRSEM) analysis .....	196
7.3.10 Cyclic Voltammetry analysis.....	197
7.3.11 Determination of Diffusion coefficient .....	199
7.3.12 Determination of b values and analysis .....	200
7.2.13 Dunn's plot analysis.....	201
7.3.14 Trassati's plot analysis.....	203
7.3.15 Chonoamperometry Charge -discharge analysis.....	204
7.3.16 Electrochemical impedance spectroscopy (EIS) analysis.....	206
7.3.17 Full cell cyclic voltammetry (CV) of Activated carbon // of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs in 2M KOH analysis .....	207

7.3.18 Full cell charge-discharge of Activated carbon // NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs in 2M KOH analysis and stability of AC// NiC <sub>2</sub> O <sub>4</sub> QDs after 2500 cycles.....	208
7.3.19 Comparative Electrochemical impedance spectroscopy (EIS) Analysis Activated carbon // of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs in 2M KOH analysis.....	209
7.3.20 NiC <sub>2</sub> O <sub>4</sub> QDs electrochemical analysis in 1M Na <sub>2</sub> SO <sub>4</sub> .....	210
7.3.21 Full cell AC// NiC <sub>2</sub> O <sub>4</sub> QDs electrochemical analysis in 1M Na <sub>2</sub> SO <sub>4</sub> .....	211
7.3.22 Comparative Power Density vs. Energy Density of AC// NiC <sub>2</sub> O <sub>4</sub> QDs in 2M KOH and 1M Na <sub>2</sub> SO <sub>4</sub> .....	212
7.4 Conclusions.....	213
References.....	215
<b>Chapter 8: Summary and Future scope</b>	
8.1 Summary .....	221
8.2 Future Scope .....	223

## List of Figure

---

Figure No.	Figure description	Page No.
Figure 1.1	Illustration of Global Warming	2
Figure 1.2	Causes of global warming and Climate change	2
Figure 1.3	Concept of energy security	4
Figure 1.4	a) Source of renewable energy b) Breakdown of renewables use in total final energy consumption terms	5
Figure 1.5	Different types of grid energy storage technologies for stationary applications	6
Figure 1.6	different types of energy storage technologies for stationary applications	7
Figure 1.7	. a) Schematic illustration of the first Li-ion battery ( $\text{LiCoO}_2/\text{Li}^+$ -ion electrolyte/graphite) b) Gravimetric power and energy densities for different rechargeable batteries	8
Figure 1.8	Suitability of energy storage technologies to different power and rate of discharge requirements	10
Figure 1.9	Schematic of the mechanism of vanadium redox flow battery	11
Figure 1.10	Schematic diagrams of Li–S cell with its charge/discharge operations	12
Figure 1.11	Schematic diagrams of Li–air battery	14
Figure 1.12	Theoretical energy density, specific energy, and nominal cell voltage of different types of metal-air batteries	15
Figure 1.13	Schematic diagrams of Metal-Air Batteries working principles for (a) non-aqueous electrolyte, and (b) aqueous electrolyte	16
Figure 1.14	Schematic diagrams of a) working principle of Zn–air battery and b) OER and ORR mechanism on air cathode	18
Figure 1.15	Schematic diagrams of Gibbs free energy of reactive species and intermediates (horizontal lines) of the oxygen evolution reaction (OER) versus the reaction coordinate. Blue lines and red lines indicate the energetics of a real (typical) catalyst and an ideal catalyst	20

Figure 1.16	Schematic diagrams of Volcano plots of common metal electrocatalysts	21
Figure 1.17	(a-b) Schematic diagrams of Volcano plots ORR and OER activity respectively on various spinel's as a function of $e_g$ occupancy of the active element at the octahedral site	22
Figure 1.18	Electronic configurations (d orbital splitting bonding ( $t_{2g}$ )) and antibonding ( $e_g$ )) and relevant metal orbitals of first-row transition metals for a $\text{BO}_5$ configuration	23
Figure 1.19	The relation between the OER catalytic activity, defined by the overpotentials at $50 \mu\text{A cm}^{-2}$ of OER current, and the occupancy of the $e_g$ -symmetry electron of the transition metal (B in $\text{ABO}_3$ )	23
Figure 1.20	a) Potentials at $25 \text{ mA/cm}^2$ of the perovskite oxides have an M-shaped relationship with the d electron number b) Role of $e_g$ electron on ORR activity of perovskite oxides, Potentials at $25 \text{ mA cm}^{-2}$ as a function of $e_g$ orbital in perovskite-based oxides	24
Figure 1.21	Advantage of supercapacitors over battery	25
Figure 1.22	Timeline of major developments in the field of pseudocapacitance	26
Figure 1.23	a) Adsorption pseudocapacitance, b) redox pseudocapacitance, and c) intercalation pseudocapacitance. d) CV of a Pt. (110) surface in aqueous $0.1\text{M HClO}_4$ solution at $50\text{mV/s}$ E) CV of a $\text{RuO}_2\text{-}0.5\text{H}_2\text{O}$ electrode in aqueous $0.5\text{M H}_2\text{SO}_4$ solutionf) CV of T- $\text{Nb}_2\text{O}_5$ Nano crystalline film in a nonaqueous $\text{Li}^+$ electrolyte cycled at $0.1 \text{ mV/s}$ .	28
Figure 1.24	Structural model of T- $\text{Nb}_2\text{O}_5$ , highlighting densely packed 4h layers and loosely packed 4g layers and proposed low-hindrance $\text{Li}^+$ diffusion paths between bridging sites Nyquist Plot for ionic solids	30
Figure 1.25	shows $\text{O}^{2-}$ intercalation in $\text{SrCoO}_{3-\delta}$	31
Figure 1.26	a) LSV collected at $5 \text{ mV s}^{-1}$ for NiO-NFBs, NiO-NPTs, and Ni foam electrodes, b) respective Tafel slopes c) CV of NiO nanoparticles film on nickel foams working electrode in $1\text{M KOH}$ d) Galvanostatic charge/discharge profiles for NiO nanoparticles film on nickel in the potential range of $0\text{--}0.5\text{V}$	33

Figure 1.27	a) morphology MnO <sub>2</sub> b) LSV -curves MnO <sub>2</sub> -based samples on Ni foam c ) CV curves at various scan rates (the inset is the CV curve at 5 mV s <sup>-1</sup> ), d) galvanostatic charge-discharge curves at various current densities of MnO <sub>2</sub>	34
Figure 2.1	Schematic representation of the three types of synthesis routes	49
Figure 2.2	block diagram of the solid-state synthesis process	50
Figure 2.3	block diagram sol-gel auto combustion synthesis process	50
Figure 2.4	block diagram Co-precipitation synthesis process	52
Figure 2.5	Schematic diagram of the incident and diffracted X-rays from the crystal	53
Figure 2.6	Rigaku, Miniflex II, Japan, IIT (BHU) Varanasi	54
Figure 2.7	Schematic diagram of the core component of SEM microscope	55
Figure 2.8	HR-SEM Instrument facility, ZEISS EVO 18 in CIFC IIT (BHU) Varanasi	55
Figure 2.9	(a) Schematic diagram of core component of TEM microscope. Transmitted and diffracted electrons for (b) Bright field and (c) Dark field imaging in TEM	57
Figure 2.10	HRTEM Facilities with EDAX spectrometer, IIT (BHU) Varanasi	57
Figure 2.11	TGA measurement system CIFC, IIT (BHU) Varanasi	58
Figure 2.12	Brief mechanism of FTIR for detection	59
Figure 2.13	FTIR spectrometer CIFC, IIT (BHU) Varanasi	60
Figure 2.14	Schematic diagram of UV-Visible spectrometer	60
Figure 2.15	Schematic representation of the scattering process in Raman scattering	61
Figure 2.16	Schematic diagram of Raman spectrometer.	62
Figure 2.17	Schematic diagram XPS Basic Principle	63
Figure 2.18	XPS Spectrometer, CIFC. IIT(BHU) Varanasi	63
Figure 2.19	BET surface area measurement system, CIFC, IIT (BHU) Varanasi	65
Figure 2.20	Electrode picture for supercapacitors application	66
Figure 2.21	An electrochemical cell in a three-electrode system	67
Figure 2.22	Linear sweep voltammetry (LSV) polarization curve, voltage(V) vs.	68

	current	
Figure 2.23	Cyclic voltammetry (CV) polarization curve , voltage(V) vs. current	69
Figure 2.24	Power-law dependence of the peak current on sweep rate for capacitive materials ( $b= 1.0$ ) and typical battery-type materials ( $b = 0.5$ ).	70
Figure 2.25	Charge-discharge (Chronopotentiometry) plot voltage vs. time	72
Figure 2.26	Electrochemical impedance spectroscopy (EIS) mechanism and cole-cole plot	74
Figure 3.1	(a). X-ray diffraction patterns of $\text{Ni}_x\text{Co}_{1-x}\text{O}$ ( $0 \leq x \leq 0.4$ ) denoted (b). Rietveld refinement of XRD pattern of $\text{Ni}_{0.3}\text{Co}_{0.7}\text{O}$	82
Figure 3.2	(a) Scanning electron micrograph of $\text{Ni}_{0.3}\text{Co}_{0.7}\text{O}$ . (b) Scanning electron micrograph (enlarged view) of $\text{Ni}_{0.3}\text{Co}_{0.7}\text{O}$ (c) EDX analysis showing the stoichiometric distribution of Co, Ni, and O elements	83
Figure 3.3	FTIR spectrum of $\text{Ni}_{0.3}\text{Co}_{0.7}\text{O}$	84
Figure 3.4	XPS of $\text{Ni}_{0.3}\text{Co}_{0.7}\text{O}$ . (a) Full XPS survey of $\text{Ni}_{0.3}\text{Co}_{0.7}\text{O}$ (b) Core level Ni2p spectrum (c) Co2p spectrum (d) O1s spectrum	85
Figure 3.5	(a) OER activity of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 1 M KOH electrolyte. (b) ORR activity of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 1 M KOH electrolyte. (c) OER and ORR performed of $\text{Ni}_{0.3}\text{Co}_{0.7}\text{O}$ with mechanism (d) EIS measurements of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 1 M KOH electrolyte	86
Figure 3.6	(a) OER activity of $\text{Co}_{0.7}\text{Ni}_{0.3}\text{O}$ from 1M to 6 M KOH electrolyte (b) EIS measurements of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 1 M KOH electrolyte	87
Figure 3.7	(a) OER activity of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 5 M KOH electrolyte. (b) ORR activity of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 5 M KOH electrolyte. (c) EIS measurements of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 5 M KOH electrolyte.	88
Figure 3.8	(a) Tafel plot of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 1 M KOH. (b) Tafel plot of $\text{Co}_{1-x}\text{Ni}_x\text{O}$ at 5 M KOH	89
Figure 3.9	Showing stability of OER activity of $\text{Ni}_{0.3}\text{Co}_{0.7}\text{O}$ up to 200 cycles.	90
Figure 3.10	a) Volcano graph depicting correlation of eg electrons with overpotential (at 10 mA/ cm <sup>2</sup> ) and the Tafel slope at 1 M KOH electrolyte b) d orbital presentation and e <sub>g</sub> electron calculation	92

Figure 4.1	(a) powder xrd pattern of $\text{Ba}_{1-x}\text{Sr}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) ,(b) Rietveld refinement XRD profile of $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$ (c) Vesta image of $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$ and (d) Represent of bond angle of Co-O-Co (between O-2p and Co-3d orbital	102
Figure 4.2	N2 adsorption/desorption isotherms of $\text{BaCoO}_{3-\delta}$ and $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$	104
Figure 4.3	(a) SEM image showing particle distribution (b) EDX elemental analysis	105
Figure 4.4	TEM image along with HRTEM showing lattice fringes and high-resolution FFT, inverse FFT with d spacing	105
Figure 4.5	(a) Full survey spectra of $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$ (b) core level of Ba (3d) and Co (2p) spectrum (c) core level of Sr(3d) spectrum (d) core level of O(1s) spectrum.	106
Figure 4.6	(a) The temperature dependence of electrical resistivity of the 2H-type solid solution $\text{Ba}_{1-x}\text{Sr}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) as a function of Sr content (b) plot of $\ln(R)$ against $T^{-1/4}$ of the resistivity data	107
Figure 4.7	UV-vis absorption spectrum of $\text{Ba}_{1-x}\text{Sr}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) powder sample	108
Figure 4.8	Scheme showing the presence of oxygen vacancies $\text{BO}_5$ octahedral with high overlapping between O(2p) and Co(3d) band.	109
Figure 4.9	Oxygen vacancies and pinning Fermi level at the top of the Co(3d)/O(2p) $\pi^*$ band	110
Figure 4.10	Scheme showing the presence of oxygen vacancies $\text{BO}_5$ octahedral with high overlapping between O(2p) and Co(3d) band. (c) Oxygen vacancies and pinning Fermi level at the top of the Co(3d)/O(2p) $\pi^*$ band	111
Figure 4.11	(a) OER and ORR polarization profiles of $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$ , (b) OER polarization profiles for the $\text{Ba}_{1-x}\text{Sr}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) samples obtained using a $3 \text{ mVs}^{-1}$ scan rate, (c) in ORR polarization profiles for the $\text{Ba}_{1-x}\text{Sr}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) samples obtained using a $3 \text{ mVs}^{-1}$ scan rate in $\text{O}_2$ saturated $0.1\text{M KOH}$ solution, (d) respective Tafel plots	112
Figure 4.12	electrochemical impedance spectra for the $\text{Ba}_{1-x}\text{Sr}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) at $1.7\text{V}$ vs RHE	113

Figure 4.13	OER polarization profiles for the $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$ at 3 mVs <sup>-1</sup> scan rate in 0.1, 1, 3, 5, and 6M KOH	114
Figure 4.14	Cycles stability up to 500 cycles of $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$ electrode at 3 mVs <sup>-1</sup> in 1M KOH	115
Figure 4.15	Chronoamperometric responses of $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$ electrode at constant potentials at 1.7 V vs RHE at an initial current density of 10 mA/cm <sup>2</sup>	115
Figure 5. 1	(a) XRD pattern of $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ )), (b) Rietveld refinement of $\text{La}_{0.5}\text{K}_{0.5}\text{CoO}_{3-\delta}$ , (c) vesta image of $\text{La}_{0.5}\text{K}_{0.5}\text{CoO}_{3-\delta}$	127
Figure 5.2	FTIR spectra of $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $x=0, 0.3, 0.5$ )	129
Figure 5.3	. (a) UV-vis absorption spectrum of $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $x=0, 0.3, 0.5$ ) (b) Optical bandgap of $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $x=0, 0.3, 0.5$ ).	130
Figure 5.4	N2 adsorption/desorption isotherms of $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $x=0, 0.3, 0.5$ )	131
Figure 5. 5	XPS of $\text{La}_{0.5}\text{K}_{0.5}\text{CoO}_{3-\delta}$ of powder sample (a) full survey, (b) Fe(2p) core level, (c) O(1s), (d) La (3d) and (e) K(2p)	132
Figure 5.6	(a) SEM image showing particle distribution of $\text{La}_{0.5}\text{K}_{0.5}\text{CoO}_{3-\delta}$ (c) EDX elemental analysis of $\text{La}_{0.5}\text{K}_{0.5}\text{CoO}_{3-\delta}$	133
Figure 5.7	(a) TEM image along with HRTEM showing lattice fringes and high-resolution FFT, inverse FFT with d spacing (012 planes) of $\text{LaCoO}_3$ . (b) TEM image along with HRTEM showing lattice fringes and high-resolution FFT, inverse FFT with d spacing (012 planes) of $\text{La}_{0.5}\text{K}_{0.5}\text{CoO}_{3-\delta}$	133
Figure 5.8	Scheme showing the presence of oxygen vacancies $\text{BO}_5$ octahedral	134
Figure 5.9	Atomic orbital diagram of double-exchange $\text{Co}^{3+} - \text{O}^{2+} - \text{Co}^{4+}$ interaction	135
Figure 5.10	Oxygen Vacancies pinning Fermi level at the top of the Co(3d)/O(2p) $\pi^*$ band	136
Figure. 5.11	Mott–Schottky plot of p-type (hole) semiconductor $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) and Flat band (Efb) potential	137
Figure 5.12	(a) OER polarization profiles of BSCF, $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{CoO}_{3-\delta}$ , and $\text{La}_{0.7}\text{K}_{0.3}\text{CoO}_{3-\delta}$ in 1M KOH solution (b) OER polarization profiles for the $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) samples obtained using a 3 mVs <sup>-1</sup> scan rate in 1M KOH solution (c) respective Tafel plots for $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) sample (d) ORR polarization profiles for the $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ ) samples obtained using a 3 mVs <sup>-1</sup> scan	138

	rate in O <sub>2</sub> saturated 1M KOH solution.	
Figure 5.13.	(a) Electrochemical impedance (EIS) spectra for the the La <sub>1-x</sub> K <sub>x</sub> CoO <sub>3-δ</sub> δ(0 ≤ x ≤ 0.5) at 1.7V vs RHE    (b) measure Cdl values of La <sub>1-x</sub> K <sub>x</sub> CoO <sub>3-δ</sub> ( x = 0.1,0.3 and 0.5)	139
Figure 5.14	Chronoamperometric responses of La <sub>0.7</sub> K <sub>0.3</sub> CoO <sub>3-δ</sub> electrode at constant potentials at 1.7 V vs. RHE at an initial current density of 10 mA/ cm <sup>2</sup> . (Insert stability retention by CV	140
Figure 5.15	Cyclic voltammetry of La <sub>0.7</sub> K <sub>0.3</sub> CoO <sub>3-δ</sub> material at scan rate 10 mV/s in 1M KOH electrolyte and at scan rate 10 mV/s in 0.5 M Na <sub>2</sub> SO <sub>4</sub> electrolyte	141
Figure 5.16	(a) Comparative Cyclic voltammetry of La <sub>1-x</sub> K <sub>x</sub> CoO <sub>3-δ</sub> (0 ≤ x ≤ 0.5) material at scan rate 10 mV/s in 0.5 M Na <sub>2</sub> SO <sub>4</sub> electrolyte (b-d) cyclic voltammetry of La <sub>1-x</sub> K <sub>x</sub> CoO <sub>3-δ</sub> (x =0, 0.3, 0.5) material in 0.5 M Na <sub>2</sub> SO <sub>4</sub> electrolyte	142
Figure 5.17	Plot of linear relationship between log (peak current) and log (scan rate) at two different scan rate regions of La <sub>1-x</sub> K <sub>x</sub> CoO <sub>3-δ</sub> (x =0, 0.3, 0.5)	143
Figure 5.18	(a) Plot of power's law of charged state at a potential and discharged state at a potential of La <sub>1-x</sub> K <sub>x</sub> CoO <sub>3-δ</sub> (x =0, 0.3, 0.5) (b) Contribution of diffusive and capacitive at different scan rates contribution of La <sub>1-x</sub> K <sub>x</sub> CoO <sub>3-δ</sub> (x =0, 0.3, 0.5) at 2mV/s	144
Figure 5.19	(a) Charge discharge (plot V vs. time) of La <sub>1-x</sub> K <sub>x</sub> CoO <sub>3-δ</sub> (0 ≤ x ≤ 0.5) electrode at 1A/g in 0.5 M Na <sub>2</sub> SO <sub>4</sub> (b) charge discharge (plot potential (V) vs. time(t) ) of La <sub>0.5</sub> K <sub>0.5</sub> CoO <sub>3-δ</sub> electrode 0.5M Na <sub>2</sub> SO <sub>4</sub> (c) capacitive retention and columbic efficacy with cycle -number	145
Figure 5.20	Impedance spectroscopy (EIS) at 10mV applied voltage(V) from 1MHz to 0.01 Hz	146
Figure 5.21	showing full cell (ASCs) performances of activated carbon vs. La <sub>0.5</sub> K <sub>0.5</sub> CoO <sub>3-δ</sub> electrode; (a) CV of individual electrodes at 10 mV/s respect to Hg/HgO electrode in 0.5 M Na <sub>2</sub> SO <sub>4</sub> , (b) CV at different scan rate of ASCs in 0.5 M Na <sub>2</sub> SO <sub>4</sub> (c) charge-discharge in 0.5 M Na <sub>2</sub> SO <sub>4</sub> , (d) Capacitance retention and coulombic efficiency with 2500 cycle at 10 A/g constant current of the full cell	147
Figure 5.22	showing EIS at 10 mV applied voltage, full cell (ASCs) performances of activated carbon vs. La <sub>0.5</sub> K <sub>0.5</sub> CoO <sub>3-δ</sub> electrode	149
Figure 5.23	showing Ragone plot full cell (ASCs) performances of activated carbon vs. La <sub>0.5</sub> K <sub>0.5</sub> CoO <sub>3-δ</sub> electrode	150
Figure 6. 1	(a) XRD pattern of La <sub>1-x</sub> K <sub>x</sub> FeO <sub>3-δ</sub> (x = 0, 0.1, 0.2, 0.3, 0.4, 0.5), (b) Rietveld	161

	refinement of La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> , (c) structure of La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> and (d) Jahn–Teller distortion over Fe-O octahedra in orthorhombic La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> structure.	
Figure 6.2	XPS of La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> of powder sample (a) full survey, (b) Fe(2p) core level, (c) O(1s), (d) La (3d) and (e) K(2p)	163
Figure 6.3	show N2 adsorption-desorption isotherms with the pore size distribution	164
Figure 6.4	(a) SEM image showing morphology characteristic of La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> and particles distribution from SEM image, (b) HRTEM image comprising the plane with distorted fringes (inset: FFT and inverse FFT of the selected region) of (002) plane and line profile of (002) plane the selected line in the inverse FFT image of the superstructural peak region.	164
Figure 6.5.	(a) Cyclic voltammetry of La <sub>1-x</sub> K <sub>x</sub> FeO <sub>3-δ</sub> (x = 0, 0.4 and 0.5) material at scan rate 10 mV/s in 2M KOH electrolyte, ( b-d) cyclic voltammetry of La <sub>1-x</sub> K <sub>x</sub> FeO <sub>3-δ</sub> (x = 0.3, 0.4, 0.5) material in 2M KOH electrolyte	166
Figure 6.6	Plot peak current density vs square root of scan rate of La <sub>1-x</sub> K <sub>x</sub> FeO <sub>3-δ</sub> (x = 0, 0.3, 0.5) sample	167
Figure 6.7	(a-b) shows the linear relationship of log (v) vs log (i), slope represents the b value according to the power-law (c ) b value at the different potential of La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> in charging and discharging process at a different potential, (d) plot of log(peak current) vs log(scan rate)	169
Figure 6.8	(a-b) capacitive and diffusion control processes contribution can be distinguished by the slope(k <sub>1</sub> ) and intercept(k <sub>2</sub> ) (c) capacitive and diffusion control process of La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> electrode at 10mV/s, (d) capacitive and diffusion control percentage with different scan rate at discharge peak potential (-0.96V)	171
Figure 6.9	(a-b) corresponds to Trasatti plot at scan rate of 100mV/s to 1mV/s	172
Figure 6.10	a) Charge–discharge plot (V vs. time) of the La <sub>1-x</sub> K <sub>x</sub> FeO <sub>3-δ</sub> (x = 0, 0.3, 0.4, 0.5) electrode at 1 A/g; (b) charge–discharge plot (potential (V) vs. time (t)) of the La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> electrode; (c) capacitance performance of the La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> 2 M KOH electrolyte at different constant currents; (d) capacitive retention and Coulombic efficiencywith cycle number	173
Figure 6.11	Electrochemical impedance spectroscopy (EIS) at 10 mV applied	174

voltage from 1 MHz to 0.1 Hz.		
Figure 6.12	Full-cell (ASC) performances of activated carbon vs. the La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> electrode. (a) CV of individual electrodes at 10 mV/s with respect to the Hg/HgO electrode; (b) CV at different scan rates of ASCs; (c) charge-discharge plot; (d) capacitance retention and Coulombic efficiency with 2000 cycles at 5 A/g constant currents of the full cell; and	175
Figure 6.13	Electrochemical impedance spectroscopy (EIS) at 10 mV applied voltage from 1 MHz to 0.1 Hz.	176
Figure 6.14	Ragone plot of the ASCs (La <sub>0.5</sub> K <sub>0.5</sub> FeO <sub>3-δ</sub> //AC) in full cell	177
Figure 7. 1	Schematic representation of synthesis process of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O and anhydrous NiC <sub>2</sub> O <sub>4</sub> quantum dots (QDs)	187
Figure. 7.2.	(a) xrd pattern of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs (b) anhydrous NiC <sub>2</sub> O <sub>4</sub> QDs	189
Figure 7.3	TGA and DTA of bulk NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O and NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs sample	190
Figure 7.4	FT-IR spectrums of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and anhydrous NiC <sub>2</sub> O <sub>4</sub> QDs powder samples	191
Figure. 7.5	BET surface area measurements plot of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs	192
Figure 7.6	Raman shift of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs	193
Figure 7.7	a) UV absorbance of bulk and NiC <sub>2</sub> O <sub>4</sub> QDs sample (b) bandgap of bulk and NiC <sub>2</sub> O <sub>4</sub> QDs	194
Figure 7.8	XPS plot of (a) full survey NiC <sub>2</sub> O <sub>4</sub> QDs (b) Ni (2p) spectrum and (c) Co 2p spectrum (d) O (1s) spectrum	195
Figure 7.9	HRSEM image showing the morphology and particle size distribution of (a) NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs (b) anhydrous NiC <sub>2</sub> O <sub>4</sub> QDs, (c) EDX of anhydrous NiC <sub>2</sub> O <sub>4</sub> QDs (d-f) elemental distribution of Ni, C, O of NiC <sub>2</sub> O <sub>4</sub> QD	196
Figure. 7.10	HRTEM image at localized regions showing QDs of (a) NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs particle size with distribution (with FFT and inverse FFT) (b) calculating d-spacing of (202) plane (c) NiC <sub>2</sub> O <sub>4</sub> .QDs particle size with distribution (with FFT and inverse FFT) and (d) d-spacing of (110) plane.	197
Figure. 7.11	(a) Cyclic voltammetry of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs (b) cyclic voltammetry	199

of anhydrous NiC <sub>2</sub> O <sub>4</sub> QDs (c) comparative cyclic voltammetry of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs at 10mV/s		
Figure 7.12	The plot of log(peak current vs. square root of scan rate of 200 NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs	200
Figure 7.13	b value of Plot of the linear relationship between log (peak current) and log (scan rate) of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs	201
Figure 7.14	(a Contribution of diffusive and capacitive at different scan rates contribution of NiC <sub>2</sub> O <sub>4</sub> QDs (b) Analysis of kinetic contribution at 10 mVs <sup>-1</sup> of NiC <sub>2</sub> O <sub>4</sub> QDs	202
Figure 7. 15	(a-b)Corresponding to Trasatti's plot of NiC <sub>2</sub> O <sub>4</sub> QDs	204
Figure 7.16.	(a) The comparative charge-discharge curve at 1A/g of NiC <sub>2</sub> O <sub>4</sub> 2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs (b-c) charge-charge curve of NiC <sub>2</sub> O <sub>4</sub> 2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDsrespectively (d) capacitance performance of NiC <sub>2</sub> O <sub>4</sub> QDs at different constant current rates (e) capacitance retention and coulombic efficiency of porous NiC <sub>2</sub> O <sub>4</sub> QDs	205
Figure 7.17	EIS plot of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O and porous NiC <sub>2</sub> O <sub>4</sub> QDs at 10mV (AC)	206
Figure. 7.18	plot for activated carbon and non-hydrate NiC <sub>2</sub> O <sub>4</sub> QDs cell in ASC mode (a) Compare single electrode CV of Activated Carbonvs.NiC <sub>2</sub> O <sub>4</sub> 2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs at 10 mV/s, in 2M KOH (b) compare Full cell CV both NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs at 10 mV/s scan rates in 2M KOH, (c-d) Full cell CV of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O and NiC <sub>2</sub> O <sub>4</sub> QDs at different scan rate charge-discharge in 2M KOH respectively	208
Figure. 7.19	(a) compare Full cell charge-discharge of both NiC <sub>2</sub> O <sub>4</sub> 2H <sub>2</sub> O QDs and NiC <sub>2</sub> O <sub>4</sub> QDs at 1A/g in 2M KOH (b-c) Full cell charge-discharge of both NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs NiC <sub>2</sub> O <sub>4</sub> QDs at a different constant current in 2M respectively (d) Capacitance retention and coulombic efficiency of NiC <sub>2</sub> O <sub>4</sub> QDs in 2M KOH	209
Figure 7.20	shows a comparative EIS plot (Nyquist) of NiC <sub>2</sub> O <sub>4</sub> .2H <sub>2</sub> O QDs and anhydrous NiC <sub>2</sub> O <sub>4</sub> QDs in the frequency range (1MHz to 0.1Hz) at 10mV/s shows, that anhydrous NiC <sub>2</sub> O <sub>4</sub> QDs has higher charge transformation and higher diffusion behavior in the low-frequency region	209

- Figure 7.21 a) compare Full cell charge-discharge of both  $\text{NiC}_2\text{O}_4 \cdot 2\text{H}_2\text{O}$  QDs and  $\text{NiC}_2\text{O}_4$  QDs at 1A/g (b) compare Full cell charge-discharge of  $\text{NiC}_2\text{O}_4$  QDs at different constant current (c) EIS both  $\text{NiC}_2\text{O}_4 \cdot 2\text{H}_2\text{O}$  QDs and  $\text{NiC}_2\text{O}_4$  QDs at 10 mV(AC) 211
- Figure. 7.22 (a) Full cell CV  $\text{NiC}_2\text{O}_4$  QDs // Activated Carbon in 1M  $\text{Na}_2\text{SO}_4$  (b) Full cell charge-discharge of  $\text{NiC}_2\text{O}_4$  QDs in 1M  $\text{Na}_2\text{SO}_4$  at different constant current (c) EIS both  $\text{NiC}_2\text{O}_4 \cdot 2\text{H}_2\text{O}$  QDs and  $\text{NiC}_2\text{O}_4$  QDs at 10 mV(AC) (d) Capacitance retention and coulombic efficiency of  $\text{NiC}_2\text{O}_4$  QDs 212
- Figure 7.23 Ragone plot (Energy density vs. power density) of  $\text{NiC}_2\text{O}_4$  QDs in 2M KOH and 1M  $\text{Na}_2\text{SO}_4$  213

## List of tables

---

Table No.		Page No.
Table 1.1	Type of renewable energy source and application	5
Table 3.1	Structural Parameters of $\text{Ni}_x\text{Co}_{1-x}\text{O}$ ( $0 \leq x \leq 0.4$ )	83
Table 3.2	Tafel slope and Overpotential values of $\text{Ni}_x\text{Co}_{1-x}\text{O}$ ( $0 \leq x \leq 0.4$ ) at 1M and 5M KOH	90
Table 4.1:	lattice parameter of $\text{Ba}_{1-x}\text{Sr}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ )	103
Table 5.1	lattice parameter of $\text{La}_{1-x}\text{K}_x\text{CoO}_{3-\delta}$ ( $0 \leq x \leq 0.5$ )	128
Table 6.1	Structural parameter of $\text{La}_{1-x}\text{K}_x\text{FeO}_3$ ( $0 \leq x \leq 0.5$ ) obtained Rietveld refinement	162
Table 6.2	Determination of diffusion coefficient	168