
Contents

Contents	xiii
List of Figures	xvii
List of Tables	xxi
List of Abbreviations	xxiii
List of Symbols	xxv
Preface	xxvii
i Introduction and Literature Review	1
1 Introduction and Literature Review	3
1.1 Introduction	3
1.2 The Origin of HPM	5
1.3 Overview and Development of Various HPM Tubes	6
1.3.1 Relativistic Backward Wave Oscillator (RBWO)	6
1.3.2 Relativistic Magnetron (RM)	7
1.3.3 Relativistic Klystron Amplifier (RKA) and, Relativistic Klystron Oscillator (RKO)	9
1.3.4 Magnetically Insulated Line Oscillator (MILO)	11
1.3.5 Split Cavity Oscillator (SCO)	14
1.3.6 Transit-Time Oscillator (TTO)	15
1.3.7 Plasma Assisted Slow-wave Oscillator (PASOTRON)	16
1.3.8 Arletron	17
1.4 Literature Review on Reltron	18
1.4.1 Time-line of reltron deveopment	19
1.4.2 Literature review	21
1.4.3 Standpoint of Reltron	29
1.5 Motivation and Problem Definition	30
1.5.1 Motivation	30
1.5.2 Problem definition	30
1.6 Plan and Scope	31
1.7 Conclusion	32
ii Parametric Study of Normal Mode Frequencies and Cold-test Results[†]	33

2	Parametric Study of Normal Mode Frequencies and Cold-test Results	35
2.1	Introduction	35
2.2	Concept of the Design	36
2.2.1	Beam injector	36
2.2.2	Modulation section	37
2.2.3	Postacceleration section	40
2.2.4	Extraction section	40
2.3	Working Principle	40
2.4	Attractive Features	41
2.5	Mode Designation	42
2.5.1	Eigenmode solver	44
2.6	Parametric study of Normal Mode Frequencies	45
2.7	Simulation of S-parameter	46
2.7.1	Frequency-domain solver	48
2.8	Calculation of Quality-factor and Cavity Reactance	49
2.9	Construction of a Test-cavity and S_{11} Measurement	51
2.9.1	Construction of test-cavity	51
2.9.2	Cold-test results	52
2.10	Conclusion	53
iii	Electromagnetic Analysis[§]	57
3	Electromagnetic Analysis	59
3.1	Introduction	59
3.2	Magnetic Coupling in Dominant Pillbox-cavity Mode	60
3.3	Normal Modes	61
3.4	Dispersion Relation from Lumped-element Equivalent Circuit Model	62
3.5	Conclusion	68
iv	PIC Simulation and Results^{† §}	69
4	PIC Simulation and Results	71
4.1	Introduction	71
4.2	PIC Solver of CST MWS	71
4.3	Modeling and Simulation Set-up	72
4.4	Results and Discussions	75
4.4.1	Temporal port-signal and output power	75
4.4.2	Oscillation frequency	75
4.4.3	Temporal current signals	77
4.4.4	Frequency tunability	78
4.4.5	Phase-space plot	79
4.4.6	Effect of Idler disc length (l_{idl}) and Coupling depth (d) on the device performance	84
4.5	Conclusion	85
v	Performance Improvement^{††}	89

5	Performance Improvement	91
5.1	Introduction	91
5.2	Design of the DSC Reltron’s Modulation Section	92
5.3	Beam-absent (Cold) Simulation and Results	93
5.3.1	Normal modes of DSC reltron	93
5.3.2	S-parameter	95
5.4	Beam-present (Hot) Simulation and Results	97
5.5	Results and Discussions	98
5.6	Conclusion	102
vi	Summary, Conclusion and Future scope	103
6	Summary, Conclusion and Future scope	105
6.1	Introduction	105
6.2	Summary and Conclusion	106
6.2.1	Chapter 1	106
6.2.2	Chapter 2	106
6.2.3	Chapter 3	108
6.2.4	Chapter 4	109
6.2.5	Chapter 5	109
6.3	Limitation of Present Work and Further Scope	111
	References	113
	Author’s Relevant Publication	123

List of Figures

1.1	Schematic diagram of RBWO (a) with resonant reflector [Guinn <i>et al.</i> (1998)], and (b) with electron collector [Chen <i>et al.</i> (2002)].	6
1.2	(a) Interconnection geometries of phased locked RM [Levine <i>et al.</i> (1991)], and (b) frequency-agile RM (RS10) [Levine <i>et al.</i> (1995)].	8
1.3	Schematic diagram of tri-axial RKA [Friedman <i>et al.</i> (1993)].	10
1.4	MILO in (a) bifrequency configuration [Chen <i>et al.</i> (2009)], and (b) a dual-band HPM source [Zhang <i>et al.</i> (2015)].	13
1.5	SCO (a) fundamental mode, and (b) schematic of experiment [Marder <i>et al.</i> (1992)].	14
1.6	Schematic diagram of (a) radial acceleretron [Arman (1996)], and (b) low-impedance TTO (LITTO) [Cao <i>et al.</i> (2009)].	15
1.7	Schematic diagram of (a) rippled waveguide SWS PASOTRON, (b) helix-PASOTRON HPM source [Goebel <i>et al.</i> (1996)].	16
1.8	Arletron (a) experimental set-up, and (b) MAGIC 3D simulation. [Gardelle <i>et al.</i> (2010)].	18
1.9	Specific energy/pulse \times efficiency versus power for a variety of HPM sources [Barker <i>et al.</i> (2001)].	19
1.10	Schematic diagram of reltron [Miller <i>et al.</i> (1992)].	20
1.11	Growth of microwave devices in terms of Pf^2 [Benford <i>et al.</i> (2007)].	29
2.1	Schematic of reltron tube.	36
2.2	3D model of gridded reltron's modulation section (a) perspective view, and (b) cross-sectional view.	37
2.3	(a) Simulation model of the modulation section, and electric field vector-plots of (b) 0, (c) $\pi/2$, and (d) π mode, respectively [Miller <i>et al.</i> (1992)].	43
2.4	(a), (b), and (c) electric field vector plot in 0, $\pi/2$ and π modes; (d), (e), and (f) contour plots of the respective modes in reltron modulation cavity using MAGIC.	44
2.5	Frequencies of resonant mode (GHz) vs. cavity dimension (mm) – (a) length of main cavity, (b) radius of main cavity radius, (c) length of side cavity, (d) radius of side cavity, (e) length of idler disc, (f) radius of idler disc, and (g) depth of coupling.	46
2.6	An enlarged view of waveguide port on SMA connector for obtaining S_{11}	47
2.7	Simulated S-parameter of reltron modulation section. Marker 1, 2 and 3 correspond to 0, $\pi/2$, and π mode, respectively.	48
2.8	Impedance locus of S_{11} . Marker 1, 2, and 3 correspond to complex impedance in 0, $\pi/2$, and π mode, respectively.	50

2.9	Equivalent model of reltron cavity for obtaining cavity reactance.	50
2.10	Construction of reltron modulation section showing– (a) different parts of the cavity, (b) the main cavity being joined with the side cavity by gas welding, and (c) final structure.	51
2.11	(a) Experimental set-up, and (b) measured S_{11}	53
2.12	Combined picture of simulated and measured S_{11}	54
3.1	Electric field and surface current in dominant TM_{010} mode in a pillbox cavity shown in– (a) and (b) perspective view, (c) and (d) cross-sectional view.	61
3.2	Disassembled schematic diagram of reltron modulation section.	62
3.3	Equivalent circuit model of reltron modulation section.	62
3.4	(a) Model of reltron modulation section in MAGIC 3D (end wall of the coupling cavity is not shown), and (b) contour plot of $\pi/2$ mode in the cavity cross sectional view along y-z plane.	65
3.5	Mode frequencies at different (d) from CST MWS, and MAGIC.	67
3.6	Variation of ω_c and k with coupling depth (d).	67
4.1	Cross sectional view of S-band reltron showing different sections, and the coupling depth (d).	73
4.2	Temporal signals from the waveguide ports for different coupling depth (d).	75
4.3	Total output power for different coupling depth (d).	76
4.4	The spectrum of port signal for different coupling depth (d), showing the fundamental modes and their harmonics. An enlarged view of the fundamental mode is shown inset.	76
4.5	Temporal currents at (a) cathode, (b) first cavity, (c) second cavity, and (d) collector.	77
4.6	Frequency tunability achievable by varying the dimensional parameters of modulation section.	78
4.7	Electron positions in real space. Color-bar shows the normalized momentum.	79
4.8	Phase space plot of electron energy (eV). Three combined frames showing (a) deceleration in the first cavity and acceleration in the second, (b) acceleration in the first cavity and deceleration in the second.	80
4.9	Phase space plot showing energy of electrons (eV) during a complete cycle of oscillation (part 1 of 2).	81
4.10	Phase space plot showing energy of electrons (eV) during a complete cycle of oscillation (part 2 of 2).	82
4.11	Phase space plot showing normalized momentum vs position at an instant of (a) first and (b) second half cycle of RF oscillation. The dotted lines indicate different sections.	83
4.12	Reduction in (a) energy spread, and (b) velocity spread in the post acceleration section, with respect to the modulation section, respectively.	83
4.13	Output power (W) at different idler disc lengths (mm).	84
4.14	Fourier transform of output port signals for $L_{idl} =$ (a) 10 mm, (b) 11 mm, (c) 12 mm, and (d) 13 mm.	85

5.1	The modulation section of a DSC reltron. (a) Perspective view (cavity side-walls are made transparent for a better view) and, (b) cross-sectional view.	92
5.2	A cross-sectional view of the modulation section of a DSC reltron showing vector plots of (a) mode 0: 2.649481 GHz, (b) mode $\pi/2$: 2.763429 GHz, (c) mode pseudo- $\pi/2$: 2.806426 GHz and, (d) mode π : 3.067092 GHz, respectively.	94
5.3	A cross-sectional view of the modulation section of a DSC reltron showing contour plots of (a) mode 0: 2.649481 GHz, (b) mode $\pi/2$: 2.763429 GHz, (c) mode pseudo- $\pi/2$: 2.806426 GHz and, (d) mode π : 3.067092 GHz, respectively.	94
5.4	Simulated S-parameter of DSC reltron modulation section from (a) Frequency-domain solver, and (b) Transient solver (inset: without AR-filtering). Marker 1, 2, and 3 correspond to 0, $\pi/2$, and π mode, respectively.	96
5.5	The cross-sectional view of a DSC grid-less reltron with dual extraction cavity.	98
5.6	(a) Port signals (\sqrt{W}) from one of the extraction cavity for fixed cathode potential of 100 kV, (b) the corresponding first harmonics.	99
5.7	Spectrum of the port signals in (a) fundamental mode, and (b) first harmonics. Data markers indicate the frequencies (GHz) and corresponding amplitudes (V/m/GHz).	99
5.8	Contour plot of electrostatic potential for cathode potential of 100 kV and PA potential of (a) 200 kV and (b) 400 kV respectively.	100
5.9	Temporal current (Amp) at (a) cathode, (b) first cavity, (c) second cavity and, (d) collector	101
5.10	Phase space plot in two opposite cycles of the RF oscillation.	101
5.11	Temporal field amplitude of fundamental mode of – (a) conventional, and (b) double side-cavity reltron.	102

List of Tables

1.1	Summary of experimental developments on reltrons	28
2.1	Comparison of normal mode frequencies (GHz) between MAGIC, and CST (Eigenmode)	43
2.2	Dimensions of the modulation cavity for maximum mode separation.	47
2.3	Comparison of normal mode frequencies (GHz), and that of S_{11} minima.	48
2.4	Quality factors, inductance and capacitance of the cavity in respective modes	50
2.5	Frequencies (GHz) of measured, and simulated S_{11} minima.	53
2.6	Summary of change in resonant mode frequencies with cavity parameters.	55
3.1	Resonant frequencies at different d , and the corresponding ω_c and k	67
4.1	Dimensions and Materials Used in PIC Simulation	74
4.2	Frequency, Output power and efficiency at different idler disc length	85
4.3	Summary of frequency and efficiency at different coupling depth	86
5.1	Dimensions of the modulation section.	93
5.2	Comparison among frequencies (GHz) of normal modes (Eigenmode solver) and S-parameter minima from Freq. domain (F.D.) solver, and Transient (T.D.) solver	97
5.3	Parameters and dimensions used in PIC simulation	97
5.4	Estimation of output power and efficiency.	100

