

Contents

Abstract	v
List of Figures	xi
Nomenclature	xv
List of Tables	1
1 Introduction	3
1.1 Background	3
1.2 Photovoltaic Power Generation	5
1.3 Challenges in Photovoltaic (PV) System	6
1.4 Photovoltaic (PV) Cell or Solar Cell	6
1.5 Types of PV Cell	7
1.5.1 Monocrystalline PV Cell	7
1.5.2 Polycrystalline PV Cell	7
1.5.3 Thin-film PV Cell	8
1.6 Photovoltaic Energy Conversion Technology	10
1.7 Types of PV system	11
1.7.1 Grid-Connected PV System	12
1.7.2 Stand-Alone PV System	12
1.7.3 Hybrid PV System	13
1.8 DC-DC Converter	15
1.9 Motivation	15
1.10 Aim of the Thesis	15
1.11 Structure of the Thesis	16

2 Maximum Power Point techniques	17
2.1 Introduction	17
2.2 Input Parameter Based MPPT Algorithms	17
2.3 Output Parameter Based MPPT Algorithms	18
2.4 Distributed MPPT Techniques	20
2.5 MPPT Algorithm Control Techniques	23
2.5.1 Reference Voltage Control	23
2.5.2 Reference Current Control	25
2.5.3 Direct Duty-Ratio Control	25
2.6 Maximum Power Point Tracking Parameters	27
2.6.1 Selecting Proper Perturbation Time T_s	27
2.6.2 Selecting Proper Perturbation Step-Size ΔD	27
2.7 Convergence Response of MPPT Algorithm	27
2.7.1 Convergence Time	28
2.7.2 Convergence Response	28
3 A Current Sensor Based Adaptive Step-Size MPPT With SEPIC Converter for PV Systems	29
3.1 Introduction	29
3.2 The Linearity of PV Current with Insolation	31
3.2.1 Switching Function for SEPIC Converter	32
3.2.2 Switching Function for Buck Converter	35
3.2.3 Switching Function for Boost Converter	35
3.3 A Novel Adaptive MPPT Technique	37
3.4 Design of the SEPIC Converter	38
3.4.1 Duty-Cycle Consideration	40
3.4.2 Inductor Selection	40
3.4.3 Output capacitor selection	41
3.4.4 Coupling Capacitor Selection	41
3.4.5 Input Capacitor Selection	42
3.5 Simulation Results	42
3.5.1 Comparison Between Fixed And Adaptive Step-Size	43

3.5.2	Comparison Between Current And Voltage Sensor Based (VSB) MPPT Techniques	43
3.5.3	Simulation Results with Different Operating Conditions	45
3.5.4	Performance Comparison	49
3.6	Experimental Setup And Validation	53
4	Load Voltage-Based MPPT Technique for Standalone PV Systems Us- ing Adaptive Step	61
4.1	Introduction	61
4.2	Problem Formulation	63
4.3	Analysis of Load Voltage Based MPPT Technique	65
4.4	Proposed Load Voltage Based MPPT Technique	66
4.4.1	LVB MPPT Technique with FSS	67
4.4.2	LVB MPPT Technique with ASS	67
4.5	Design and Operation of the SEPIC Converter	69
4.6	Transition Analysis	71
4.7	Simulation Results	72
4.7.1	Tracking Efficiency	74
4.7.2	Ropp Test	77
4.8	Hardware Implementation and Experimental Results Validation	78
5	Conclusions and Future Work	87
5.1	Summary and Contribution	87
5.2	Future Work	88

List of Figures

1.1	Global electricity consumption.	4
1.2	Electricity consumption in India.	4
1.3	India - source wise installed power generation capacity.	4
1.4	Monocrystalline PV module.	8
1.5	Polycrystalline PV module.	9
1.6	Thin-film PV module.	9
1.7	Formation of PV array from a PV cell.	10
1.8	Conversion mechanism of solar insolation into electricity.	11
1.9	Classification of PV systems.	11
1.10	Block diagram of grid-connected PV system.	12
1.11	Block diagram of stand-alone PV system with battery storage.	13
1.12	Block diagram of photovoltaic hybrid system.	14
2.1	I-V and P-V characteristics curve of PV module.	18
2.2	Block diagram of PV system with input parameter based MPPT controller. .	19
2.3	Block diagram of PV system with output parameter based MPPT controller. .	19
2.4	Types of MPPT methods.	20
2.5	Distributed PV system.	21
2.6	I-V characteristics of a PV array with three modules with different insolation.	22
2.7	P-V characteristics of a PV array with three modules with different insolation.	22
2.8	Grid connected DMPPT PV system with output ports connected in series. .	23
2.9	Grid connected DMPPT PV system with output ports connected in parallel. .	24
2.10	Reference voltage control MPPT technique for PV system.	25
2.11	Reference current control MPPT technique for PV system.	26
2.12	Direct duty-ratio control MPPT technique for PV system.	26

3.1	PV system with the MPPT controller.	33
3.2	Normalized variation of P_{pv}, S for a PV module.	34
3.3	Variation of S for a step change in insolation level.	36
3.4	Variation of S at steady-state.	36
3.5	PV power P_{pv} for different values of α	38
3.6	Flow-chart of CSB MPPT Technique with adaptive step-size.	39
3.7	Circuit model of PV system with MPPT.	42
3.8	Convergence response of CSB MPPT technique using fixed and adaptive step-size with resistive load. (a) PV Current I_{pv} (b) PV Voltage V_{pv} (c) PV Power P_{pv} (d) Duty-cycle D	44
3.9	PV power P_{pv} at steady-state. (a) Voltage sensor based MPPT. (b) Current sensor based MPPT.	46
3.10	Comparison of dynamic performance at $G = 800 \text{ W/m}^2$	47
3.11	Switching functions vs duty-cycle ($S, Q - D$) characteristics.	47
3.12	PV power P_{pv} with different loads.	48
3.13	Load power P_o with different loads.	48
3.14	PV power P_{pv} with RL and RC loads.	48
3.15	PV power P_{pv} with variable temperature.	49
3.16	PV power P_{pv} with different switching frequencies.	49
3.17	Comparison of adaptive current sensor based MPPT technique and enhanced auto scaling IncCond MPPT technique with resistive load.	51
3.18	Comparison of duty-cycle at steady state for CSB (ASS) MPPT and EAS IncCond MPPT techniques.	51
3.19	Comparison of adaptive current sensor based MPPT technique and enhanced auto scaling IncCond MPPT technique with battery load.	52
3.20	Experimental model of the PV system.	53
3.21	Convergence response of CSB MPPT technique using FSS with resistive load. (a) start-up at $G = 800 \text{ W/m}^2$ (b) for increase in insolation level (c) for decrease in insolation level.	55
3.22	Convergence response of CSB MPPT technique using ASS with resistive load. (a) start-up at $G = 800 \text{ W/m}^2$ (b) for increase in insolation level (c) for decrease in insolation level.	56

3.23 Two level operation at steady-state for $G = 500 \text{ W/m}^2$ with CSB (ASS) MPPT Technique using $T_s = 1 \text{ s}$	57
3.24 Convergence response of CSB (ASS) MPPT technique with battery load for start-up at $G = 800 \text{ W/m}^2$	57
3.25 Convergence response of EAS IncCond MPPT technique with battery load for start-up at $G = 800 \text{ W/m}^2$	58
4.1 Block diagram PV system with MPPT controller.	64
4.2 Characteristics waveforms of $P_{pv} - D$ and $V_L - D$.	66
4.3 Adaptive step-size MPPT algorithm flowchart.	68
4.4 Circuit model of developed PV system.	70
4.5 Inductor L_1 current waveform.	71
4.6 Inductor L_2 current waveform.	71
4.7 $V_L - D$ characteristic at different insolation level.	72
4.8 Duty-ratio waveform for LVB MPPT method using FSS and ASS for resistive load.	74
4.9 Converter output convergence responses with LVB MPPT method using FSS and ASS for resistive load (a) Load Voltage (V_L) (b) Load Current (I_L) (c) Load Power (P_L).	75
4.10 Converter input convergence responses with LVB MPPT method using FSS and ASS for resistive load (a) PV Voltage (V_{pv}) (b) PV Current (I_{pv}) (c) PV Power (P_{pv}).	76
4.11 Comparison of proposed LVB (ASS) MPPT method with P&O. and Inc- Cond method.	77
4.12 Ropp profile of insolation-level.	78
4.13 PV power P_{pv} with LVB MPPT method using FSS and ASS.	79
4.14 Developed hardware setup of PV system for experimental validation.	79
4.15 Load voltage (V_L) and load current (I_L) convergence responses with FSS method (a) start-up for $G = 270 \text{ W/m}^2$ (b) for change in insolation from $G = 270 \text{ W/m}^2$ to 500 W/m^2 (c) for change in insolation from $G = 500$ W/m^2 to 270 W/m^2 .	82

4.16 Load voltage (V_L) and load current (I_L) convergence responses with ASS method (a) start-up for $G = 270 \text{ W/m}^2$ (b) for change in insolation from $G = 270 \text{ W/m}^2$ to 500 W/m^2 (c) for change in insolation from $G = 500 \text{ W/m}^2$ to 270 W/m^2	83
4.17 PV voltage (V_{pv}) and PV current (I_{pv}) convergence responses with FSS method (a) start-up for $G = 270 \text{ W/m}^2$ (b) for change in insolation from $G = 270 \text{ W/m}^2$ to 500 W/m^2 (c) for change in insolation from $G = 500 \text{ W/m}^2$ to 270 W/m^2	84
4.18 PV voltage (V_{pv}) and PV current (I_{pv}) convergence responses with ASS method (a) start-up for $G = 270 \text{ W/m}^2$ (b) for change in insolation from $G = 270 \text{ W/m}^2$ to 500 W/m^2 (c) for change in insolation from $G = 500 \text{ W/m}^2$ to 270 W/m^2	85
4.19 Convergence response of PV voltage (V_{pv}) and PV current (I_{pv}) using fixed step-size at $G = 270 \text{ W/m}^2$ for P&O algorithm.	86
4.20 Convergence response of PV voltage (V_{pv}) and PV current (I_{pv}) using fixed step-size at $G = 270 \text{ W/m}^2$ for IncCond algorithm.	86

List of Tables

2.1	Comparison of MPPT techniques	20
3.1	SEPIC converter design consideration.	40
3.2	Comparison of CSB (ASS) MPPT with enhanced auto scaling IncCond MPPT technique.	52
3.3	Comparison of experimental results of CSB MPPT technique using fixed and adaptive step-size with resistive load.	59
3.4	Comparison of experimental results of CSB MPPT technique using adap- tive step-size and EAS IncCond with battery load.	59
3.5	Comparison of simulation and experimental results of CSB MPPT tech- nique using adaptive step-size with resistive load.	59
4.1	Design parameters of SEPIC Converter	73
4.2	Comparison of simulation results of MPPT techniques	77
4.3	Comparison of experimental results of MPPT techniques	81