

Contents

Title		Page No.
Title of Thesis		I
Certificates		II-IV
Dedication		V
Acknowledgements		VI-IX
Table of contents		X-XIII
List of Figures		XIV-XVIII
List of Tables		XIX
List of Symbols		XX
List of Abbreviation		XXI-XXII
Preface		XXIII-XXV
Chapter 1	Introduction	1-7
1.1	Introduction	1
1.2	Problem Statement	5
Chapter 2	Literature Review	8-60
2.0	• MOFs Introduction	8
2.1	• Hydrogen: The Global Perspective	10
2.1.1	• Current status of Hydrogen	12
2.2	• Biomass	13
2.3	• Bio-oil	14
2.3.1	• Bio-oil properties	15
2.3.2	• Drawbacks of bio-oil	17
2.4	• Steam Reforming	18
2.5	• Partial Oxidation	20
2.6	• Oxidative steam reforming	21
2.7	• Aqueous phase reforming	22
2.8	Acetic acid as a model compound of bio-oil	24
2.8.1	• Reaction network and coke formation mechanism of AASR	26
2.9	• Nature of carbon deposition during AASR	32-36

2.10	• Kinetic studies of steam reforming	37
2.10.1	• Effect of operating parameters on AASR and coke deposition	37
2.11	• Effect of choice of reactors	38-43
2.12	• Catalyst consideration for AASR	43-57
	➤ Active metals	43
	➤ Noble metal	44
	➤ Transition Metal	45
	➤ Cobalt	45
	➤ Nickel	46
	➤ Active metal sintering	48
	➤ Additives	49
2.13	• Effect of support	49
	➤ Al ₂ O ₃	51
	➤ ZrO ₂	51
	➤ CeO ₂	52
	➤ La ₂ O ₃	54
2.14	• Effect of alkali and alkaline earth metals	55
2.15	• Summary of literature review	58-59
2.16	• Objective of the present research work	60
Chapter 3	Experimental	61-77
3.1	• Materials and Methods	61
3.1.1	• Preparation of Alumina and Alumina lanthanum cerium (ALC) support	61
3.1.2	➤ Synthesis of Ni/ALC Catalyst	63
3.1.3	➤ Synthesis of Ni-complex and Ni-complex/ALC catalysts	64-66
3.1.4	➤ Table of synthesized catalysts	67
3.2	• Experimental set-up for steam reforming reaction	67
3.2.1	➤ Feed section	67
3.2.2	➤ Reaction section	69
3.2.3	➤ Product analysis	70

3.3	• Characterization of catalysts	71
3.3.1	➤ X-Ray diffraction (XRD)	72
3.3.2	➤ Transmission electron microscope (TEM) and selected area diffraction (SAED)	73
3.3.3	➤ X-Ray Photoelectron spectroscopy	74
3.3.4	➤ Temperature Programmed Reduction (TPR)	75
3.3.5	➤ Thermo gravimetric analysis (DT-TGA)	75
3.3.6	➤ Scanning electron microscopy (SEM/EDAX)	76
3.3.7	➤ Low temperature N ₂ adsorption and desorption (BET analysis)	76
Chapter 4	• Results and discussion	78
Section: I	• Comparative study of hydrogen production from steam reforming of acetic acid over synthesized catalysts via MOF and wet impregnation method	78-98
4.0	➤ Introduction	78
4.1	➤ Characterization of precursors	78
4.2	➤ XRD analysis of catalysts	81
4.3	➤ TPR analysis	82
4.4	➤ Surface area and pore size analysis	84
4.5	➤ TEM analysis	85
4.6	➤ SEM/EDAX analysis	87
4.7	➤ XPS analysis	89
4.8	➤ Catalytic activity and yield of catalysts	92-95
4.9	➤ Stability Test	95
4.10	➤ DT-TGA analysis of spent catalysts	96
	➤ Summary	97-98
Section: II	• Effect of Ni loading on catalytic activity and products distribution for acetic acid steam reforming over nickel-based catalyst synthesized via MOF process	99-115
5.0	➤ Introduction	99
5.1	➤ Characterization of catalyst	99-106
5.1.1	➤ XRD analysis	99

5.1.2	➤ Surface area and pore size analysis	101
5.1.3	➤ TPR analysis	103
5.1.4	➤ SEM analysis	105
	➤ TEM analysis	106
5.2	• Effect of the operating variables on the performance of catalysts	107
5.2.1	➤ Effects of temperatures	107
5.2.2	➤ Effects of Ni loadings on product distribution	110
5.2.3	• Effect of Ni loading over catalytic stability and coke deposition behaviour	111
5.3	• DT-TGA analysis of spent catalysts	112
	• Summary	114-115
Section: III	• Activation, Deactivation and Kinetic studies	116-132
6.0	➤ Introduction	116
6.1	➤ Characterization of catalysts	116-123
6.1.1	➤ Surface area and pore size analysis	116
6.1.2	➤ XRD analysis	118
6.1.3	➤ TPR analysis	120
6.1.4	➤ SEM analysis	121
6.1.5	➤ DT-TGA analysis of spent catalysts	122
6.2	• Activation, deactivation and regeneration studies	123-129
6.2.1	➤ Effect of temperatures	123
6.2.2	➤ Effect feed flow rate	125
6.2.3	➤ Effect of steam to carbon molar ratio	127
6.2.4	➤ Catalyst stability and regeneration studies	129
	➤ Summary	131-132
Chapter 5	• Conclusions and Future Recommendations	133-137
	➤ References	138-154
	➤ Appendix	155-159
	➤ List of Publications	160

List of Figures

Figure No.	Figure Caption	Page No.
1.1	World energy consumption	2
1.2	Worldwide projection of carbon dioxide emission	3
2.1	Different sources of hydrogen generation	12
2.2	Strategies for production of fuels from lignocellulosic biomass	14
2.3	Possible route of hydrogen generation from biomass via steam reforming	19
2.4	The reaction mechanism for C–C and C–O breaking in the APR of ethylene glycol over a metal catalyst. The horizontal lines represent a metal surface	23
2.5	Schematic representation of acetic acid steam reforming	25
2.6	Schematic representation of reaction mechanism for acetic acid steam reforming	27
2.7	The dissociation patterns of acetic acid on catalyst surface	28
2.8	Assumed reaction pathways and carbon deposition mechanism from intermediate methyl group during AcOH during reforming	30
2.9	(a) TGA of used 15Ni/Al (inset, SEM micrographs of 15Ni/Al catalyst after reaction) and 15Ni5Mg/Al (inset, SEM micrographs of 15Ni5Mg/Al catalyst after reaction) catalysts performed under airflow and (b) derivative thermograms for used 15Ni/Al and 15Ni5Mg/Al catalysts	34
2.10	DTA analysis of used catalysts (a) 5Ni/MA, 5Cu/MA (b) 5Ni/ HifuelR-120.	35

2.11	Scanning electron microscopy and EDX scan of the used 12%Ni/CeO ₂ -ZrO ₂ catalyst	36
2.12	A typical schematic diagram of a fixed-bed setup for steam reforming of acetic acid	39
2.13	Schematic diagram of the two-stage reactors performing acetic acid cracking/regeneration sequences in opposition for continuous hydrogen production	40
2.14	Schematic diagram of the spouted bed reactor	41
2.15	A typical schematic representation of sorption enhanced assembly for AASR	42
2.16	HRTEM image of 15 Ni/Al catalyst (sintering process)	48
2.17	The oxidation of CO, coke and coke precursor via migrated oxygen vacancies in the lattice of CeO ₂ during the steam reforming of acetic acid	53
3.1	Process flow diagram for the preparation of support	62
3.2	Process flow diagram for the synthesis of supported catalyst	63
3.3	Process Flow diagram for the synthesis of monometallic complex of nickel	64
3.4	Ni-complex crystal	65
3.5	Process flow diagram for the preparation of supported monometallic catalyst	66
3.6	Process flow diagram for the Synthesis of Ni-Complex/ALC	66
3.7	Schematic diagram of experimental set-up	68
3.8	A real time experimental figure	70
4.1	TGA profiles of nickel formate (Ni(HCOO) ₂).2H ₂ O)	79
4.2	TGA and DTA profiles of Ni-complex	79

4.3	XRD pattern of monometallic complex of Ni	80
4.4	XRD Patterns of Alumina, ALC, Catalyst 1 and Catalyst 2	82
4.5	TPR profiles of Catalyst 1, Catalyst 2, and pure NiO	83
4.6	TEM image and SAED diffraction of Catalyst 1	86
4.7	TEM image and SAED diffraction of Catalyst 2	86
4.8	SEM analysis of Catalyst 1 and Catalyst 2	87
4.9	EDAX analysis of Catalyst 1	88
4.10	EDAX analysis of Catalyst 2	88
4.11	(A) Ce 3d XPS spectra of Catalyst 1 & (B) Catalyst 2	89
4.12	Conversion of AcOH and product distribution as a function of temperature over ALC support	93
4.13	Conversion of acetic acid and yield of the gaseous products over catalyst 1, catalyst 2 in the different temperature range of 400-650 °C. Experimental conditions: S/C mole ratio 6.5:1, mixture flow rate 2.5 mL/h	94
4.14	Conversion and H ₂ yield (%) of catalyst 1 and catalyst 2, Reaction condition: temperature - 600 °C; N ₂ flow rate- 30 mL/min; mixture flow rate -2.5 mL/h; and S/C-6.5 mole/mole	95
4.15	TGA-DTG profile of spent catalysts after stability test (a) TG (b) DTG	96
5.1	XRD patterns of catalyst 2, 3 and 4	100
5.2	N ₂ adsorption - desorption isotherms of the support and catalysts	101
5.3	TPR analysis of Catalysts 3, 2 and 4	104

5.4	SEM images of (A) Catalyst 3 (B) Catalyst 2 (C) Catalyst 4	105
5.5	TEM micrographs of (A) Catalyst 3 (B) Catalyst 2 (C) Catalyst 4	106
5.6	Acetic acid Conversion and the product distribution over reaction temperature and nickel loading; S/C = 6.5; WHSV= 1.2 h ⁻¹ ; P = 1atm	108-109
5.7	Effect of Ni loading as time on stream (a) AcOH conversion and (b) H ₂ yield	112
5.8	TG and DTG analysis of spent catalysts after 36 h TOS	113
6.1	N ₂ adsorption - desorption isotherms of the support and fresh catalyst	117
6.2	XRD patterns of (a) ALC support, (b) Fresh catalyst, (c) Deactivated, and (d) Regenerated catalyst	119
6.3	TPR profiles of 15%Ni-Comp/ALC catalyst and pure NiO	121
6.4	SEM image (A) 15 % Ni-Comp/ALC (Fresh) (B) 15% Ni-Comp/ALC (Spent) after 36h	122
6.5	TG-DTA analysis of fresh catalyst after 36 h TOS deactivation after 36 h of TOS	122
6.6	Conversion and yields of products over 15%Ni-Comp/ALC: S/C = 6.5, Feed flow rate = 2.5mL/h, P = 1 atm	124
6.7	Effect of the feed flow rate of AcOH mixture on conversion and yield of products over 15 wt%Ni-Comp/ALC; Temp 600 °C, S/C ratio - 6.5: 1, P=1atm	126
6.8	Effect of S/C ratio on conversion of AcOH and product distribution over 15%Ni-Comp/ALC at 600 °C, Feed flow rate– 2.5 mL/h, and P-1atm	127
6.9	AcOH conversion and yield of gaseous product versus reaction time over 15%Ni-Comp/ALC catalyst. Reaction condition: temperature-600 °C; N ₂ ; Feed flow rate-2.5 mL/h; and S/C- 6.5	129

- 6.10 AcOH conversion and Yield of gaseous products versus reaction time over regenerated 15% Ni-Comp/ALC catalyst. Reaction condition: temperature-600 °C; N₂ flow rate- 30mL/min; feed flow rate - 2.5 mL/h; and S/C- 6.5 mole/mole 131

List of Tables

Table No.	Title	Page No.
2.1	Combustion values of hydrogen and fossil fuels	11
2.2	Physical properties of bio-oil (pine wood) produced at different temperatures	15
2.3	Effects of S/C on acetic acid conversion and selectivity of gaseous product at T = 673 K; T=973 K LHSV = 10.1 h ⁻¹ ; P = 1 atm	38
2.4	Conversion, H ₂ yield, carbon deposition, and stability analysis during AASR over different type of catalysts	161
3.1	Table of synthesized catalysts	67
3.2	Characterization techniques used in the present study	72
4.1	Textural properties of synthesized catalysts	84
4.2	Pore size distribution of catalyst	85
4.3	Binding Energy (eV) (catalyst 1)	90
4.4	Binding Energy (eV) (catalyst 2)	92
5.1	Textural properties of fresh, deactivated and Regenerated catalysts	102
5.2	Pore size distribution of fresh, deactivated and Regenerated catalysts	103
6.1	Textural properties of synthesized catalysts	117
6.2	Pore size distribution of catalysts	118

List of Symbols

AcOH	Acetic acid
Dp	Crystallite size, nm
dp	Pore diameter
D	Crystalline lattice size
Ni(0)	Metallic nickel
T	Temperature, °C
Wt.	Weight of catalyst, g
Wt %	Weight percentage
XAcOH (%)	Acetic acid conversion
X _{C-C}	Carbon conversion
Y	Yield

List of Abbreviations

AASR	Acetic acid steam reforming
AcOH	Acetic acid
ALC	$\text{Al}_2\text{O}_3/\text{La}_2\text{O}_3/\text{CeO}_2$
$\gamma\text{-Al}_2\text{O}_3$	Gamma Alumina
APR	Aqueous phase reforming
BET	Brunauer-Emmet-Teller
C	Carbon/Coke
CeO_2	Cerium oxide
CO	Carbon monoxide
CO_2	Carbon die oxide
Comp	Complex
CH_4	Methane
DT-TGA	Differential thermal, Thermal gravimetric
EDAX	Energy dispersive Xray-analysis
TCD	Thermal Conductive Detector
FID	Flame Ionization Detector
GC	Gas Chromatography
H_2	Hydrogen
La_2O_3	Lanthanum oxide
MOFs	Metal Organic Frameworks

Ni	Nickel
Ni-complex	(Ni[bpy] ₂ Cl ₂)
OSR	Oxidative steam reforming
POX	Partial oxidation
RPM	Round per minute
RWGS	Reverse water gas shift reaction
S/C	Steam to carbon molar ratio
SEM	Scanning Electron Microscopy
TEM	Transmission Electron Microscopy
TPR	Temperature Programme Reduction
WGS	Water gas shift Reaction
WHSV	Weight hour space velocity
XPS	Xray-Photoelectron Spectroscopy
XRD	Xray-Diffraction analysis