

# Table of Contents

---

<b>Certificate</b>	iii
<b>Declaration by the Candidate</b>	v
<b>Copyright Transfer Certificate</b>	vii
<b>Acknowledgement</b>	xi
<b>Table of Contents</b>	xiii
<b>List of Figures</b>	xvii
<b>List of Tables</b>	xxiii
<b>List of Abbreviations</b>	xxv
<b>List of Symbols</b>	xxvii
<b>List of Illustrations</b>	xxix
<b>Abstract</b>	xxxix
<b>Chapter 1 INTRODUCTION</b>	<b>1</b>
1.1. General.....	1
1.2. Motivation for the study.....	3
1.3. Objective of the study.....	5
1.4. Outline of the thesis.....	5
<b>Chapter 2 LITERATURE REVIEW</b>	<b>9</b>
2.1. General.....	9
2.2. Strata behavior.....	10
2.2.1. Caving phenomena.....	10
2.2.2. Roof assessment techniques.....	12
2.2.3. Strata monitoring instruments.....	15
2.3. Pillar extraction schemes.....	17
2.3.1. Modified Navid.....	18
2.3.2. Fish-bone.....	19
2.3.3. Split and fender.....	20
2.3.4. One-third split and fender.....	22

2.3.5. Double split and fender.....	23
2.4. Panel designing techniques.....	24
2.4.1. Pillar design techniques.....	25
2.4.2. Remnant pillar design techniques.....	30
2.5. Concluding remarks.....	31
<b>Chapter 3 NUMERICAL SIMULATION METHODOLOGY</b>	<b>33</b>
3.1. General.....	33
3.2. Analyses tool.....	33
3.3. Design approach.....	34
3.3.1. Panel design approach.....	36
3.3.2. Remnant pillar design approach.....	38
3.4. Coal mass strength parameters.....	43
3.5. Concluding remarks.....	46
<b>Chapter 4 FIELD STUDY</b>	<b>49</b>
4.1. General.....	49
4.2. Case A.....	49
4.2.1. Depillaring operation in ‘Case A’.....	53
4.2.2. Numerical simulation for ‘Case A’.....	54
4.2.3. Simulation results for ‘Case A’.....	56
4.2.4. Field observations in ‘Case A’.....	59
4.3. Case B.....	62
4.3.1. Depillaring operation in ‘Case B’.....	64
4.3.2. Numerical simulation for ‘Case B’.....	65
4.3.3. Simulation results for ‘Case B’.....	67
4.3.4. Field observations in ‘Case B’.....	68
4.4. Case C.....	72
4.4.1. Depillaring operation in ‘Case C’.....	72
4.4.2. Numerical simulation for ‘Case C’.....	74
4.4.3. Simulation results for ‘Case C’.....	76
4.4.4. Field observations in ‘Case C’.....	78
4.5. Concluding remarks.....	81
<b>Chapter 5 DESIGN PARAMETERS FOR CM PANEL</b>	<b>83</b>

5.1. General.....	83
5.2. Design of the panel.....	83
5.2.1. Design parameters for panel.....	84
5.2.2. Numerical simulation for panel design.....	85
5.3. Design of the remnant pillar.....	86
5.3.1. Design parameters for remnant pillar.....	87
5.3.2. Numerical simulation for remnant pillar design.....	88
5.4. Concluding remarks.....	91
<b>Chapter 6 RESULTS AND ANALYSIS</b>	<b>93</b>
6.1. General.....	93
6.2. Panel design.....	93
6.2.1. Simulation results for pillar width of 26 m.....	94
6.2.2. Simulation results for pillar width of 35 m.....	97
6.2.3. Simulation results for pillar width of 45 m.....	102
6.2.4. Simulation results for pillar width of 48 m.....	112
6.2.5. Analysis for panel design.....	119
6.2.6. Guidelines for panel design.....	124
6.3. Remnant pillar design.....	127
6.3.1. Simulation results for pillar width of 26 m.....	129
6.3.2. Simulation results for pillar width of 35 m.....	133
6.3.3. Simulation results for pillar width of 45 m.....	137
6.3.4. Simulation results for pillar width of 48 m.....	144
6.3.5. Analysis for remnant pillar design.....	151
6.3.6. Guidelines for remnant pillar design.....	157
6.4. Concluding remarks.....	160
<b>Chapter 7 CONCLUSION AND SUGGESTIONS</b>	<b>161</b>
<b>References</b>	<b>167</b>
<b>Appendix – A</b>	<b>173</b>
<b>Appendix – B</b>	<b>176</b>
<b>Appendix – C</b>	<b>181</b>

## List of figures

---

2.1	Main and periodic distances in the caving process.....	12
2.2	Typical layout of the bord and pillar panel.....	12
2.3	Strata monitoring instruments.....	16
2.4	Extraction schemes adopted during depillaring operation.....	18
2.5	Modified Navid pattern of pillar extraction.....	19
2.6	Fish-bone pattern of pillar extraction.....	20
2.7	Split and fender pattern of pillar extraction.....	21
2.8	One – third split and fender pattern of pillar extraction.....	22
2.9	Double split and fender pattern of pillar extraction.....	23
2.10	Typical layout of vertical stress.....	28
3.1	Typical layout of the panel showing critical depillaring stage and focused pillars.....	37
3.2	Failure mechanism of the immediate strata.....	39
3.3	Typical layout of the panel showing focused remnant pillar.....	41
3.4	Flow chart showing designing sequence adopted for optimum remnant pillar design.....	42
3.5	Typical discretized view of the model for the coal pillar.....	44
3.6	Numerical pillars strength and stress.....	46
4.1	Borehole log of the strata in ‘Case A’.....	51
4.2	Layout of the panel in ‘Case A’.....	52
4.3	Typical layout of the depillaring panel and extraction pattern in ‘Case A’.....	53
4.4	Discretized view of the model in ‘Case A’.....	54
4.5	Vertical stress and yield profile of the panel in ‘Case A’.....	58
4.6	Time interval between flashing of AWTT and roof fall in ‘Case A’.....	60
4.7	Natural roof falls in the panel during depillaring in ‘Case A’.....	61
4.8	Area of overhang before and after roof fall in ‘Case A’.....	61
4.9	Borehole log of the strata in ‘Case B’.....	63

4.10	Layout of the panel in ‘Case B’ .....	64
4.11	Discretized view of the model in ‘Case B’ .....	66
4.12	Vertical stress and yield profile of the panel in ‘Case B’ .....	68
4.13	Time interval between flashing of AWTT and roof fall in ‘Case B’ .....	70
4.14	Natural roof falls in the panel during depillaring in ‘Case B’ .....	71
4.15	Area of overhang before and after roof fall in ‘Case B’ .....	71
4.16	Borehole of the strata in ‘Case C’ .....	73
4.17	Layout of the panel in ‘Case C’ .....	73
4.18	Discretized view of the model in ‘Case C’ .....	75
4.19	Vertical stress and yield profile of the panel in ‘Case C’ .....	77
4.20	Induced stress on a pillar no. 13 during the depillaring operation.....	79
4.21	Area of overhang before and after roof fall in ‘Case C’ .....	80
5.1	Discretized view of the model for panel design.....	85
5.2	Discretized view of the model for remnant pillar design.....	90
6.1	Vertical stress and yield profile of the panel with a pillar width of 26 m at a depth of 90 m.....	96
6.2	Vertical stress and yield profile of the panel with a pillar width of 35 m at a depth of 150 m.....	99
6.3	Vertical stress and yield profile of the panel with a pillar width of 35 m at a depth of 180 m.....	101
6.4	Vertical stress and yield profile of the panel with a pillar width of 45 m at a depth of 240 m.....	104
6.5	Vertical stress and yield profile of the panel with a pillar width of 45 m at a depth of 270 m.....	106
6.6	Vertical stress and yield profile of the panel with a pillar width of 45 m at a depth of 300 m.....	108
6.7	Vertical stress and yield profile of the panel with a pillar width of 45 m at a depth of 330 m.....	111
6.8	Vertical stress and yield profile of the panel with a pillar width	

	of 48 m at a depth of 360 m.....	113
6.9	Vertical stress and yield profile of the panel with a pillar width of 48 m at a depth of 390 m.....	115
6.10	Vertical stress and yield profile of the panel with a pillar width of 48 m at a depth of 420 m.....	117
6.11	Average vertical stress on the selected pillars at different depth of cover.....	120
6.12	Average vertical stress on the selected pillars.....	121
6.13	Stress ratio for the pillar with different FOS during development.....	123
6.14	Vertical stress and yield profile of the panel with a pillar width of 26 m and snook width of 4.5 m at a depth of 90 m during 'Stage I'.....	131
6.15	Vertical stress and yield profile of the panel with a pillar width of 26 m and snook width of 4.5 m at a depth of 90m during 'Stage II' through 'Stage IV'.....	132
6.16	Vertical stress and yield profile of the panel with a pillar width of 35 m and snook width of 4.5 m at a depth of 180m during 'Stage 0'.....	135
6.17	Vertical stress and yield profile of the panel with a pillar width of 35 m and snook width of 4.5 m at a depth of 180 m during 'Stage I' through 'Stage V'.....	136
6.18	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 5.5 m at a depth of 330 m during 'Stage 0'.....	139
6.19	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 5.5 m at a depth of 330 m during 'Stage I' through 'Stage IV'.....	140
6.20	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 5.5 m at a depth of 330 m during 'Stage V' through 'Stage VIII'.....	142
6.21	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 5.5 m at a depth of 330 m during 'Stage IX'	

	through 'Stage XI' .....	143
6.22	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 5.5 m at a depth of 420 m during 'Stage 0' .....	146
6.23	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 5.5 m at a depth of 420 m during 'Stage I' through 'Stage IV' .....	147
6.24	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 5.5 m at a depth of 420 m during 'Stage V' through 'Stage VIII' .....	149
6.25	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 5.5 m at a depth of 420 m during 'Stage IX' through 'Stage XI' .....	150
6.26	Graphical representation of the SF of the remnant pillar for the selected pillars .....	154
6.27	Graph showing reaction provided by the remnant pillar for different areas .....	155
B.1	Vertical stress and yield profile of the panel with a pillar width of 26 m at a depth of 120 m .....	175
B.2	Vertical stress and yield profile of the panel with a pillar width of 35 m at a depth of 210 m .....	176
B.3	Vertical stress and yield profile of the panel with a pillar width of 45 m at a depth of 360 m .....	177
B.4	Vertical stress and yield profile of the panel with a pillar width of 48 m at a depth of 450 m .....	178
C.1	Vertical stress and yield profile of the panel with a pillar width of 26 m and snook width of 5.5 m at a depth of 90 m during 'Stage I' .....	180
C.2	Vertical stress and yield profile of the panel with a pillar width of 26 m and snook width of 5.5 m at a depth of 90 m during 'Stage II' through 'Stage IV' .....	181

C.3	Vertical stress and yield profile of the panel with a pillar width of 26 m and snook width of 6.5 m at a depth of 90 m during ‘Stage I’.....	182
C.4	Vertical stress and yield profile of the panel with a pillar width of 26 m and snook width of 6.5 m at a depth of 90 m during ‘Stage II’ through ‘Stage IV’.....	183
C.5	Vertical stress and yield profile of the panel with a pillar width of 35 m and snook width of 5.5 m at a depth of 180 m during ‘Stage 0’.....	184
C.6	Vertical stress and yield profile of the panel with a pillar width of 35 m and snook width of 5.5 m at a depth of 180 m during ‘Stage I’ through ‘Stage V’.....	185
C.7	Vertical stress and yield profile of the panel with a pillar width of 35 m and snook width of 6.5 m at a depth of 180 m during ‘Stage 0’.....	186
C.8	Vertical stress and yield profile of the panel with a pillar width of 35 m and snook width of 6.5 m at a depth of 180 m during ‘Stage I’ through ‘Stage V’.....	187
C.9	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 4.5 m at a depth of 330 m during 'Stage 0'.....	188
C.10	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 4.5 m at a depth of 330 m during 'Stage I' through 'Stage IV'.....	189
C.11	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 4.5 m at a depth of 330 m during 'Stage V' through 'Stage VIII'.....	190
C.12	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 4.5 m at a depth of 330 m during 'Stage IX' through 'Stage XI'.....	191
C.13	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 6.5 m at a depth of 330 m during ‘Stage 0’.....	192
C.14	Vertical stress and yield profile of the panel with a pillar width of 45 m	

	and snook width of 6.5 m at a depth of 330 m during ‘Stage I’ through ‘Stage IV’ .....	193
C.15	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 6.5 m at a depth of 330 m during ‘Stage V’ through ‘Stage VIII’ .....	194
C.16	Vertical stress and yield profile of the panel with a pillar width of 45 m and snook width of 6.5 m at a depth of 330 m during ‘Stage IX’ through ‘Stage XI’ .....	195
C.17	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 4.5 m at a depth of 420 m during ‘Stage 0’ .....	196
C.18	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 4.5 m at a depth of 420 m during ‘Stage I’ through ‘Stage IV’ .....	197
C.19	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 4.5 m at a depth of 420 m during ‘Stage V’ through ‘Stage VIII’ .....	198
C.20	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 4.5 m at a depth of 420 m during ‘Stage IX’ through ‘Stage XI’ .....	199
C.21	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 6.5 m at a depth of 420 m during ‘Stage 0’ .....	200
C.22	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 6.5 m at a depth of 420 m during ‘Stage I’ through ‘Stage IV’ .....	201
C.23	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 6.5 m at a depth of 420 m during ‘Stage V’ through ‘Stage VIII’ .....	202
C.24	Vertical stress and yield profile of the panel with a pillar width of 48 m and snook width of 6.5 m at a depth of 420 m during ‘Stage IX’ through ‘Stage XI’ .....	203

## List of tables

---

2.1	Cavability index vs. caving behavior of strata.....	14
3.1	Material properties used in the model for coal.....	44
3.2	Material properties used in the model for roof and floor.....	45
4.1	Strength parameter for coal used in the model for ‘Case A’.....	56
4.2	FOS of the next intact pillar (‘N’) in ‘Case A’.....	58
4.3	Strength parameter for coal used in the model for ‘Case B’.....	66
4.4	FOS of the working pillar in ‘Case B’.....	68
4.5	Strength parameters for coal used in the model for ‘Case C’.....	76
4.6	FOS of the working pillar in ‘Case C’.....	78
5.1	Parameters used for designing the panel.....	84
5.2	Parameters used for designing the remnant pillar.....	88
6.1	Simulation results of the panel with a pillar width of 26 m at a depth of 90 m.....	97
6.2	Simulation results of the panel with a pillar width of 35 m at a depth of 150 m.....	99
6.3	Simulation results of the panel with a pillar width of 35 m at a depth of 180 m.....	102
6.4	Simulation results of the panel with a pillar width of 45 m at a depth of 240 m.....	105
6.5	Simulation results of the panel with a pillar width of 45 m at a depth of 270 m.....	107
6.6	Simulation results of the panel with a pillar width of 45 m at a depth of 300 m.....	109
6.7	Simulation results of the panel with a pillar width of 45 m at a depth of 330 m.....	111
6.8	Simulation results of the panel with a pillar width of 48 m at a depth of 360 m.....	114

6.9	Simulation results of the panel with a pillar width of 48 m at a depth of 390 m.....	116
6.10	Simulation results of the panel with a pillar width of 48 m at a depth of 420 m.....	118
6.11	Average vertical stress on the pillars during development and depillaring.....	122
6.12	Stress ratio of the focused pillars during depillaring.....	123
6.13	Nomograph showing the optimum width of the pillar for a mechanized depillaring panel.....	127
6.14	Simulation results of the remnant pillars for a pillar width of 26 and snook width of 4.5 m at a depth of 90 m.....	133
6.15	Simulation results of remnant pillars for a pillar width of 35 and snook width of 4.5 m at a depth of 180 m.....	137
6.16	Simulation results of remnant pillars for a pillar width of 45 and snook width of 4.5 m at a depth of 330 m.....	144
6.17	Simulation results of remnant pillars for a pillar width of 48 m and snook width of 5.5 m at a depth of 420 m.....	151
6.18	<i>SF</i> of the focused remnant pillars for pillar width of 26 m.....	153
6.19	<i>SF</i> of the focused remnant pillar for pillar width of 35 m.....	153
6.20	<i>SF</i> of the focused remnant pillars for pillar width of 45 m.....	153
6.21	<i>SF</i> of the focused remnant pillars for pillar width of 48 m.....	153
6.22	<i>SF</i> of the optimum remnant pillar design for the selected pillars.....	154
6.23	Average vertical stress on the focused remnant pillars for the selected pillars.....	156
6.24	Percentage of extraction in optimum cases of remnant pillars for the selected pillars.....	156
6.25	Optimum area and percentage of the snook for different pillar sizes.....	157
A.1	Failed cases of pillar from Indian coal mines.....	172
A.2	Stable cases of pillar from Indian coal mines.....	172

A.3	Factor of safety ( <i>FOS</i> ) of failed cases of pillars.....	173
A.4	Factor of safety ( <i>FOS</i> ) of stable cases of pillars.....	173

## List of Abbreviations

---

<i>AWTT</i>	Auto – warning Tell-tale
<i>CIL</i>	Coal India Limited
<i>CM</i>	Continuous Miner
<i>CMR</i>	Coal Mine Regulations
<i>CMRI</i>	Central Mining Research Institute
<i>DHTT</i>	Dual Height Tell–tale
<i>FISH</i>	FLAC – ISH (language of FLAC)
<i>FLAC<sup>3D</sup></i>	Fast Lagrangian Analysis of Continua in three dimension
<i>FOS</i>	Factor of Safety
<i>GSI</i>	Geological Strength Index
<i>LTD</i>	Load Transfer Distance
<i>MOC</i>	Ministry of coal
<i>RBE</i>	Roof Bolt Extensometer
<i>RMR</i>	Rock Mass Rating
<i>RQD</i>	Rock Quality Designation
<i>RTT</i>	Rotary Tell–tale
<i>SCCL</i>	Singareni Collieries Company Limited
<i>SECL</i>	South Eastern Coalfields Limited
<i>SF</i>	Strength Factor
<i>SR</i>	Stress Ratio
<i>UCS</i>	Uniaxial Compressive Strength
<i>US</i>	United States

## List of Symbols

---

$I$	Cavability Index
$\sigma$	Uniaxial Compressive Strength
$l$	Average length of core
$t$	Thickness of strong bed
$s_p$	Strength of pillar
$w$	Width of pillar
$h$	Height of pillar
$s_{cube}$	Strength of cubical pillar
$D$	Depth of cover
$^{\circ}$	Degree
$c$	Cohesion
$\phi$	Friction angle
$D_{max}$	Maximum depth of cover
$SR_W$	Stress ratio of working pillar
$SR_B$	Stress ratio of barrier pillar
$FOS_{Development}$	Factor of safety of pillar during development
$L$	Load-bearing capacity of remnant
$A$	Area of remnant
$L_P$	Load-bearing capacity of previously extracted pillar
$L_W$	Load-bearing capacity of working pillar
$SF_W$	Strength Factor of working pillar/remnant
$SF_P$	Strength Factor of previously extracted pillar/remnant

## List of Illustrations

---

6.1	Panel design for mechanized depillaring.....	125
6.2	Remnant pillar design during mechanized depillaring.....	158