

**TABLE OF CONTENTS**

<b>List of Figures</b>	xiv-xviii
<b>List of Tables</b>	xix-xxii
<b>Nomenclature</b>	xxiii-xxiv
<b>Preface</b>	xxv-xxxii
<b>CHAPTER 1 INTRODUCTION</b>	1-11
<b>CHAPTER 2 LITERATURE REVIEW AND RESEARCH OBJECTIVES</b>	12-45
2.1 Literature review	12
2.1.1 Raw materials	12
2.1.1.1 Feedstock for the pyrolysis process	12
2.1.1.1.1 Feed characterization	14
2.1.1.2 Catalysts for pyrolysis	15
2.1.1.2.1 Catalyst characterization	21
2.1.2 Types of reactor/design	29
2.1.3 Types of pyrolysis process	31
2.1.3.1 Thermal pyrolysis	31
2.1.3.2 Catalytic pyrolysis	33
2.1.4 Mechanism for the formation of BTE via thermal and catalytic pyrolysis	34
2.1.5 Factors affecting the BTE production from PS	37
2.1.5.1 Production of BTE via thermal pyrolysis of PS	37
2.1.5.2 Production of BTE via catalytic pyrolysis of PS	40
2.1.6 Pyrolysis product characterization	42
2.2 Objectives	44

<b>CHAPTER 3: EXPERIMENTAL</b>	46-61
3.1 Materials	46
3.2 Experimental setup	48
3.3 Method	51
3.3.1 Feed preparation	51
3.3.2 Feed characterization	52
3.3.2.1 Proximate analysis	52
3.3.2.2 Thermogravimetry analysis (TGA)	53
3.3.3 Catalyst synthesis from natural red clay	53
3.3.4 Catalyst characterization	54
3.3.4.1 Scanning electron microscope-energy dispersive X-ray spectroscopy (SEM-EDX)	55
3.3.4.2 X-ray diffraction (XRD)	55
3.3.4.3 Brunauer-Emmet-Teller (BET) surface area	55
3.3.4.4 Fourier transformed infra-red spectroscopy (FTIR)	56
3.3.5 Pyrolysis process for the production of BTE	56
3.3.6 Catalyst regeneration	57
3.4 Pyrolysis oil analysis	58
3.4.1 Gas chromatography (GC) analysis	58
3.4.1.1 Estimation of BTE and styrene in pyrolysis oil	58
3.4.2 FTIR of pyrolysis oil	59
3.4.3 Physicochemical properties	59
3.4.3.1 Gross calorific value (GCV)	59

---

3.4.3.2 Carbon residue	60
3.4.3.3 Flash and fire point	60
<b>CHAPTER 4: OPTIMIZATION OF PROCESS PARAMETERS USING RSM</b>	<b>62-69</b>
4.1 Introduction	62
4.2 Optimization using RSM-BBD	67
<b>CHAPTER 5: RESULTS AND DISCUSSION</b>	<b>70-189</b>
5.1 Feed characterization	71
5.1.1 Proximate analysis of WEPS	71
5.1.2 Thermo-chemical behaviour of WEPS	71
5.2 Thermal pyrolysis of WEPS: Part I	73
5.2.1 Effect of process parameters on product yield	73
5.2.1.1 Effect of temperature and holding time	73
5.2.1.2 Effect of heating rate	75
5.2.1.3 Effect of temperature	76
5.2.2 Analysis of thermal pyrolysis oil	77
5.2.2.1 Estimation of aromatic content/BTE and styrene in pyrolysis oil	77
5.2.2.2 FTIR analysis of thermal pyrolysis oil	80
5.2.2.3 Physicochemical properties of thermal pyrolysis oil	82
5.3 Catalytic pyrolysis of waste expanded polystyrene (WEPS): Part II	84
5.3.1 Catalytic pyrolysis using ZSM-5 ammonium powder as catalyst	84
5.3.1.1 Effect of process parameters on product yield	84
5.3.1.1.1 Effect of feed to catalyst ratio	84

---

## Table of Contents

---

5.3.1.1.2 Effect of temperature and holding time	86
5.3.1.1.3 Effect of heating rate	88
5.3.1.1.4 Effect of temperature	90
5.3.1.2 Analysis of pyrolysis oil obtained using ZSM-5 ammonium powder catalyst	93
5.3.1.2.1 Estimation of aromatic content/BTE and styrene in pyrolysis oil	93
5.3.1.2.2 FTIR analysis of pyrolysis oil	99
5.3.1.2.3 Physicochemical properties of pyrolysis oil	101
5.3.2 Catalytic pyrolysis using Nickel on silica-alumina as catalyst	102
5.3.2.1 Effect of process parameters on product yield	102
5.3.2.1.1 Effect of feed to catalyst ratio	102
5.3.2.1.2 Effect of temperature and holding time on liquid and solid yield	104
5.3.2.1.3 Effect of heating rate	106
5.3.2.1.4 Effect of temperature	108
5.3.2.2 Analysis of pyrolysis oil obtained using Nickel on silica-alumina catalyst	110
5.3.2.2.1 Estimation of aromatic content/BTE and styrene in pyrolysis oil	110
5.3.2.2.2 FTIR analysis of pyrolysis oil	115
5.3.2.2.3 Physicochemical properties of pyrolysis oil	117
5.3.3 Catalytic pyrolysis using synthesized catalyst from natural red clay	118
5.3.3.1 Catalyst characterization	118
5.3.3.1.1 SEM-EDX analysis	118
5.3.3.1.2 BET surface area analysis	121
5.3.3.1.3 XRD analysis	124
5.3.3.1.4 FTIR analysis of red clay catalysts	127

---

## Table of Contents

---

5.3.3.2 Selection of best catalyst among all synthesized red clay catalysts	128
5.3.3.3 Effect of process parameters on product yield	130
5.3.3.3.1 Effect of feed to catalyst ratio	130
5.3.3.3.2 Effect of temperature and holding time	132
5.3.3.3.3 Effect of heating rate	134
5.3.3.3.4 Effect of temperature	135
5.3.3.4 Analysis of pyrolysis oil obtained using RC-800 catalyst	138
5.3.3.4.1 Estimation of aromatic content/BTE and styrene in pyrolysis oil	138
5.3.3.4.2 FTIR of pyrolysis oil	143
5.3.3.4.3 Physicochemical properties of pyrolysis oil	145
5.4 Performance comparison of three catalysts for the BTE production	147
5.5 Process parameters through RSM	149
5.5.1 RSM coupled with BBD for maximization of liquid yield	149
5.5.1.1 Optimization of process variables	160
5.5.1.1.1 Optimization of process variables using ZSM-5 ammonium powder	160
5.5.1.1.2 Optimization of process variables using Nickel on silica-alumina catalyst	164
5.5.1.1.3 Optimization of process variables using best red clay catalyst RC-800	168
5.5.2 Analysis of pyrolysis oil	172
5.5.2.1 Qualitative analysis of pyrolysis oil obtained using three different catalysts	172
5.5.2.2 Physicochemical properties of pyrolysis oil obtained using three different catalysts	177
5.6 Regeneration and reusability study of catalyst	178

---

## Table of Contents

---

5.6.1 Reusability assessment of best catalyst Nickel on silica-alumina catalyst	179
5.6.1.1 Characterization of regenerated catalyst Nickel on silica-alumina	179
5.6.1.1.1 SEM analysis	179
5.6.1.1.2 BET surface area analysis	181
5.6.1.2 Product yield of AB-type pyrolysis	181
5.6.1.3 Analysis of pyrolysis oil	183
5.6.1.3.1 Quantification of aromatic content/BTE and styrene in pyrolysis oil	183
5.6.1.3.2 Physicochemical properties of pyrolysis oil	184
<b>6. CONCLUSIONS</b>	189-198
<b>REFERENCES</b>	199-218
Appendix A1	219
Appendix A2	220
Appendix A3	221
Appendix A4	223
Appendix A5	224
Appendix A6	226
Appendix A7	227
Appendix A8	229