

LIST OF FIGURES

Figure 1.1:	Electromagnetic spectrum of the sunlight.	6
Figure 1.2:	Schematic structures of photoconductor and photodiode.	8
Figure 1.3:	Photoconductor working principle under UV illumination.	10
Figure 1.4:	Energy band diagram of pn junction.	14
Figure 1.5:	Photodiode circuit schematic under UV illumination.	14
Figure 1.6:	Wurtzite crystal structure of ZnO with lattice parameters: $a=3.250 \text{ \AA}$, $c=5.207 \text{ \AA}$ (http://physique.unice.fr).	16
Figure 1.7:	Band structure of QDs and bulk semiconductor.	18
Figure 2.1:	Synthesis flow chart of ZnO QDs under the inert environment.	37
Figure 2.2:	Spin coater setup for thin film deposition.	37
Figure 2.3:	Experimental setup for optical characterization of thin films (Reflectance and Transmittance) and thickness measurement.	39
Figure 2.4:	(a) Device Structure of Au/ZnO QDs Schottky photodiode (b) Fabricated device on n-Si and packaged using silver paste.	39
Figure 2.5:	Fabrication flow of process.	40
Figure 2.6:	(a) TEM image of as-grown ZnO QDs with a particle size of $\sim 2.53 \text{ nm}$, and (b) Diffraction pattern of as grown ZnO QDs.	41
Figure 2.7:	(a) TEM image of ZnO QDs annealed at 450°C with a particle size of $\sim 13.80 \text{ nm}$ (b) Diffraction pattern of ZnO QD annealed at 450°C .	41
Figure 2.8:	XRD pattern of ZnO QDs annealed at 450°C .	42
Figure 2.9:	EDS spectra of the as-grown ZnO QDs on carbon copper grid.	42
Figure 2.10:	J-V characteristics of Au/ZnO Schottky photodiode under dark and UV illumination at 365 nm from the UV LED light with $800 \mu\text{W}/\text{cm}^2$ optical power.	43
Figure 2.11:	Experimental measurement setup for electrical characterization.	44
Figure 2.12:	C-V characteristic of the Au/ZnO Quantum Dot Schottky photodiode at 500 kHz .	46

Figure 2.13:	Charge distribution and energy band on the surface of the ZnO QDs under the UV illumination and dark.	48
Figure 2.14:	Responsivity spectrum of the Au/ZnO QDs Schottky photodiode at an applied -5 V, -3 V, and -1 V bias.	48
Figure 2.15:	Experimental measurement setup for the photocurrent vs wavelengths measurement.	50
Figure 2.16:	Normalized Absorption of ZnO Quantum Dots thin film (thickness ~200nm) and Transmittance of Au thin film (thickness ~70nm).	51
Figure 2.17:	Experimental setup for the time response measurement (a) UV LED source provides the UV pulses (c) complete time response measurement setup with data acquisition using LabView.	51
Figure 2.18:	Time response of the Au/ZnO QDs Schottky photodiode under the illumination of UV LED pulsating 1sec ON and OFF.	52
Figure 3.1:	Process flow of fabrication of Photodetector on glass substrate	59
Figure 3.2:	(a) Device structure and (b) front view of fabricated device on glass substrate.	60
Figure 3.3:	Energy band diagram of QDs with the change of particle size, increase in the particle size leads the discrete bands of QDs to continuum state.	61
Figure 3.4:	Absorption Spectra of ZnO QDs Thin film at 450°C and 600°C, and (b) the energy band gap of ZnO QDs at both temperature.	62
Figure 3.5:	Current density versus applied voltage and device structure fabricated on Glass Substrate.	63
Figure 3.6:	Charge distribution and energy band diagram of three conjoint quantum dots (a) dark and (b) with UV illumination.	64
Figure 3.7:	Photoresponse characteristics (a) and (b) detectivity of the device annealed at an applied bias 1 and 2 V	65
Figure 3.8:	Time Response characteristics of MSM photoconductor under UV pulses illumination.	68
Figure 4.1:	ZnO NPs synthesis process	75
Figure 4.2:	Device structure fabricated on glass substrate with interdigitated Ag electrodes spacing 300µm.	76
Figure 4.3:	Device fabrication flow of process	76
Figure 4.4:	(a) SEM image of ZnO NPs, and (b) XRD pattern of ZnO NPs	77

Figure 4.5:	Reflection, refraction, and scattering of light (Zhang et al., 2012)	78
Figure 4.6:	Scattering efficiency dependence on the particle size and incident wavelength	80
Figure 4.7:	Absorbance spectrum of ZnO QDs (film thickness ~100nm) deposited on quartz substrate and Transmittance of ZnO NPs (film thickness ~500nm).	81
Figure 4.8:	Dark current density Vs voltage characteristics of Ag/ZnO-QD/Ag and ZnO NPs coated Ag/ZnO-QDs/Ag photodetector.	82
Figure 4.9:	J-V characteristics of ZnO NPs and ZnO QDs separately acts as active layer under the UV illumination of power density (~70 $\mu\text{W}/\text{cm}^2$) at an wavelength 360 nm.	82
Figure 4.10:	Photoresponse under front illumination: (a) ZnO NPs acts as filter layer, and (b) spectral response (responsivity) of device.	84
Figure 4.11:	Photoresponse under back illumination: (a) ZnO NPs acts as scattering layer, and (b) spectral response (responsivity) of the device.	84
Figure 4.12:	Filter effects on the time response under the illumination of UV LED from front side.	86
Figure 4.13:	Scattering effects under the illumination of UV LED from back side of device with and without ZnO NPs	87