

# List of Tables

2.1	Voltage stress across switches and diodes . . . . .	30
2.2	Comparison of proposed converter with existing converter . . . . .	31
2.3	Specification and design parameters of converter . . . . .	32
3.1	Loss factors . . . . .	55
3.2	Comparison of components used in conventional SBI and proposed SBI . . . . .	55
3.3	Voltage stress analysis between SBI and proposed SBI . . . . .	57
3.4	Design parameters and specification . . . . .	59
3.5	Converter component . . . . .	59
3.6	Comparison of SBI at different duty cycle in NZ-DCM and FCCM . . . . .	64
4.1	Merits and demerits of Z source converters . . . . .	68
5.1	Switching state under shoot through . . . . .	87
5.2	Switching state under active state . . . . .	88
6.1	Loss factors . . . . .	106
6.2	MBDHC specification . . . . .	107
6.3	Stress analysis of proposed converter . . . . .	109
6.4	Comparison of proposed converter with existing converter . . . . .	110
6.5	Components used . . . . .	111
7.1	L-ZSI specification . . . . .	134
7.2	Components used . . . . .	146
8.1	Specification of the converter . . . . .	177
8.2	Stress analysis of proposed converter . . . . .	178
8.3	Comparison of proposed converter with existing converter . . . . .	179

8.4	Comparison of proposed converter with existing Boost converter . . . . .	179
8.5	Components used in experiment . . . . .	180