

# Contents

---

|   |              |
|---|--------------|
| <b>List of Figures</b>  | <b>xix</b>   |
| <b>List of Tables</b>   | <b>xxi</b>   |
| <b>Preface</b>  | <b>xxiii</b> |
| <b>1 Introduction</b>   | <b>1</b>     |
| 1.1 Literature review and introduction of the thesis  | 1            |
| 1.2 Modes of fracture   | 10           |
| 1.3 Crack Propagation Parameters  | 11           |
| 1.3.1 Stress intensity factor   | 11           |
| 1.3.2 Stress magnification factor   | 12           |
| 1.3.3 Crack opening displacement  | 13           |
| 1.4 Mathematical techniques and methods   | 15           |
| 1.4.1 Fourier transformation  | 15           |
| 1.4.2 Kronecker delta function  | 15           |
| 1.4.3 Bessel function   | 15           |
| 1.4.4 Schmidt method  | 16           |
| 1.4.5 Wiener-Hopf technique   | 18           |
| <b>2 Study of collinear cracks in a composite medium subjected to time-harmonic wave disturbance</b>                    | <b>23</b>    |
| 2.1 Introduction  | 23           |
| 2.2 Mathematical formulation  | 25           |
| 2.3 Solution of the problem   | 28           |
| 2.4 Stress intensity factor   | 35           |
| 2.5 Numerical results and discussion  | 35           |
| 2.6 Conclusion  | 42           |
| <b>3 The mathematical study of an Edge crack in two different specified models under time-harmonic wave disturbance</b> | <b>43</b>    |
| 3.1 Introduction  | 43           |
| 3.2 Mathematical formulation  | 45           |

|          |   |            |
|----------|---|------------|
| 3.3      | Solution of the problems  | 48         |
| 3.4      | Results and discussion  | 54         |
| 3.5      | Conclusion  | 60         |
| <b>4</b> | <b>Semi-infinite Moving Crack under Antiplane Shear Loading</b>             | <b>61</b>  |
| 4.1      | Introduction  | 61         |
| 4.2      | Mathematical formulation of the problem                                     | 63         |
| 4.3      | Solution of the problem   | 66         |
| 4.3.1    | Wiener-Hopf technique   | 67         |
| 4.4      | Stress intensity factor(SIF) and Crack opening displacement(COD)            | 70         |
| 4.5      | Numerical results and discussion  | 71         |
| 4.6      | Conclusion  | 83         |
| <b>5</b> | <b>Two semi-infinite moving cracks situated at two different inter-</b>     |            |
|          | <b>faces of four semi-infinite orthotropic strips in a composite medium</b> | <b>85</b>  |
| 5.1      | Introduction  | 85         |
| 5.2      | Mathematical problem formulation  | 86         |
| 5.3      | Solution of the mathematical problem  | 91         |
| 5.3.1    | Wiener-Hopf technique   | 93         |
| 5.4      | Expressions of Stress intensity factor(SIF) and Crack opening dis-          |            |
|          | placement(COD)  | 100        |
| 5.5      | Numerical results and discussions   | 102        |
| 5.6      | Conclusion  | 110        |
| <b>6</b> | <b>Conclusions and future work</b>  | <b>113</b> |
| 6.1      | Conclusions   | 113        |
| 6.2      | Scope for future study  | 115        |
|          | <b>Appendix</b>   | <b>121</b> |
|          | <b>Bibliography</b>   | <b>123</b> |
|          | <b>List of publications</b>   | <b>133</b> |