#### Effect of Metal Inert Gas (MIG) Welding Parameters on Weldability of A6061 and A6063 Aluminium Alloys



Thesis submitted in the partial fulfilment

for the award of degree

#### **Doctor of Philosophy**

By

Sanjay Kumar

Department of Mechanical Engineering Indian Institute of Technology (Banaras Hindu University) Varanasi-221005

13131507

### CERTIFICATE

It is certified that the work contained in the thesis titled *"Effect of Metal Inert Gas (MIG) Welding Parameters on Weldability of A6061 and A6063 Aluminium Alloys"* by *"SANJAY KUMAR"* has been carried out under our supervision and this work has not been submitted elsewhere for a degree.

It is further certified that the student has fulfilled all the requirements of Comprehensive Examination, Candidacy and SOTA for the award of Ph.D. Degree.

Supervisor Dr. Satya Prakash Tewari Department of Mechanical Engineering Indian Institute of Technology (Banaras Hindu University) Varanasi – 221005, INDIA. Co-Supervisor Dr. Jayant Kumar Singh Department of Metallurgical Engineering Indian Institute of Technology (Banaras Hindu University) Varanasi – 221005, INDIA.

### **DECLARATION BY THE CANDIDATE**

I, "SANJAY KUMAR", certify that the work embodied in this thesis is my own bona fide work and carried out by me under the supervision of "Prof. SATYA PRAKASH TEWARI and Dr. JAYANT KUMAR SINGH", from DECEMBER 2013 to MARCH 2021, at the "DEPARTMENT OF MECHANICAL ENGINEERING", Indian Institute of Technology (BHU), Varanasi. The matter embodied in this thesis has not been submitted for the award of any other degree/diploma. I declare that I have faithfully acknowledged and given credits to the research workers wherever their works have been cited in my work in this thesis. I further declare that I have not wilfully copied any other's work, paragraphs, text, data, results, *etc.*, reported in journals, books, magazines, reports dissertations, theses, *etc.*, or available at websites and have not included them in this thesis and have not cited as my own work.

Date:

Place: Varanasi

Sanjay Kumar

#### **CERTIFICATE FROM THE SUPERVISORS**

This is to certify that the above statement made by the candidate is correct to the best of our knowledge.

Supervisor Dr. Satya Prakash Tewari Department of Mechanical Engineering Indian Institute of Technology (Banaras Hindu University) Varanasi – 221005, INDIA Co-Supervisor Dr. Jayant Kumar Singh Department of Metallurgical Engineering Indian Institute of Technology (Banaras Hindu University) Varanasi – 221005, INDIA

Professor and Head Department of Mechanical Engineering Indian Institute of Technology (Banaras Hindu University) Varanasi – 221005, INDIA

## **COPY RIGHT TRANSFER CERTIFICATE**

Title of the Thesis: Effect of Metal Inert Gas (MIG) Welding Parameters on Weldability of A6061 and A6063 Aluminium Alloys

Name of the Student: Sanjay Kumar

#### **Copyright Transfer**

The undersigned hereby assigns to the Indian Institute of Technology (Banaras Hindu University) Varanasi all rights under copyright that may exist in and for the above thesis submitted for the award of the "DOCTOR OF PHILOSOPHY".

Date:

Place: Varanasi

(SANJAY KUMAR)

Note: However, the author may reproduce or authorize others to reproduce material extracted verbatim from the thesis or derivative of the thesis for author's personal use provided that the source and the Institute's copyright notice are indicated.

#### **Table of Contents**

Prefa	cei
Ackn	owledgementsv
List o	of Tables vii
List c	of Figures viii
Chap	oter 1
1.1	Introduction2
1.2	Background of the Research Study
1.3	Weldability of Aluminium and Its alloys:
1.3	.1 Characteristics of Aluminium and Its alloys:
1.4	Use of Aluminum Alloy:
1.5	Application of A6061& A6063 Aluminium alloys7
1.6	Weldability of Aluminium Alloys7
1.7	Different type of Processes used for Welding Aluminium7
1.8	Based on the heat source used welding processes can be categorized as follows8
1.9	Advantages of MIG Welding10
1.10	Shielding Gas Functions
1.1	0.1 Properties of Shielding Gases11
1.1	0.2 Weld Profile Troubleshooting
1.11	Welding process parameters

1.11.1 Welding current	
1.11.2 Welding voltage	
1.11.3 Travel speed	
1.11.4 Electrode size	
1.11.5 Inert gas	
1.12 Motivation of the res	earch work17
1.13 Summary	
Chapter 2	
2.1 Literature Review	
2.1 Observation from lit	erature review/ Research gap32
Chapter 3	
3. Materials and Method	
3.1 Introduction	
3.2 Research Methodo	logy
3.3 Material Selection	
3.3.1 Base Materials A	
3.3.2 Base Materials A	
3.3.3 Filler Material	
3.3.4 Procured Items	
3.4 Evaluation of Base	Metal Properties
3.5 Experimental Setu	o

3.5.1	MIG Welding
3.5.2	Supply of Shielding Gas41
3.5.3	Fabrication of Beads and Joints
3.6 (	Characterization
3.6.1	Evaluation of Bead Profile Characteristics
3.6.2	Macro and Microstructural Analysis46
3.6.3	X-Ray Diffraction (XRD)47
3.6.4	Tensile Test
3.6.5	Scanning Electron Microscopy (SEM)
3.6.6	Hardness Test
3.7 S	Summary
3.7 S Chapter 4	Summary
3.7 S Chapter 4 4 Resul	49 4
3.7 S Chapter 4 4 Resul 4.1 I	Summary
3.7 S Chapter 4 4 Resul 4.1 I 4.2 H	49 49 49 49 49 49 49 49 49 49
3.7 S Chapter 4 4 Result 4.1 I 4.2 H 4.3 V	Summary
3.7 S Chapter 4 4 Result 4.1 I 4.2 H 4.3 V 4.3.1	Summary
3.7 S Chapter 4 4 Result 4.1 I 4.2 H 4.3 N 4.3.1 4.3.2	Summary
3.7 S Chapter 4 4 Result 4.1 I 4.2 H 4.3 V 4.3.1 4.3.2 4.4 N	Summary    49      I
3.7 S Chapter 4 4 Result 4.1 I 4.2 H 4.3 N 4.3.1 4.3.2 4.4 N 4.4.1	immary    49      immary    (51-107)      is and Discussion    52      ntroduction    52      Heat Input Calculations    52      Visual Inspection    53      Visual Inspection A6061    54      Visual Inspection A6063    54      Accrostructure of the MIG Welded Joints    55      Effect of Welding Parameters on weld bead and Penetration    56

4.5 Effect of Welding Parameters on Microstructure
4.5.1 Microstructure of A6061
4.5.2 Microstructure of A606369
4.5.3 Grain Size Distribution and Phase Transformation
4.6 XRD Analysis of Welded Joint
4.6.1 XRD Analysis of A606181
4.6.2 XRD Analysis of A6063
4.7 Effect of Welding Parameters on Microhardness
4.7.1 Effect of Welding on Microhardness of A6061
4.7.2 Effect of Welding on Micro Hardness of A6063
4.8 Effect of Welding Parameters on Tensile Strength
4.8.1 Tensile Test of A6061 at Different Conditions
4.8.2 Tensile Test of A6063 at Different Conditions
4.9 Effect of Welding Parameters on Fracture Morphology
4.10 Comparison of Welded A6061 and A6063 joints106
4.11 Summary107
Chapter 5 (108-111)
5.1 Summary and Conclusions109
5.2 Suggestions for Future Work111
References

List of Publications

#### PREFACE

Welding is a process of joining two or more pieces of the same or dissimilar materials which are melted together by the application of heat or pressure or both and with or without adding a filler material to obtain monolithic structures (Connor 1987). Often a filler material is added to facilitate coalescence. The assembled parts that are joined by welding are called weldments. Welding is primarily used in metal parts and their alloys. Recent technologies behind welding have enormously created opportunities to add more value to welded structures and products. Few typical examples are automobiles, aircraft, ships, locomotives, space shuttles, and offshore platforms, to name but a few. As these structures are predominated by metals, the quest for the use of metals in manufacturing innovative products by utilizing welding as the main joining process is highly indispensable. The component requirements in the aircraft, missile, automobile, electronics, and nuclear, aerospace, and commercial fields have given rise to many new and demanding service conditions. To meet the stringent requirements of these exacting operations, it is not only necessary to develop new materials but also methods to fabricate them into useful engineering components. One such fabrication technique is the fusion welding process.

A6061 and A6063 aluminium alloys possess some unique properties like a light in weight and high strength to weight ratio. They are becoming the most popularly used medium-strength aluminium alloy in aerospace, marine, automobile, and agriculture, structural industries. With the increased use of aluminium alloys in industries, a reliable joining technique needs to be developed for the effective utilization of aluminium alloys. Metal Inert Gas Welding (MIG) is the most extensive gas shielded arc welding processes used in the joining of aluminium and its alloys due to their preferable flexibility and economy. But there are few problems like low welding speed, partial penetration, and lack of the deposited metal that occurred during this process. The high solubility of hydrogen and other atmospheric gases in the molten state and the formation of the oxide layer are the major problems associated with this kind of joining process. Hence in this research, an attempt was made to increase the welding speed, reduce the porosity, and maximize the mechanical properties of the MIG welding joints by the different welding parameters. In this investigation, different gas flow rates at different working conditions

Bead on plate welding is performed on A6061 and A6063 aluminium alloy plates at different combinations of input parameters like Welding Current (I), Voltage (V), and Gas flow rate (l/m). MIG joints were fabricated using an inert gas with the help of automated welding machines. The joints were evaluated by conducting tensile tests using the universal testing machine and interface hardness was found using Vickers hardness testing equipment. Microscopic examinations and characterizations of the joints were done using Optical Microscopy (OM), X-ray radiography, Scanning Electron Microscopy (SEM), and X-Ray Diffraction (XRD) techniques.

Aluminium and its alloy have a very wide area of application i.e. aerospace, automobile, and structural industries. The present investigation aimed to study the effect of MIG welding on microstructural and mechanical properties of A6061 and A6063 aluminium alloy. The characteristics of the fusion zone are typical coarse columnar grains structure because of the prevailing thermal conditions during weld metal solidification. In this work, plates of 5mm thickness have been used as the base material for preparing single pass butt welded joints at different-different current values. The filler wire used for joining the plates is AA4043 (Al-5%Si by wt.) grade aluminium alloy. From this investigation, it was found that the hardness of the fusion zone was degraded significantly due to the usage of lower hardness filler metal. The

precipitation evolution in the heat-affected zone was characterized by XRD which improves the tensile properties of the welded A6061 and A6063 alloy.

**Organisation of the thesis-:** The thesis is classified into 5 chapters.

**Chapter 1** gives a brief introduction to the various types of welding processes, their classifications, materials and their applications. It also describes the GMAW Process and its components in detail. The material chosen for this investigation and the problems encountered in the welding of aluminium alloys are briefly discussed. The motivation of the research work and outline of the thesis are also presented in this chapter.

**Chapter 2** reviews the various literatures of GMAW pertaining to the present investigation. A brief survey is carried out on the welding of AA6061 and AA6063 aluminum alloys. Based on the available literature effect of process parameters on bead profile characteristics have been reviewed. Further, literatures related to optimization and prediction techniques of bead profile characteristics have been reviewed and presented. Literatures related to the discussion of the scope and objectives of the present investigation on GMAW joints have been discussed.

**Chapter 3** discusses the materials and methods experimental adopted for this investigation. In this chapter the entire work flow chart and its various tests are also presented. It also deals with the chemical and mechanical properties of the base material. A detailed description of the experimental set up, different types of alternating shielding gases, welding procedure and testing methods are also presented.

**Chapter 4 e**numerates the effect of welding parameters such as current, voltage, gas flow rate and heat input on mechanical and metallurgical properties of GMAWed joints respectively.

**Chapter 5** summarizes the results obtained for achieving the objectives of the present investigation are drawn as important conclusions from various experimental investigations conducted. This chapter also briefs the possible future scope of the present investigations.

#### ACKNOWLEDGEMENTS

I am using this opportunity to express my sincere thanks and gratitude beyond words to my supervisors, Prof. S. P. Tewari and Dr. J. K. Singh for their consistent help, encouragement, and valuable discussions during entire period of my research work. It would not have been possible without their utmost involvement and invaluable efforts. They motivated me to pursue research problem and the need for persistent effort to accomplish the goal. I am truly indebted to them. They are the real definition of the best teacher being friendly and behind for all the problems of not only mine but all the students.

Besides my supervisors, I would like to thank my RPEC members Prof. S. K. Sinha and Dr. G.S. Mahobia for their insightful comments and encouragement. I sincerely thank Prof. A. P. Harsha, Head of the Department of Mechanical Engineering and the former heads Prof. A. K. Jha and Prof. A. K. Agrawal for providing all the research facilities to successfully accomplish my research in the department. I have deep sense of gratitude to all the faculty members of the Department of Mechanical Engineering, IIT (BHU), Varanasi especially Prof. V. K. Srivastava and Prof. Rajnesh Tyagi for their cooperation and inspiration.

I praise and thank Manish Deo and Rabindra Prasad for the enormous amount of help and support throughout these years. I am thankful to my all friends Khemraj, Manvendra, Sushant, Parshant, Avinash, Nishant, Ashish and Harish for their constant encouragement, making joyful and memorable life being with my moments of happiness and troubles at IIT (BHU), Varanasi. I would also like to thank my juniors Siddharth, Akash, Sanjay, Sushil and Nitesh for their support.

Dozens of people have helped and taught me immensely at IIT (BHU) Varanasi. I'd like to thank my colleagues from CAM lab, Welding and Production Lab. I am also thankful to all the lab, workshop and office staffs specially Mr. Lalji ji, Mr. Ajay Yadav ji and Mr. Akash Mishra ji for their help and encouragement.

Last but not the least, I would like to express my deepest gratitude to my entire extended family, my parents, my Elder Brothers, my Elder Sisters and my Fufa and buaa for giving my life in the first place, for educating me, for unconditional support and encouragement to pursue my interest. I've been lucky to have their confidence, patience, pride, nurturing and love throughout my life. I would also like to thank Alisha, Priya, Badi Bhabhi and Choti Bhabhi for their support, love and encouragement during the most difficult times of this journey and it would not have been even half sweet without them.

The world is going through some unprecedented times as the normal has been upended by the arrival of the deadly coronavirus pandemic. People across the globe are battling with Covid-19. Many when who are locked at home like us are doing their part also by helping the people in many ways. But, others like doctors, soldiers, teachers, bank employee, office staff, railway employee, social volunteers etc. who were working outside to fulfil our requirements and taking care of the affected ones by risking their lives. I would like to thank them for their service towards humanity. Also, I would like to express my deepest condolences to those who lost their lives during this pandemic. Hope can always help pull people out of the most difficult of times. It is a powerful force and can prove to be a source of reassurance. Hence, I am immensely optimistic that very soon we will win this battle.

Finally, I wish to thank my friends and the persons who directly or indirectly helped in this journey but their names have not been mentioned here.

#### Sanjay Kumar

### List of Tables

Table 1.1: Weldability of Aluminium Alloys 7
Table 1.2: Properties of shielding gas11
Table 1.3: Weld Profile Troubleshooting
Table 3.1: Chemical composition (Wt. %) of A6061, A6063 and ER4043 filler material
aluminium alloy
Table 3.2: Mechanical properties of A6061 and A6063 aluminium alloy    38
Table 3.3: MIG welding parameters for experimentation
Table 4.1: Calculation of HI for Various welding parameters
Table 4.2: Heat Inputs: (a) 6.7kJ/cm, (b) 9.4kJ/cm, (c) 8.6kJ/cm, (d) 12.1kJ/cm
Table 4. 3: Base material A6061 properties106
Table 4. 4: Comparison table for Welded A6061 aluminium alloy
Table 4. 5: Base material A6063 properties107
Table 4. 6: Comparison table for Welded A6063 aluminium alloy

# List of Figures

Figure 1.1: Pie chart of utilization of aluminium (a) across the world (b) in different shapes
(c) in various engineering sectors
Figure 1.2: Schematic diagram of MIG welding process10
Figure 3.1: Experimental Plan
Figure 3.2: Dimensions of the tensile test specimen (ASTM E8)
Figure 3.3: (a) Vertical Milling and (b) Tensile specimen of base metals
Figure 3.4: Base metal A6061 a) Optical micrograph b) SEM Fractograph
Figure 3.5: Base metal A6063 a) Optical micrograph b) SEM Fractograph
Figure 3.6: Schematic diagram of MIG welding process40
Figure 3.7: Actual Setup of MIG used for experimentation41
Figure 3.8: Joint configuration for MIG welding
Figure 3.9: The Welded plates of a) A6061and b) A606344
Figure 3.10: (a) Band saw and (b) fabricated samples for microstructure and hardness test
Figure 3.11: Steps followed during fabrication and sample extraction for analysis45
Figure 3.12: Stereomicroscope
Figure 3.13: Universal Testing Machines (UTM)
Figure 3.14: Location of hardness measurement across welded joints
Figure 4.1: a) 140A_15V_18lpm, b) 160A_18V_14lpm, c) 180A_18V_18lpm 54
Figure 4.2: a) 140A_15V_10lpm, b) 160A_18V_14lpm, c) 180A_18V_18lpm55
Figure 4.3: Blowholes and lower levels of Penetration for 140A_15V_10lpm55
Figure 4.4: Average porosity at different gas flow rate

Figure 4.5: Radiography image at different gas flow rate a) 10 LPM b) 18 LPM, and c) 14
LPM
Fig. 4.6: Optical Micrographs welded A6061 alloy for Welding Parameter: Current: 160A
Voltage:18V Gas flow rate: 14LPM: (a) Base metal(BM) (b) Transition zone(TM),(c)
Fusion line(FL)(d) Fusion Zone(FZ)61
Figure 4.7: BM: Region is un-affected by weld heat Current: 160A Voltage:18V Gas flow
rate: 14LPM, HI: 9.2 kJ/cm62
Figure 4.8: Optical micrograph of MIG welded A6061 alloy: Transition zone(TM) 62
Figure 4.9: Optical micrograph of MIG welded A6061 alloys: Fusion line(FL)63
Figure 4.10: Optical micrograph of MIG welded A6061 alloy: Fusion Zone (FZ)63
Figure 4.11: Optical micrograph (a) 140A_15V at Gas flow rate: 10LPM and Heat Input of
(a) 6.7kJ/cm
Figure 4.12: Optical micrograph (b) 140A_21V at Gas flow rate: 10LPM and Heat Input
of (b) 9.4kJ/cm
Figure 4.13: Optical micrograph(c) 180A_15V at Gas flow rate: 10 LPM and Heat Input of
(c) 8.6kJ/cm
Figure 4.14: Optical micrograph (d) 180A_21V at Gas flow rate: 10LPM and Heat Input
of (d) 12.1kJ/cm
Figure 4.15: Optical micrograph (a) 140A_15V at Gas flow rate:14 LPM and Heat Input
of(a)6.7kJ/cm
Figure 4.16: Optical micrograph (b) 140A_21V at Gas flow rate:14 LPM and Heat Input
of(b)9.4kJ/cm
Figure 4.17: Optical micrograph (c) 180A_15V at Gas flow rate:14 LPM and Heat Input
of (c)8.6kJ/cm67

Figure 4.18: Optical micrograph (d)180A_21V at Gas flow rate:14 LPM and Heat Input
of (d)12.1kJ/cm67
Figure 4.19: Optical micrograph (a) 140A_15V at Gas flow rate: 18 LPM and Heat Input
of (a) 6.7kJ/cm
Figure 4.20: Optical micrograph (b) 140A_21V at Gas flow rate: 18 LPM and Heat Input
of (b) 9.4kJ/cm
Figure 4.21: Optical micrograph (c) 180A_15V at Gas flow rate: 18 LPM and Heat Input
of (c) 8.6kJ/cm
Figure 4.22: Optical micrograph (d) 180A_21V at Gas flow rate: 18 LPM and Heat Input
of (d) 12.1kJ/cm
Figure 4.23: Optical Micrographs welded A6063 alloy for Welding Parameter: Current:
160A Voltage:18V Gas flow rate: 14LPM: (a) Base metal(BM) (b) Transition
zone(TM),(c) Fusion line(FL)(d) Fusion Zone(FZ)70
Figure 4.24: BM: Region is un-affected by weld heat71
Figure 4.25: Optical micrograph of MIG welded A6063 alloy: (b) Transition zone(TM)71
Fig. 4.26 shows the distinguishing line for BM and HAZ for Welding Parameter: Current:
160A Voltage:18V Gas flow rate:14LPM HI: 9.216kJ/cm71
Figure 4.27: Optical micrograph of MIG welded A6063 alloy: (c) Fusion line (FL)72
Figure 4.28: Optical micrograph of MIG welded A6063 alloy (d) Fusion Zone(FZ)72
Figure 4.29: Optical micrograph (a) 140A_15V at Gas flow rate: 10LPM and Heat Input of
(a) 6.7kJ/cm
Figure 4.30: Optical micrograph (b) 140A_21V at Gas flow rate: 10LPM and Heat Input
of (b) 9.4kJ/cm
Figure 4.31: Optical micrograph (c) 180A_15V at Gas flow rate: 10LPM and Heat Input of
(c) 8.6kJ/cm

Figure 4.32: Optical micrograph (c) 180A_21V at Gas flow rate: 10LPM and Heat Input of
(d) 12.1kJ/cm
Figure 4.33: Optical micrograph (a) 140A_15V at Gas flow rate: 14LPM and Heat Input of
(a) 6.7kJ/cm
Figure 4.34: Optical micrograph (b) 140A_21V at Gas flow rate: 14LPM and Heat Input
of (b) 9.4kJ/cm
Figure 4.35: Optical micrograph (c)180A_15V at Gas flow rate: 14LPM and Heat Input of
(c)8.6kJ/cm76
Figure 4.36: Optical micrograph (d) 180A_21V at Gas flow rate: 14LPM and Heat Input
of (d)12.1kJ/cm76
Figure 4.37: Optical micrograph (a) 140A_15V at Gas flow rate: 18LPM and Heat Input
of (a)6.7kJ/cm77
Figure 4.38: Optical micrograph (b) 140A_21V at Gas flow rate: 18LPM and Heat Input
of (b) 9.4kJ/cm77
Figure 4.39: Optical micrograph (c) 180A_15V at Gas flow rate: 18LPM and Heat Input of
(c) 8.6kJ/cm78
Figure 4.40: Optical micrograph (d) 180A_21V at Gas flow rate: 18LPM and Heat Input
of (d)12.1kJ/cm
Figure 4.41: XRD analysis of A6061 weld bead during welding
Figure 4.42: XRD analysis of A6063 weld bead during welding
Figure 4.43: Variation of microhardness across weld of A6061 for Current: 160A, Voltage:
18V and Gas flow rate: 14LPM and different zones BM: Base Metal, HAZ: Heat Affected
Zone FZ: Fusion Zone
Figure 4.44: Microhardness distribution of A6061 for Fusion zones at gas flow rate of
10LPM

Figure 4.45: Microhardness distribution of A6061 for Fusion zones at gas flow rate of
14LPM
Figure 4.46: Microhardness distribution of A6061 for Fusion zones at gas flow rate of
18LPM
Figure 4.47: Variation of microhardness across weld of A6061 for Current: 160A, Voltage:
18V and Gas flow rate: 14LPM and different zones BM: Base Metal HAZ: Heat Affected
Zone FZ: Fusion Zone
Figure 4.48: Microhardness distribution of A6063 for Fusion zones at gas flow rate of
10LPM
Figure 4.49: Microhardness distribution of A6063 for Fusion zones at gas flow rate of
14LPM
Figure 4.50: Microhardness distribution of A6063 for Fusion zones at gas flow rate of
18LPM
Figure 4.51: Tensile samples of MIG Joints a) Before testing, b) A6061 After testing and
c) A6063 After testing90
Figure 4.52: The variations in Yield Strength, Ultimate Tensile Strength and %Elongation
of A6061 aluminium alloy and welded A6061 at 10 LPM gas flow rate94
Figure 4.53: The variations in Yield Strength, Ultimate Tensile Strength and %Elongation
of A6061 aluminium alloy and welded A6061 at 14 LPM gas flow rate95
Figure 4.54: The variations in Yield Strength, Ultimate Tensile Strength, and %Elongation
of A6061 aluminium alloy and welded A6061 at 18 LPM gas flow rate96
Figure 4.55: The variations in Yield Strength, Ultimate Tensile Strength, and %Elongation
of A6063 aluminium alloy and welded A6063 at different working conditions (a) at 10LPM

Figure 4.56: The variations in Yield Strength, Ultimate Tensile Strength, and %Elongation
of A6063 aluminium alloy and welded A6063 at different working conditions at (b)
14LPM
Figure 4.57: The variations in Yield Strength, Ultimate Tensile Strength, and %Elongation
of A6063 aluminium alloy and welded A6063 at different working conditions (c) at 18LPM
Figure 4.58: SEM micrographs of the fracture surface A6061-T6 equiaxed dimples100
Figure 4.59: SEM micrographs of the fracture surface A6063 T-6 Plastic slip bands Dimple
Figure 4.60: SEM micrographs of the fracture surface Welded A A6061 Dimple Plastic slip
bands Cleavage facets Tear ridges
Figure 4.61: SEM micrographs of the fracture surface Welded A6063 Plastic slip bands
Figure 4.62: SEM images of fracture surfaces of A6061 (a) Base metal (b) 14LPM
(c) 10LPM (d) 18LPM
Figure 4.63: SEM images of fracture surfaces of A6063 (a) Base metal, b) 10lpm,
c)14 LPM and d) 18lpm)105