## References

- IEA (2021), Global Energy Review 2021, IEA, Paris https://www.iea.org/reports/global-energy-review-2021
- [2] Vijayan, P.K, Nayak, A.k, Kumar K., 2019 "Single-Phase, Two-Phase and Supercritical Natural Circulation Systems", Woodhead Publishing, ISBN 9780081024867.
- [3] Pinto, R.V.; Fiorelli, F.A.S., 2016, "Review of the mechanisms responsible for heat transfer enhancement using nanofluids," Appl. Therm. Eng., vol.108, pp. 720–739.
- [4] Close, D.J., 1962, "The Performance of Solar Water Heaters with Natural Circulation," Solar Energy, 6, pp. 33–40.
- [5] Ong, K.S., 1974. A finite-difference method to evaluate the thermal performance of a solar water heater. Sol. Energy 16 (3–4), 137–147.
- [6] Mertol, A., Place, W., Webster, T., Greif, R., 1981. Detailed loop model (DLM) analysisof liquid solar thermosiphons with heat exchangers. Sol. Energy 27 (5), 367–386.
- [7] Morrison, G.L., Ranatunga, D.B.J., 1980. Transient response of thermosyphon solarcollectors. Sol. Energy 24 (1), 55–61.
- [8] Cohen, H., Bayley, F.J., 1955. "Heat transfer problems of liquid cooled gas turbine blades," Proc. Inst. Mech. Eng. 169, 1063–1080.
- Kreitlow, D.B., Reistad, G.M., Miles, C.R., Culver, G.G., 1978. "Thermosyphon models for downhole heat exchanger applications in shallow geothermal systems".
   J.Heat Transfer 100, 713–719.
- [10] Sinha, R.K., Kakodkar, A., 2006. "Design and development of the AHWR The Indian Thorium fuelled innovative nuclear reactor," Nucl. Eng. Des. 236 (7–8),683– 700.

- [11] Basu, D.N., Bhattacharyya, S., and Das, P.K., 2009, "Steady-state behavior of a twophase natural circulation loop with thermodynamic nonequilibrium," Journal of Heat Transfer, 131(2), 022901.
- [12] Tuma, P.E., Mortazavi, H.R., 2006. "Indirect thermosyphons for cooling electronic devices. Electron," Cool. 12 (1), 26–32.
- [13] Pastukhov, V.G., and Maydanik, Y.F., 2007, "Low-noise cooling system for PC on the base of loop heat pipes," Applied Thermal Engineering, 27, 894–901.
- [14] Kaga, S., Nomura, T., Seki, K., Hirano, A., 2008. "Development of compact inverter refrigerating system using R600a/CO2by Thermosiphon," In: Proc. 8th Gustav Lorentzen Conf. on Natural Working Fluids, Copenhagen, Denmark, Paper No. W3-04.
- [15] Yadav, A.K., Bhattacharyya, S., and Ramgopal, M., 2016, "Optimum operating conditions for subcritical/supercritical fluid-based natural circulation loops," Journal of Heat Transfer, 138(11), 112501.
- [16] Kumar, K. K., and Ram Gopal, M., 2009, "Carbon Dioxide as Secondary Fluid in Natural Circulation Loops," Proc. Inst. Mech. Eng., Part E, 223(3), 189–194.
- [17] Japikse, D., 1973, "Advances in thermosyphon technology," In: Hartnett, J.P., IrvineJr., T.F. (Eds.), Advances in Heat Transfer, vol. 9. Academic Press, New York, pp.1–111.
- [18] Zvirin, Y.,1981, "A review of N. C. loops in PWR and other systems," Nuclear Engineering and Design, 67,203-225.
- [19] Greif, R., 1988. Natural circulation loops. J. Heat Transfer 110,1243–1258.
- [20] Basu, D. N., Bhattacharyya, S., and Das P.K., 2014"A review of modern advances in analyses and applications of single-phase natural circulation loop in nuclear thermal hydraulics", Nuclear Engineering and Design, 280,326-348.

- [21] Creveling, H.F., De Paz, J.F., Baladi, J.Y., and Schoenhals, R.J., 1975, "Stability characteristics of a single-phase free convection loop," J. Fluid Mech. 67 (1), 65–84.
- [22] Damerell, P. S., and Schoenhals, R. J., 1979, "Flow in a toroidal thermosyphon with angular displacement of heated and cooled sections," J. Heat Transfer, 101, 672-676.
- [23] Zvirin, Y., Shitzer, A., and Grossman, G., 1977, "The natural circulation solar heatermodels with linear and non-linear temperature distribution," Int. J. Heat Mass Transfer, 20, 997-999.
- [24] Zvirin, Y., Shitzer, A., and Bartal-Bornstein, A.,1978, "On the stability of the natural circulation solar heater," Proc. 6th Int. heat transfer Conference, Toronto, Canada, vol. 2,141-145.
- [25] Hallinan, K.P., Viskanta, R., 1985, "Heat transfer from a vertical tube bundle under natural circulation conditions," Int. J. Heat Fluid Flow 6 (4), 256–264.
- [26] Hallinan, K.P., Viskanta, R., 1986, "Dynamics of a natural circulation loop: analysis & experiments," Heat Transfer Eng. 7 (3–4), 43–52.
- [27] Misale, M., and Frogheri, M., 1999, "Influence of pressure drops on the behaviour of a single-phase natural circulation loop: Preliminary results," International Communications in Heat and Mass Transfer, 26 (5),597–606.
- [28] Vijayan, P.K., Sharma, M., Saha, D., 2007. Steady state and stability characteristics of single- phase natural circulation in a rectangular loop with different heater and cooler orientations. Exp. Therm. Fluid Sci. 31, 9250–9945.
- [29] Garibaldi, P., and Misale, M., 2008, "Experiments in Single-Phase Natural Circulation Mini loops With Different Working Fluids and Geometries,"Journal of Heat Transfer, 130 (10),1–5.

- [30] Misale, M., Garibaldi, P., Tarozzi, L., and Barozzi, G.S., 2011, Influence of thermal boundary conditions on the dynamic behaviour of a rectangular single-phase natural circulation loop, Int. J. of Heat and Fluid Flow, 32 (2),413-423.
- [31] Misale, M., 2016, "Experimental study on the influence of power steps on the thermohydraulic behavior of a natural circulation loop," Int. J. Heat and Mass Trasfer, 99, 782-791.
- [32] Vijayan, P.K., 2002, "Experimental observations on the general trends of the steady state and stability behaviour of single-phase natural circulation loops," Nucl. Eng.Des;, 215 (1) 139-152.
- [33] Vijayan P.K, Nayak, A.K., Saha, D., Gartia M.R., 2008, "Effect of loop diameter on the steady state and stability behaviour of single-phase and two-phase natural circulation loops," Science and Technology of Nuclear Installations, 672704.
- [34] Misale, M., Devia, F., 2012 "Analysis of the effects of heat sink temperature on single-phase natural circulation loops behaviour," International Journal of Thermal Sciences, 59, 195-202.
- [35] Chen, L., Deng, B.L., Zhang, X.R., 2013b. "Experimental investigation of CO2 thermosyphon flow and heat transfer in the supercritical region," Int. J. Heat Mass Transfer 64, 202–211.
- [36] Chen, L., Zhang, X.R., Jiang, B., 2013c. Effects of heater orientations on the natural circulation and heat transfer in a supercritical CO2 rectangular loop. J. Heat Transfer 136 (5), 052501.
- [37] Chen, L., Zhang, X.R., Deng, B.L., Jiang, B., 2013e, "Effects of inclination angle and operation parameters on supercritical CO2 natural circulation loop," Nucl. Eng. Des. 265, 895–908.

- [38] Sharma, M., Pilkhwal, D.S., Vijayan, P.K., Saha, D., Sinha, R.K., 2010c, "Experimental and theoretical investigations on steady-state behavior of natural circulation systems operating with supercritical carbon-dioxide," In: Revankar, S.T., Iyer, K.N. (eds.), Proc. 20th National and 9th International ISHMT-ASME Heat and Mass Transfer Conference, Mumbai, India.
- [39] Sharma, M., Vijayan, P.K., Pilkhwal, D.S., and Asako, Y., 2013, "Steady state and stability characteristics of natural circulation loops operating with carbon dioxide at supercritical pressures for open and closed loop boundary conditions," Nucl. Eng. Des. 265, 737–754.
- [40] Kumar K.K, Gopal M.R,2009,"Carbon dioxide as a secondary fluid in natural circulation loops," Proceedings of the Institution of Mechanical Engineers, Part E: Journal of Process Mechanical Engineering, 223(3):189-194. doi:10.1243/09544089JPME242
- [41] Borgohain, A., Jaiswal, B. K., Maheshwari, N. K., Vijayan, P. K., Saha, D., Sinha, R.
  K., 2011, "Natural circulation studies in a lead bismuth eutectic loop," Progress in Nucl. Energy, 53, 308-319.
- [42] Naphade, P., Borgohain, A., ThundilKaruppa Raj, R., and Maheshwari, N. K., 2013,
   "Experimental and CFD study on Natural Circulation Phenomenon in Lead Bismuth Eutectic Loop," Procedia Engineering, 64, 936-945.
- [43] Borgohain, A.,Srivastava, A.K., Jana, S.S., Maheshwari, N.K., Kulkarni, R.D., Vijayan, P.K., Tewari, R., Ram A. M., and Jha, S.K., 2016, "Natural circulation studies in a LBE loop for a wide range of temperature," Nuclear Engineering and Design, 300,358-375.
- [44] Kudariyawar, J.Y., Srivastava, A.K., Vaidya A.M, Maheshwari, N.K., and Satyamurthy, P., 2016, "Computational and Experimental Investigation of Steady

state and Transient Characteristics of Molten Salt Natural Circulation Loop," Applied Thermal Engineering, 99,560-571,

- [45] Srivastava, A.K., Kudariyawar, J.Y., Borgohain, A., Maheshwari, N.k., and Vijayan,
   P. K., 2016, "Experimental and theoretical studies on the natural circulation behaviour of molten salt," Applied Thermal Engineering, 513-521.
- [46] Britsch, K., Anderson, M., Brooks, P., Sridharan, K., 2019 "Natural circulation FLiBe loop overview," International Journal of Heat and Mass Transfer, 134, 2019, 970-983.
- [47] Nayak, A.K.,Gartia, M.R., and Vijayan, P.K., 2008, "An experimental investigation of single-phase natural circulation behaviour in a rectangular loop with Al<sub>2</sub>O<sub>3</sub> nanofluids," Experimental Thermal and Fluid Science, 33,184–189.
- [48] Nayak, A.K., Gartia, M.R., and Vijayan, P.K., 2009, "Nanofluids: A Novel Promising Flow Stabilizer in Natural Circulation Systems," American Institute of Chemical Engineers, 55, 268–274.
- [49] Nayak, A.K., Gartia, M.R., and Vijayan, P.K., 2009, "Thermal-hydraulic characteristics of a single-phase natural circulation loop with water and Al2O3 nanofluid,"Nuclear Engineering and Design, 239,526–540.
- [50] Misale, M., Devia, F.,and Garibaldi, P., 2012, "Experiments with Al2O3nanofluid in a single-phase natural circulation mini-loop: Preliminary results," Applied Thermal Journal of Heat Transfer 29 Engineering, 40, 64–70.
- [51] Ho, C.J., Chung, Y.N., and Lai, C.M, 2014, "Thermal performance of Al2O3/water nanofluid in a natural circulation loop with a mini-channel heat sink and heat source," Energy Conversion and Management, 87,848–858.
- [52] Dogana, S., and Turgut, A., 2015, "Enhanced effectiveness of nanofluid based natural circulation mini loop," Applied Thermal Engineering, 75, pp. 669–676.

- [53] Koca, H.D., Doganay, S., and Turgut, A., 2017, "Thermal characteristics and performance of Ag-water nanofluid: Application to natural circulation loops," Energy Conversion and Management, 135,pp. 9–20.
- [54] Thomas, S., and Sobhan, C.B., 2017, "Stability and transient performance of vertical heater vertical cooler natural circulation loops with metal oxide nanoparticle suspensions," Heat Transfer Engineering, 39(10), pp. 861-873.
- [55] Bejjam, R. B., Kiran Kumar, K., and Balasubramanian, K., 2019. "Experimental Studies on Nanofluid-Based Rectangular Natural Circulation Loop." ASME. J. Thermal Sci. Eng. Appl. 11(4): 041006.
- [56] Çobanoğlu, N., and Karadeniz, Z.H., 2020. "Effect of Nanofluid Thermophysical Properties on the Performance Prediction of Single-Phase Natural Circulation Loops" Energies 13, no. 10: 2523.
- [57] Keller, J.B., 1966, "Periodic oscillations in a model of thermal convection" J. Fluid Mech.26 (3), 599–606.
- [58] P. Welander, 1979, "On the oscillatory instability of a differentially heated fluid loop," J. Fluid Mech., 29 (1)17-30.
- [59] Sen, M., Trevi<sup>n</sup>o, C., 1982. Dynamic analysis of a one-dimensional thermosyphonmodel. J. Therm. Eng. 3 (1), 15–20.
- [60] Chen, K., 1985, "On the oscillatory instability of closed loop thermosyphons," Journal of Heat Transfer 107,826-831.
- [61] Mousavian, S.K., Misale, M., D'Auria, F., and Salehi, M.A., 2004, "Transient and stability analysis in single-phase natural circulation loop," Annals of Nuclear Energy, 31, 1177-1198.

- [62] Sadhu, S., Ramgopal, M., and Bhattacharyya, S., 2018, "Steady-state analysis of a high-temperature natural circulation loop based on water- cooled supercritical CO2," Journal of Heat Transfer,140(6), 062502.
- [63] Cammi, A.,Misale, M., Devia, F.,Cauzzi, M.T.,Pini, A., and Luzzi, L., 2017, "Stability analysis by means of information entropy: Assessment of a novel method against natural circulation experimental data," Chemical Engineering Science, 166,220-234.
- [64] Rao, N.M., Mishra, M., Maiti, B., and Das, P.K., 2005, "Dynamic performance of a natural circulation loop with end heat exchangers under different excitations," Int. Com. Heat Mass Transfer, 48 (15), 3185-3196.
- [65] Basu, D.N., Bhattacharyya, S., and Das, P.K.,2012, "Performance comparison of rectangular and toroidal natural circulation loops under steady and transient conditions," International Journal of Thermal Sciences 57,142–151.
- [66] Basu, D.N., Bhattacharyya, S., and Das, P.K., 2013, "Dynamic response of a singlephase rectangular natural circulation loop to different excitations of input power," International Journal of Heat and Mass Transfer 65, 131–142.
- [67] Basu, D.N., Bhattacharyya, S., and Das, P.K., 2013, "Influence of geometry and operating parameters on the stability response of single-phase natural circulation loop," International Journal Heat Mass Transfer 58, 322–334.
- [68] Misale, M., and Devia, F., 2012, "Analysis of the effects of heat sink temperature on single-phase natural circulation loops behaviour," International Journal of Thermal Sciences, 59, 195-202.
- [69] Krishnani, M., and Basu D.N., 2017, "Computational stability appraisal of rectangular natural circulation loop: Effect of loop inclination," Annals of Nuclear Energy,107,17-30.

- [70] Vijayan, P.K., and Austregesilo, H., 1994. "Scaling laws for single-phase natural circulationloops," Nucl. Eng. Des. 152 (1–3), 331–347.
- [71] Huang, B. J., and Zelaya, R., 1988, "Heat transfer behavior of a rectangular Thermosyphon loop," Journal of Heat Transfer, 110, 487-493.
- [72] Ambrosini, W., and Ferreri, J. C., 1998, "The effect of truncation error on numerical prediction of stability boundaries in a natural circulation loop." Nuclear Engineering Design, 183, 53-76.
- [73] Ambrosini, W., Forgione, N., Ferreri, J. C., Bucci, M., 2004, The effect of wall friction in Single-phase natural circulation stability at the transition between laminar and turbulent flow, Annals of Nuclear Energy, 31, 1833-1865.
- [74] Pilkhwal, D. S., Ambrosini, W., Forgione, N., Vijayan, P. K., Saha, D., Ferreri, J. C., 2007, "Analysis of the unstable behavior of a single-phase natural circulation loop with one dimensional and computational fluid-dynamic models," Annals of Nuclear Energy, 34,339-355.
- [75] Swapnalee, B.T., and Vijayan, P.K., 2011 "A generalized flow equation for single phase natural circulation loops obeying multiple friction laws," Int. J. Heat Mass Transfer 54, 2618–2629.
- [76] Cammi, A., Luzzi, L., and Pini, A., 2016, "The influence of the wall thermal inertia over a single-phase natural convection loop with internally heated fluids." Chem. Eng. Sci. 153 (2016) 411-433.
- [77] Misale, M., Ruffino, P., and Frogheri, M., 2000, "The influence of the wall thermal capacity and axial conduction over a single-phase natural circulation loop: 2-D numerical study," Heat Mass Transf. 36 (2000) 533-539.
- [78] Lin, J.F., Chiu, S.Y., and Ho, C. J., 2008, "Conjugate heat transfer simulation of a rectangular natural circulation loop." Heat Mass Transf. 45,167-175.

- [79] Cheng, H., Lei, H., Zeng, L., and Dai C., 2019, "Experimental investigation of singlephase natural circulation in a mini-loop driven by heating and cooling fluids." Exp. Therm. Fluid Sci. 103,182-190.
- [80] Basu, D.N., Bhattacharyya, S., and Das, P.K., 2007, 'Effect of heat loss to ambient on steady-state behaviour of a single-phase natural circulation loop," Applied Thermal Engineering 27, 1432–1444.
- [81] Krishnani, M., and Basu D.N.,2016, "On the validity of Boussinesq approximation in transient simulation of single-phase natural circulation loops," International Journal Thermal Sciences 105, 224-232.
- [82] Sabharwall, P., Yoo, Y.J., Wu, Q., and Sienicki, J.J., 2012. Natural circulation and linear stability analysis for liquid-metal reactors with the effect of fluid axial conduction. Nucl. Technol. 178 (3), 298-317.
- [83] Wu, Q., and Sienichi, J.J., 2003. "Stability analysis on single-phase natural circulation in Argonne lead loop facility," Nucl. Eng. Des. 224, 23-32.
- [84] Sabharwall, P., Yoo, Y.J., Wu, Q., and Sienicki, J.J., 2012. "Natural circulation and linear stability analysis for liquid-metal reactors with the effect of fluid axial conduction," Nucl. Technol. 178 (3), 298-317.
- [85] Coccoluto, G., Gaggini, P., Labanti, V., Tarantino, M., Ambrosini, W., Forgione, N.,Napoli, A., and Oriolo, F., 2011. 'Heavy liquid metal natural circulation in a one dimensional loop," Nucl. Eng. Des. 241, 1301-1309.
- [86] Kudariyawar, J.Y., A.K., Vaidya A.M, Maheshwari, N.K., Satyamurthy, P., and Srivastava, A.K, 2015, "Estimating Steady state and Transient characteristics of Molten Salt Natural Circulation Loop using CFD," KERNTECHNIK 80 (1), 20-31. DOI 10.3139/124.110478

- [87] Kudariyawar, J.Y., A.K., Vaidya A.M, Maheshwari, N.K., Satyamurthy, P., Srivastava, A.K, and Lingade, B.M., 2016, "Investigation on heat transfer behaviour of molten salt natural circulation loop using numerical simulations, Journal of Nuclear Energy Science and Power Generation Technology, 5:5, DOI: 10.4172/2325-9809.1000165
- [88] Srivastava, A. K., Vaidya, A. M., Maheshwari, N. K., Vijayan, P. K., 2013, "Heat transfer and pressure drop characteristics of molten fluoride salt in circular pipe," Applied Thermal Engineering, 61, 198-205.
- [89] Shin, Y., Seo, S. B., Kim, I. G., and Bang,2018,S "Study on flow characteristics of high-Pr heat transfer fluid near the wall in a rectangular natural circulation loop", International Journal of Heat and Mass Transfer, Volume 121,1350-1363,
- [90] Shin, Y., Seo, S. B., Kim, I. G., and Bang, I. C., 2016, "Natural circulation with DOWTHERM RP and its MARS code implementation for molten salt-cooled reactors." Int. J. Energy Res., 40: 1122–1133.
- [91] Shin, Y., Seo, S. B., Kim, I. G., and Bang, I. C, 2016, "Single-phase Natural Circulation of High-Pr Heat Transfer Simulant oil," Transactions of the Korean Nuclear Society Spring Meeting Jeju, Korea, May 12-13.
- [92] K, Kiran & Bejjam, Ramesh & Najan, Atul. 2014, "Steady state analysis of nanofluid based thermosyphon system".
- [93] Bejjam, R.B., and Kumar, K.K., 2018, "Numerical investigation to study the effect of loop inclination angle on thermal performance of nanofluid-based single-phase natural circulation loop performance of nanofluid-based single-phase natural circulation loop," International Journal of Ambient Energy, DOI: 10.1080/01430750.2018.1432502.

- [94] Bejjam, R.B., and Kumar K.K., 2017, "Numerical study on heat transfer characteristics of nanofluid based natural circulation loop," Thermal Science, 22 (2), pp. 1-12.
- [95] Devi, P., Rao, C.S., and Kumar, K., 2018, "Suitability of magnetic nanofluid in heat transfer loops, " International Journal of Heat and Technology, 36(26), pp. 195-200.
- [96] Karadeniz, Z. H., Doganay, S., Turgut, A., 2016, "Numerical study on nanofluid based single phase natural circulation mini loops: A steady 3D approach," High Temp. Press. 45.
- [97] P.K. Vijayan, V.K. Bhojwani, M.H. Bade, M. Sharma, A.K. Nayak, D. Saha, R.K. Sinha, 2002." Investigation on the effect of heater and cooler orientation on the steady state, transient and stability behaviour of single-phase natural circulation in a rectangular loop", BARC/2001/E/034.
- [98] Sundar,L.S., Sharma,K.V., Singh M.K., and Sousa, A.C.M., 2017, "Hybrid nanofluids preparation, thermal properties, heat transfer and friction factor – A review," Renewable and Sustainable Energy Reviews, 68,pp. 185–198.
- [99] E.B. Ogut, 2009. "Natural convection of water-based nanofluids in an inclined enclosure with a heat source", International Journal of Thermal Sciences 48, 2063– 2073.
- [100] M. Devarajan, N.P. Krishnamurthy, M. Balasubramanian, B. Ramani, S. Wongwises,K.A. El-Naby, R. Sathyamurthy, 2018. "Thermophysical properties of CNT andCNT/Al2O3 hybrid nanofluid", Micro and Nano Letter 13, 617–621.
- [101]L. Deng, R.J. Young, I.A. Kinloch, R. Sun, G. Zhang, L. Noe, M. Monthioux, 2014. "Coefficient of thermal expansion of carbon nanotubes measured by Ramaspectroscopy", Applied Physics Letters 104, 051901.

- [102]D. Yoon, Y.W. Son, H. Cheong, 2011. "Negative thermal expansion coefficient of graphene measured by Raman spectroscopy, Nano Lett. 11, 3227–3231.
- [103]N. Ahammed, L.G. Asirvatham, S. Wongwises, 2016, "Entropy generation analysis of graphene–alumina hybrid nanofluids in multiport mini channel heat exchanger coupled with thermoelectric cooler", International Journal of Heat and Mass Transfer 103, 1084–1097.
- [104]Chamkha, A.J., Miroshnichenko, I.V., and Sheremet, M.A., 2017, "Numerical analysis of unsteady conjugate natural convection of hybrid water-based nanofluid in a semi-circular cavity," Journal of Thermal Science and Engineering Applications, 9, pp. 1–9.
- [105]Timofeeva, E.V., Routbort, J.L., and Singh, D., 2009, "Particle shape effects on thermophysical properties of alumina nanofluids," Journal of Applied Physics, 106,014304.
- [106] Streeter, V.L., Wylie E.B., 1983, "Fluid Mechanics, McGraw-Hill Book Company, Singapore," pp. 243–245.
- [107]Cengel, Y. A., & Ghajar, A. J. 2014, "Heat and mass transfer: Fundamentals and applications (5th ed.)." McGraw-Hill Professional
- [108]Gnielinski, V., 1976, "New equations for heat and mass transfer in turbulent pipe and channel flow", Int. Chem. Eng. 16, 359–368.
- [109] Moraveji, M.K., Darabi, M., Haddad, S.M.H. and Dabvaranejad R., 2011, "Modelling of convective heat transfer of a nanofluid in the developing region of a tube flow withcomputational fluid dyanamics," Int. Commun. Heat Mass Transf. 38, 1291– 1295.

- [110] Vijjaha, R.S. and Das, D.K., 2010, "Development of new correlations for convective heat transfer and friction factor in turbulent regime for nanofluid," Int. J. Heat Mass Transf. 53, 4607–4618.
- [111]Klein SA. 2017, Engineering Equation Solver Professional. Version V10.215, F-Chart Software, Madison, WI.
- [112]Celik, I., Ghia, U., Roache, P. J., Freitas, C., Coleman, H., and Raad, P. E., 2008, "Procedure for Estimation and Reporting of Uncertainty Due to Discretization in CFD Applications," J. Fluids Eng., 130(7), p. 078001.
- [113] Tiwari, A.K., Ghosh, P., and Sarkar, J., 2015, "Particle concentration levels of various nanofluids in plate heat exchanger for best performance," Int. J. Heat Mass Transf. 89, 1110–1118.
- [114]Maxwell, J.C. 1881, "A Treatise on Electricity and Magnetism"; Clarendon Press: Oxford, UK; Volume 1.
- [115]Batchelor, G.K. 1977, "The effect of Brownian motion on the bulk stress in a suspension of spherical particles". J. Fluid Mech., 83, 97–117.
- [116] Hallinan, K.P., Viskanta, R., Heat transfer from a rod bundle under natural circulation conditions, NUREG/CR-4556.
- [117]S.W. Churchill, H.H.S. Chu, 1975, "Correlating equations for laminar and turbulent free convection from vertical plate", Int. J. Heat Mass Transfer 18 (11) 1323–1329.
- [118]Kumar, V., Sarkar, J., 2020 "Experimental hydrothermal characteristics of minichannel heat sink using various types of hybrid nanofluids," Advanced Powder Technology," Volume 31, Issue 2, 621-631.
- [119]S. Kline and F. Mcclintock, 1953, "Describing Uncertainties in Single-Sample Experiments," Mechanical Engineering, Vol. 75, pp. 3-8.

[120]Edwin E. Garcia Rojas, Jane S.R. Coimbra & Javier Telis-Romero, 2013, "Thermophysical Properties of Cotton, Canola, Sunflower and Soybean Oils as a function of Temperature", International Journal of Food Properties, 16:7, 1620-1629.

## LIST OF PUBLICATIONS

## JOURNALS

- Mayaram Sahu and Jahar Sarkar, "Steady-state energetic and exergetic performances of single-phase natural circulation loop with hybrid nanofluids," J. Heat Transf. 141 (2019), 082401.
- Mayaram Sahu, Jahar Sarkar and Laltu Chandra, "Transient thermo-hydraulics and performance characteristics of single-phase natural circulation loop using hybrid nanofluids", Int. Commun. Heat Mass Transf. 110 (2020) 104433.
- Mayaram Sahu, Jahar Sarkar and Laltu Chandra, "Steady-state and transient hydrothermal analysis of single-phase natural circulation loop using ternary hybrid nanofluid", AIChE Journal 67, no. 6 (2021): e17179.
- Mayaram Sahu, Jahar Sarkar and Laltu Chandra, "Single-phase natural circulation loop using oils and ternary hybrid nanofluids: Steady-state and transient thermohydraulics", J. Thermal Sci. Eng. Appl. 13 (2) (2021), 021030.
- Mayaram Sahu, Jahar Sarkar and Laltu Chandra, "Effects of various modeling assumptions on steady-state and transient performances of single-phase natural circulation loop," Int. Commun. Heat Mass Transf. 124 (2021) 105247.
- Mayaram Sahu, Jahar Sarkar and Laltu Chandra, "Experimental investigation of performances of single-phase natural circulation loop using water-based mono/hybrid nanofluids", Revision submitted, *Int. J. Therm. Sci.*,2022
- Mayaram Sahu, Jahar Sarkar and Laltu Chandra, "Experimental study on energyexergy performance of single-phase natural circulation loop using mono/hybrid nano-oils" Revision submitted, *Applied thermal engineering*,2022.

## CONFERENCES

- Mayaram Sahu, Jahar Sarkar and Laltu Chandra, "Performance of single-phase natural circulation loop using hybrid nanofluids for heating above 1000 C". Proceedings of the 25th National and 3rd International ISHMT-ASTFE Heat and Mass Transfer Conference, 2019, 28-31 December, IIT Roorkee.
- Mayaram Sahu, Shubham Kashyap, Jahar Sarkar and Laltu Chandra, "Evaluation of thermal performance of passive indirect solar water heating system using thermal oil-based hybrid nanofluids", " In Proceedings of the 26thNational and 4th International ISHMT-ASTFE Heat and Mass Transfer Conference December 17-20, 2021, IIT Madras, Chennai-600036, Tamil Nadu, India. Begel House Inc., 2021.