

REFERENCES

- Ahamed, H. and Senthilkumar, V., Consolidation behavior of mechanically alloyed aluminum based nanocomposites reinforced with nanoscale Y_2O_3/Al_2O_3 particles, Mater. Charact., 62, 1235 – 1249, 2011.
- Aikin, R.M., The mechanical properties of in-situ composites, J. Metals, 8, 35-39, 1997.
- Akbarpour, M.R., Salahi, E., Hesari, F. A., Simchi, A. and Kim, H.S., Microstructure and compressibility of SiC nanoparticles reinforced Cu nanocomposite powders processed by high energy mechanical milling, Ceram. Inter., 40, 951–960, 2014.
- Akhtar, F., Askari, S. J., Shah, K.A., Dua, X. and Guo, S., Microstructure, mechanical properties, electrical conductivity and wear behavior of high volume TiC reinforced Cu-matrix composites, Mater. Charact., 60, 327 – 336, 2009.
- Alaneme, K.K. and Odoni, B.U., Mechanical properties, wear and corrosion behavior of copper matrix composites reinforced with steel machining chips, Eng. Sci.Tech. Inter. J., 2016.
- Altinsoy, I., Efe, F.G.C., Aytaş, D., Kılıç, M., Ozbek, İ. and Bindal, C., Some Properties of Cu-B₄C Composites Manufactured by Powder Metallurgy, Peri.Engg.Natu.Sci., 1,34-38, 2013.
- Archard, J. F., Contact and rubbing of flat surfaces, J. App. Phy., 24, 981–988, 1953.
- Ayyappadas, C., Muthuchamy, A., Annamalai, A. R. and Agrawal, D.K., An investigation on the effect of sintering mode on various properties of copper-graphene metal matrix composite, Adv. Pow. Techno., 28, 1760–1768, 2017.
- Bagheri,G.H.A.,The effect of reinforcement percentages on properties of copper matrix composites reinforced with TiC particles, J. Alloys Compd., 676, 120-126, 2016.
- Bagheri,G.H.A., Abachi, P., Purazrang, K. and Rostami, A., Production of Cu-TiC nanocomposite using mechanical alloying route, Adv. Mat. Res. 829,572-576, 2013.
- Bowden, F. P. and Tabor, D., The friction and lubrication of solids, Part I, Clarendon Press, Oxford, 1954.
- Bowden, F.P and Leben, L.,The nature of sliding and the analysis of friction, Proc. of the royal soc. of London A, 169,371-379, 1939.
- Buytoz, S., Dagdelen, F., Islak ,S., Kok, M., Kir, D. and Ercan, E., Effect of the TiC content on microstructure and thermal properties of Cu–TiC composites prepared by powder metallurgy, J. Therm. Anal. Calorim., 117, 1277–1283, 2014.
- Callister, W.D., Mater. Sci. and Eng., John Wiley & Sons, 2007.

Celikyurek, I., Korpe, N.O., Olcer, T. and Gurler, R., Microstructure, properties and wear behaviors of $(\text{Ni}_3\text{Al})_p$ reinforced Cu matrix composites, *J. Mater. Sci. Technol.*, 27, 937–943, 2011.

Chandrakanth, R.G., Rajkumar, K. and Aravindan, S., Fabrication of copper–TiC–graphite hybrid metal matrix composites through microwave processing, *Int. J. Adv. Manuf. Technol.*, 48, 645–653, 2010.

Chrysanthou, A. and Erbaccio, G., Enhancing the dispersion of TiC in copper, *J. Mater. Sci. Lett.*, 15, 774–5, 1996.

Chauhan, S. R. and Dass, K., Optimization of machining parameters in turning of titanium (Grade-5) alloy using response surface Methodology, 27, 531-537, 2012.

Cheng, J., Ma, J., Li, F., Qiao, Z., Yang, J. and Liu, W., Dry-sliding tribological properties of Cu/AlMgB14 composites, *Tribol. Lett.*, 55, 35–44, 2014.

Chang, B.P., Akil, H.M., Nasir, R.B. and Khan, A., Optimization on wear performance of UHMWPE composites using response surface methodology, *Tribo. Intern.*, 88 ,252–262, 2015.

Chu, K., Liu, Z., Jia, C., Chen, H., Liang, X. and Gao, W., Thermal conductivity of SPS consolidated Cu/diamond composites with Cr-coated diamond particles, *J. Alloys Comp.*, 490, 453–458, 2010.

Chung, D.D.L., Metal-Matrix Composites, Carbon Composites (Second Edition), doi.org/10.1016/B978-0-12-804459-9.00009-9, 532-562, 2014.

Dash, K. and Ray, B.C., Implications of degree of thermal shocks on flexural properties of Cu-Al₂O₃ micro- and nano-composites, *J. Mater. Eng. Perform.*, 25, 259-266, 2016.

Davis, J.R., Copper and copper alloys, ASM International, Materials Park, OH, 2001.

Das, S., Das, S. and Das, K., Synthesis and thermal behavior of Cu/Y₂W₃O₁₂ composite, *Ceram. Inter.*, 40, 6465–64, 2014.

Deshpande ,P.K. and Lin, R.Y., Wear resistance of WC particle reinforced copper matrix composites and the effect of porosity, *Mater. Sci. Eng.*, A, 418, 137–145, 2006.

Denny, P.J., Compaction Equations: A Comparison of the Heckel and Kawakita Equations, *Powder Technol.*, 127, 162–172, 2002.

Dhokey, N. B. and Paretkar, R. K., Study of wear mechanisms in copper-based SiCp (20% by volume) reinforced composite, *Wear*, 265,117–133, 2008.

- Donglai, W., Zhenshan, C. and Jun, C., Optimization and tolerance prediction of sheet metal forming process using response surface model, *Comp. Mater. Sci.*, 42, 228–233, 2008.
- Efe, G.C., Ipek, M., Zeytin, S. and Bindal, C., An investigation of the effect of SiC particle size on Cu–SiC composites, *Composites: Part B*, 43, 1813–1822, 2012.
- Eksi, A. and Yuzbasioglu, A.H., Effect of sintering and pressing parameters on the densification of cold isostatically pressed Al and Fe powders, *Mater. Des.*, 28, 1364–1368, 2007.
- Elshimy, H., Heiba, Z.K. and Sayed, K.E., Structural, microstructural, mechanical and magnetic characterization of ball milled Tungsten heavy alloys, *Advan. Mater. Phy. Chem.*, 4, 237–257, 2014.
- Ezilarasan, C., Kumar, V.S., Velayudham, A. and Palanikumar, K., Surface roughness analysis on machining of nimonic C-263 alloy using ANN and RSM techniques, *Int. J. of Preci. Techno.*, 2, 340 – 354, 2011.
- Fathy, A., Shehata, F., Abdelhameed, M. and Elmahdy, M., Compressive and wear resistance of nanometric alumina reinforced copper matrix composites, *Mater. Des.*, 36, 100–107, 2012.
- Gan, K. and Gu, M., The compressibility of Cu/SiCp powder prepared by high-energy ball milling, *J. Mater. Process. Tech.*, 199, 173–177, 2008.
- Gautam, R.K. , Ray, S., Jain, S.C. and Sharma, S.C., Tribological behavior of Cu–Cr–SiCp in situ composite, *Wear* , 265, 902–912, 2008.
- Gautam, R.K. , Ray, S., Sharma, S.C., Jain, S.C. and Tyagi, R., Dry sliding wear behavior of hot forged and annealed Cu–Cr–graphite in-situ composites, *Wear*, 271, 658–664, 2011.
- Gangatharan, K. and Selvakumar, N., Optimizing the dry sliding wear behavior of copper hybrid nano composites reinforced with MWCNTs and nano B₄C using full factorial design, *Trans. Indian. Inst. Met.*, 69, 717–732, 2016.
- Gao, X., Yue, H., Guo, E., Zhang, H., Lin, X., Yao, L. and Wang, Bao., Mechanical properties and thermal conductivity of graphene reinforced copper matrix composites, *Pow. Techno.*, 301, 601-607, 2016.
- Ge, R., A New Powder Compaction Equation, *Int J Powder Metall.*, 27, 211–216, 1991.
- Harish,S. and Keshavamurthy, R., Mechanical properties of copper-TiC *In Situ* metal matrix composite, *App. Mech. Mater.*, 787, 593-597, 2015.

Hassan, A.M., Alrashdan, A., Hayajneh, M.T. and Mayyas, A.Turki., Wear behavior of Al–Mg–Cu–based composites containing SiC particles, *Tribo. Inter.*, 42,1230–1238, 2009.

Hassan, A. M., Mayyas, A.T., Alrashdan, A. and Hayajneh, M.T., Wear behavior of Al–Cu and Al–Cu/SiC components produced by powder metallurgy, *J. Mater. Sci.*, 43, 5368–5375, 2008.

Hesabi, Z. R., Simchi, A. and Reihani, S. M. S., Structural evolution during mechanical milling of nanometric and micrometric Al_2O_3 reinforced Al matrix composites, *Mater. Sci. Engg. A*, 428,159–168, 2006.

Heringhaus, F. and D, Raabe, Recent advances in the manufacturing of copper-base composites, *J. Mater. Process. Technol.*, 59, 367–372, 1996.

Hoang, O. N. T., Hoang, V.N., Kim, J.S. and Dina, D.V., Structural investigations of TiC–Cu nanocomposites prepared by ball milling and spark plasma sintering, *Metals*, 7, 1-11, 2017.

Hoang, O. N.T., Hoang, V. N., Kim, J. C. and Kim, J.S., Synthesis and characterization of Cu–TiC nanocomposites by ball milling and spark plasma sintering, *Mat. Sci.For.*, 804, 173-176, 2015.

Huiping, L., Guoqun, Z., Shanting, N. and Yiguo, L., Technologic parameter optimization of gas quenching process using response surface methods, *Comput. Mater. Sci.*, 38, 561–70, 2007.

Islak, S., Kir, D. and Buytoz, S., Effect of sintering temperature on electrical and microstructure properties of hot pressed Cu-TiC composites, *Sci. Sint.*, 46, 15-21, 2014.

Jeyasimman, D., Sivasankaran, S. , Sivaprasad, K. , Narayanasamy, R. and Kambli, R. S., An investigation of the synthesis, consolidation and mechanical behaviour of Al 6061 nanocomposites reinforced by TiC via mechanical alloying, *Mater. Des.*, 57, 394–404, 2014.

Joardar, H., Das, N.S., Sutradhar, G. and Singh, S., Application of response surface methodology for determining cutting force model in turning of LM6/SiCP metal matrix composite, *Measurement*, 47, 452–464, 2014.

Kainer, K.U., Basics of metal matrix composites, Development, 89-96, 2006.

Kamrani, S., Simchi, A., Riedel, R. and Reihani, S.M.S., Effect of reinforcement volume fraction on mechanical alloying of Al-SiC nanocomposite powders, *Powder Metall.*,50, 276–282, 2007.

Kato, H., Takama, M., Iwai, Y., Washida, K. and Sasaki, Y., Wear and mechanical properties of sintered copper–tin composites containing graphite or molybdenum disulfide, Wear, 255, 573–578, 2003.

Kestursatya, M., Kim, J.K. and Rohatgi, P.K., Wear performance of copper–graphite composite and a leaded copper alloy, Mater. Sci. Eng., A, 339, 150- 158, 2003.

Khisamov, R. K., Nazarov, K. S., Zubairov, R., Nazarov, A. A., Mulyukov, R. R., Safarov, I. M., Sergeev, S. N., Musabirov, I. I., Phuong, D. D., Trinh, P. V., Luan, N. V., Minh, P. N. and Huan, N. Q., Fabrication, microstructure, and microhardness of copper composites reinforced by carbon nanotubes, Phy.Sol.Sta., 57, 1206-1212, 2015.

Khorshid, M. T., Jahromi, S.A. J. and Moshksar, M. M., Mechanical properties of trimodal Al matrix composites reinforced by nano- and submicron-sized Al_2O_3 particulates developed by wet attrition milling and hot extrusion, Mater. Des., 31, 3880–3884, 2010.

Khakbiz, M. and Akhlaghi, F., Synthesis and structural characterization of Al–B4C nano-composite powders by mechanical alloying, J. Alloy Compd., 479, 334–341, 2009.

Kovalchenko , A.M., Fushchich, O.I. and Danyluk, S.,The tribological properties and mechanism of wear of Cu-based sintered powder materials containing molybdenum disulfide and molybdenum diselenite under unlubricated sliding against copper, Wear, 290–291, 106–123, 2012.

Kumar, R. and Dhiman, S.,A study of sliding wear behaviors of Al-7075 alloy and Al-7075 hybrid composite by response surface methodology analysis, Mater. Des., 50, 351–359, 2013.

Kumar, A., Mahapatra, M.M. and Jha, P.K.,Modeling the abrasive wear characteristics of in-situ synthesized Al–4.5%Cu/TiC composites, Wear, 306 , 170–178, 2013.

Kumar, A., Jha, P.K. and Mahapatra, M.M., Abrasive wear behavior of In Situ TiC reinforced with Al-4.5%Cu matrix, 23, 743-752, 2014.

Larionova, T., Koltsova, T., Fadin, Y. and Tolochko, O., Friction and wear of copper–carbon nanofibers compact composites prepared by chemical vapor deposition, Wear, 319, 118-122, 2014.

Lee, D.W., Ha, G.H. and Kim, B.K., Synthesis of Cu– Al_2O_3 nano com- posite powder. Scrip Mater.44, 2137–40, 2001.

Liang, Y.H., Wang, H.Y., Yang, Y.F., Wang, Y.Y. and Jiang, Q.C.,Evolution process of the synthesis of TiC in the Cu–Ti–C system, J. Alloys Compd., 452, 298-303, 2008.

Li, Li., Wong, Y.S., Fuh, J.Y.H. and L, L., EDM performance of TiC/copper-based sintered electrodes, Mater. Des., 22, 669-678, 2001.

Mandal, N., Roy, H., Mondal, B., Murmu, N.C. and Mukhopadhyay, S.K., Mathematical Modeling of wear characteristics of 6061 Al-Alloy-SiCp composite using response surface methodology, J. Mater. Eng. Perform., 21,17–24, 2012.

Mallikarjuna, H.M., Ramesh, C.S., Koppad,P.G., Keshavamurthy, R. and Keshavamurthy, D., Nanoindentation and wear behaviour of copper based hybrid composites reinforced with SiC and MWCNTs synthesized by spark plasma sintering, doi.org/10.1016/j.vacuum.2017.09.016, 2017.

Miracle, D.B., Metal matrix composites – From science to technological significanc, Compos. Sci. Technol., 65, 2526–2540, 2005.

Mirazimi, J., abachi, P. and Purazrang, K., Microstructural characterization and dry sliding wear behavior of spark plasma sintered Cu–YSZ composites, Trans. Non.Met. Soc. China, 26, 1745–1754, 2016.

Minitab Inc., User manual of MINITAB statistical software. Release 13.31. State College, PA 16801 USA; 2000.

Montgomery, D.C., Design and analysis of experiments, 3rd Ed. Wiley: New York, 1991.

Moustafa, S.F., El-Badry, S.A., Sanad, A.M. and Kieback, B., Friction and wear of copper-graphite composites made with Cu-coated and uncoated graphite powders, Wear, 253, 699-710, 2002.

Narayanasamy, R., Ramesh, T. and Prabhakar, M., Effect of particle size of SiC in aluminium matrix on workability and strain hardening behaviour of P/M composite, Mater. Sci. Engg. A, 504, 13-23, 2009.

Narayanasamy, R., Anandakrishnan, V. and Pandey, K. S., Some aspects on plastic deformation of copper and copper-titanium carbide powder metallurgy composite preforms during cold upsetting, Int. J. Mater. Form, 1, 189–209, 2008.

Nayak,D., Ray,N. , Sahoo, R. and Debata, M., Analysis of tribological performance of Cu hybrid composites reinforced with graphite and TiC using factorial techniques, Tribotrans.,57, 908-918, 2014.

Nayan, N., Kumar, A., Shukla, P. C., Srinivasa R.B., Murty, S. V. S. N., Pant, B. and Venkitakrishnan, P. V., Processing and characterization of spark plasma sintered copper/carbon nanotube composites, Mater. Sci. Eng., A, 682, 229-237, 2017.

- Nemati, N., Khosroshahi, R., Emamyb, M., and Zolriasatein, A., Investigation of microstructure, hardness and wear properties of Al-4.5 wt% Cu-TiC nanocomposites produced by mechanical milling, *Mater. Des.*, 32, 3718–3729, 2011.
- Palma, R.H., Sep' ulveda, A.H., Espinoza, R.A. and Montiglio, R.C., Performance of Cu-TiC alloy electrodes developed by reaction milling for electrical-resistance welding, *J. Mater. Process. Tech.*, 69, 62–66, 2005.
- Panelli, R. and Francisco, A.F., A Study of a New Phenomenological Compacting Equation, *Powder Technol.*, 114, 255–261, 2001.
- Pabari, R.M. and Ramtoola, Z., Application of face centred central composite design to optimise compression force and tablet diameter for the formulation of mechanically strong and fast disintegrating orodispersible tablets, *Inter. J. Pharma.*, 430, 18– 25, 2012.
- Pierson, H.O., *Handbook of refractory carbides and nitrides*, Noyes: William Andrew; 1996.
- Prosviryakov, A.S., SiC content effect on the properties of Cu-SiC composites produced by mechanical alloying, *J. Alloys Compd.*, 632, 707–710, 2015.
- Prabhu, B. and Suryanarayana, C., Synthesis and characterization of high volume fraction Al-Al₂O₃ nanocomposite powders by high energy milling, *Mater. Sci. Eng., A*, 425, 192–200, 2006.
- Rathod, S., Sharma, M., Modi, O. P., Khare, A.K. and Prasad, B. K., Effect of aluminium addition on densification behaviour and microstructural features of P/M processed Cu-TiC composites, *Int. J. Mater. Res.*, 104, 666-674, 2013.
- Rajkovic, V., Bozic, D. and Jovanovic, M.T., Properties of copper matrix reinforced with nano- and micro-sized Al₂O₃ particles, *J. Alloys Compd.*, 459, 177–184, 2008.
- Rajkovic, V., Bozic, D., Stasic, J., Wang, H. and Jovanovic, M. T., Processing, characterization and properties of copper- based composites strengthened by low amount of alumina particles, *Powder Technol.*, 268, 392–400, 2014.
- Rajkumar, K. and Aravindan, S., Tribological studies on microwave sintered copper–carbon nanotube composites, *Wear*, 270, 613–621, 2011.
- Rajkumar, K. and Aravindan, S., Tribological behavior of microwave processed copper–nanographite composites, *Tribo. Inter.*, 57, 282–296, 2013.
- Rabinowicz, E., *Friction and wear of metals*, John Willey and Sons, Inc; New York, USA, 1965.

- Ramesh, C.S., Noor, A.R., Mujeebu, M.A. and Abdullah, M.Z., Development and performance analysis of novel cast copper–SiC–Gr hybrid composites, Mater. Des., 30, 1957–1965, 2009.
- Ramesh, C.S., Noor, A.R., Mujeebu, M.A. and Abdullah, M.Z., Fabrication and study on tribological characteristics of cast copper–TiO₂–boric acid hybrid composites, Mater. Des., 30, 1632–1637, 2009.
- Radhika, N. and Raghu, R., Dry sliding wear behaviour of aluminium Al–Si12Cu/TiB₂ metal matrix composite using response surface methodology, Tribol. Lett. 59, 1–9, 2015.
- Rahimian, M., Ehsani, N., Parvin, N. and Baharvandi, H.R., The effect of particle size, sintering temperature and sintering time on the properties of Al–Al₂O₃ composites, made by powder metallurgy, J Mater Process Technol., 209, 5387–93, 2009.
- Rosso, M., Ceramic and metal matrix composites: Routes and properties, J. Mater. Process. Tech., 175, 364–375, 2006.
- Ross, P.J., Taguchi techniques for quality Engineering, McGraw-Hill International Editions, New York, 329, 1996.
- Rohatgi, P.K., Future Directions in Solidification of Metal Matrix Composites", Key Engg. Mat., 104–107, 293–312, 1995.
- Saka, N., Teixeira, J. J. P., Suh, N. P., Wear of two phase metals, Wear, 44, 77–86, 1977.
- Sabbaghian, M., Shamanian, M., Akramifard, H.R. and Esmaeilzadeh, M., Effect of friction stir processing on the microstructure and mechanical properties of Cu–TiC composite, Ceram. Inter., 40, 12969–12976, 2014.
- Samal, P.K. and Newkirk, J.W., Powder Metallurgy, ASM International, Materials Park, OH, 1998.
- Samal, C.P., Parihar, J.S. and Chaitra, D., The effect of milling and sintering techniques on mechanical properties of Cu–graphite metal matrix composite prepared by powder metallurgy route, J. Alloys Compd., 569, 95–101, 2013.
- Schoutens, J.E. and Tempo, K., Introduction to Metal Matrix Composite Materials, DOD Metal Matrix Comp. Inform. Anal. Cent., 3–20, 1982.
- Schuberta, Th., Trindade, B., Weißgarber, T., and Kieback, B., Interfacial design of Cu-based composites prepared by powder metallurgy for heat sink applications, Mater. Sci. Eng. A, 475, 39–44, 2008.
- Schatt, W. and Wieters, K., Powder metallurgy-process and materials, Eu Pow. Meta Asso Shrewsbury, 1997.

Shabani, M., Paydar, M.H., Goodarzi, R. Z.M. and Moshksar, M. M., Microstructural and sliding wear behavior of SiC-particle reinforced copper matrix composites fabricated by sintering and sinter-forging processes, *J. Mat.Res.Tech.*, 5, 5-12, 2016.

Sharma, P., Khanduja, D. and Sharma, S., Dry sliding wear investigation of Al6082/Gr metal matrix composites by response surface methodology, *J. Mater. Res. Techn.*, 5, 29–36, 2016.

Shorowordi, K.M., Laoui,T., Haseeb,A.S.M.A., Celis, J.P. and Froyen, L. Microstructure and interface characteristics of B₄C, SiC and Al₂O₃ reinforced Al matrix composites: a comparative study, *J. Mater. Process. Tech.*, 142,,738–743, 2003.

Sivasankaran, S., Sivaprasad, K., Narayanasamy, R. and Iyer, V. K., An investigation on flowability and compressibility of AA6061100-x-x wt.% TiO₂ micro and nanocomposite powder prepared by blending and mechanical alloying, *Powder Techn.*, 201,70–82, 2010.

Sorkhe, Y.A., Aghajani, H. and Tabrizi, A. T., Mechanical alloying and sintering of nanostructured TiO₂ reinforced copper composite and its characterization, *Mater. Des.*, 58, 168–174, 2014.

Srinivasan, K., Composite materials: production, properties, testing and applications, Alpha Sci. Inter. Ltd., 1-200, 2009.

Stachowiak, G.W., and A.W. Batchelor, Engg. Tribology, Burlington, Elsevier Butterworth-Heinemann, 2005.

Suresh, S., Moorthi, N. S.V., Vettivel, S.C. and Selvakumar, N., Mechanical behavior and wear prediction of stir cast Al-TiB₂ composites using response surface methodology, *Mater. Des.*, 59, 383–396, 2014.

Suryanarayana, C., Mechanical alloying and milling, *Prog. Mater. Sci.*, 46, 1–184, 2001.

Suh, N.P., The delamination theory of wear, *Wear*, 25, 111-124, 1973.

Suh, M.S., Chae, Y.H. and Kim, S.S., Friction and wear behavior of structural ceramics sliding against zirconia, *Wear*, 264, 800-806, 2008.

Tabandeh, K. M., Jenabali, J. S.A. and Moshksar, M.M., Mechanical properties of trimodal Al matrix composites reinforced by nano- and submicron-sized Al₂O₃ particulates developed by wet attrition milling and hot extrusion. *Mater. Des.*, 31, 3880–3884, 2010.

Thankachan , T. and Prakash, K.S., Microstructural, Mechanical and Tribological Behavior of Aluminum Nitride Reinforced Copper Surface Composites Fabricated Through Friction Stir Processing, *Mater. Sci. Eng.*, A, 688, 301–308, 2017.

- Tian,L., Kim, H., Anderson, I. and Russell, A., The Microstructure-strength relationship in a deformation processed Al-Ca composite, Mater. Sci. Eng., A, 570, 106–113, 2013.
- Tian, L., Anderson, I., Riedemann, T. and Russell, A., Modeling the electrical resistivity of deformation processed metal–metal composites, Acta Mater., 77, 151–161, 2014.
- Tjong ,S.C. and Lau, K.C., Tribological behaviour of SiC particle-reinforced copper matrix composites, Mat. Lett., 43, 274–280, 2000.
- Torralba, J. M., Da Costa, C. E., and Velasco, F., P/M aluminum matrix composites: An overview, J. Mater. Process. Tech., 133, 203–206, 2003.
- Tomolya, K., Sycheva, A., Sveda, M., Arki, P., Miko, T., Roosz, A., and Janovszky, D., Synthesis and Characterization of Copper-Based Composites Reinforced by CuZrAlNiTi Amorphous Particles with Enhanced Mechanical Properties, Metals , 7, 92-96, 2017.
- Tu, J.P., Rong, W., Guo,S.Y. and Yang ,Y.Z., Dry sliding wear behavior of in situ Cu–TiB₂ nanocomposites against medium carbon steel, Wear, 255, 832-835, 2003.
- Upadhyaya, A and Upadhyaya, G.S., Sintering of copper-alumina composites through blending and mechanical alloying powder metallurgy routes, Mater. Des., 16, 41-45, 1995.
- Vettivel ,S.C., Selvakumar, N. and Leema, N.,Experimental and prediction of sintered Cu–W composite by using artificial neural networks, Mater. Des., 45, 323–335, 2013.
- Vu, H. L., Tran, L. Q. , Duong, B. N. and Dang, K. Q.,Consolidation and properties of Cu-TiC composite by a reduction sintering and cold extrusion process, ECCM15 - 15TH European Conference On Composite Materials, Venice, Italy, 24-28 June 2012.
- Wang, F., Li, Y., Yamanaka, K., Wakon, K., Harata and K., Chiba, A., Influence of two-step ball-milling condition on electrical and mechanical properties of TiC-dispersion-strengthened Cu alloys, Mater. Des., 64, 441–449, 2014.
- Wang, F., Li, Y., Wang, X., Koizumi, Y., Kenta, Y. and Chiba, A., In-situ fabrication and characterization of ultrafine structured Cu-TiC composites with high strength and high conductivity by mechanical milling, J. Alloys Compd., 657, 122-132, 2016.
- Widanka, K., Effect of compacting pressure on interconnected porosity in iron PM compacts, Pow. Metall.Prog., 8, 1-6, 2008.

Xiao, J.K., Zhang, Wei., Liu, L.M., Zhang, L. and Zhang, C., Tribological behavior of copper-molybdenum disulfide composites, Wear, 384-385, 61-71, 2017.

Xiao, G., Duan, F., Zhang, G., and Fan, Q., Dissolution-precipitation mechanism of self-propagating high-temperature synthesis of TiC-Cu cermets, Materials, 14, 568-572, 2007.

Yan, J. and Jiang, K.Y., Effects of process parameters on microstructure and properties of TiC reinforced Cu-matrix composites, Adv. Mat. Res., 557-559, 318-323, 2012.

Yeoh, A., Schmerling, M., Marcus, H. L. and Eliezer, Z., Attrition and vibratory milling of Cu-TiN, J. Mater. Sci. Lett., 12, 1095-1098, 1993.

Yigezu, B.S., Mahapatra, M.M. and Jha, P.K. ,On modeling the abrasive wear characteristics of in situ Al-12%Si/TiC composites, Mater. Des., 50, 277-284, 2013.

Yue, H., Yao, L., Gao, X., Zhang, S., Guo, E., Zhang, H., Lin, X. and Wang, B., Effect of ball-milling and graphene contents on the mechanical properties and fracture mechanisms of graphene nanosheets reinforced copper matrix composites, J. Alloys Compd., 691, 755-762, 2017.

Yusoff, M., Othman, R. and Hussain, Z., Mechanical alloying and sintering of nanostructured tungsten carbide-reinforced copper composite and its characterization, Mater. Des., 32, 3293-3298, 2011.

Zarrinfar, N., Kennedy, A.R. and Shipway, P.H., Reaction synthesis of Cu-TiCx master-alloys for the production of copper based composites. Scr. Mater., 50, 949-952, 2004.

Zhao, N., LI, J. and Yang, X., Influence of the P/M process on the microstructure and properties of WC reinforced copper matrix composite, J. Mater. Sci., 39, 4829-4834, 2004.

Zhuang, J., Liu, Y.B., Cao, Z.Y., Li, Y.Y. and Liu, X.R., Microstructure characterization of the Cu-Ti-C composites prepared by mechanical alloying and spark plasma sintering, Mater. Sci. Forum, 610-613, 629-634, 2009.

Zhan, Y. and Zhang, G., Friction and wear behavior of copper matrix composites reinforced with SiC and graphite particles, Tribol. Lett., 17, 91-98, 2004.

Zhuang, J., Liu, Y.B., Cao, Z.Y. and Li, Y.Y., The Influence of technological process on dry sliding wear behaviour of Titanium Carbide reinforcement copper matrix composites, Mater. Trans., 51, 2311-2317, 2010.