LIST OF TABLES

| No. | Title | | | | | | | | |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|--|--|--|--|--|--|--|
| Table 3.1 | Chemical composition of copper (Cu) powder | | | | | | | | |
| Table 3.2 | Chemical composition of nickel (Ni) powder | | | | | | | | |
| Table 3.3 | Composition of EN-31 steel | | | | | | | | |
| Table 4.1 | Structural characterization of Cu4Ni-x wt.% TiC composite powder after 6 h of milling time, $x = 0, 2,4, 6$ and 8 wt. % | | | | | | | | |
| Table 4.2 | 2 Structural characterization of Cu4Ni-4TiC composite powder after 6 h of milling time | | | | | | | | |
| Table 4.3 | The Parameter (A), correlation coefficient (R ²) values of Cu4Ni-4TiC composite powders at different milling times using various compaction equations | | | | | | | | |
| Table 4.4 | | | | | | | | | |
| Table 4.5 | Relative density and sintered density of composites 850°C for 2 h milling duration | | | | | | | | |
| Table 6.1 | Wear test parameters and their coded values | 116 | | | | | | | |
| Table 6.2 | Design layout and experimental results of wear tests of composites | 116 | | | | | | | |
| Table 6.3 | Analysis of variance and estimated regression coefficients for volume loss of composites | | | | | | | | |
| Table 6.4 | Analysis of variance and estimated regression coefficient for coefficient of friction (COF) | 120 | | | | | | | |

| Table 6.5 | Results | of | conformation | experiment | and | their | comparison | with | 123 |
|-----------|---------------------|----|--------------|------------|-----|-------|------------|------|-----|
| | regression analysis | | | | | | | | |

 Table 6.6
 The target value and upper value of responses of composites
 127