

- Abe, M., & Uchino, K. (1974). X-ray study of the deficient perovskite $\text{La}_{23}\text{TiO}_3$. *Materials Research Bulletin*, 9(2), 147-155.
- Adams, T. B., Sinclair, D. C., & West, A. R. (2006). Characterization of grain boundary impedances in fine-and coarse-grained $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics. *Physical review B*, 73(9), 094124.
- Adams, T. B., Sinclair, D. C., & West, A. R. (2006). Characterization of grain boundary impedances in fine-and coarse-grained $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics. *Physical review B*, 73(9), 094124.
- Ahmadipour, M., Ain, M. F., & Ahmad, Z. A. (2016). A short review on copper calcium titanate (CCTO) electro ceramic: synthesis, dielectric properties, film deposition, and sensing application. *Nano-Micro Letters*, 8(4), 291-311.
- Ahn, C. W., Jeong, E. D., Kim, Y. H., Lee, J. S., Lee, H. J., & Kim, I. W. (2009). The effect of $\text{Bi}_4\text{Ti}_3\text{O}_{12}$ particles addition in lead-free $\text{Bi}_{0.5}(\text{Na}_{0.75}\text{K}_{0.25})_{0.5}\text{TiO}_3$ ceramics. *Journal of electroceramics*, 23(2-4), 402.
- Allison, M. (2007). *Metrology and analysis of nano-particulate barium titanate dielectric material* (Doctoral dissertation, Kansas State University).
- Amow, G., Au, J., & Davidson, I. (2006). Synthesis and characterization of $\text{La}_4\text{Ni}_{3-x}\text{Co}_x\text{O}_{10\pm\delta}$ ($0.0 \leq x \leq 3.0$, $\Delta x = 0.2$) for solid oxide fuel cell cathodes. *Solid State Ionics*, 177(19), 1837-1841.

Andrés, J., Longo, V. M., Cavalcante, L. S., Moreira, M. L., Varela, J. A., & Longo, E. (2011). A Fresh Look at the structural, ferroelectric and photoluminescent properties in perovskites.

Aurivillius, B. (1949). Mixed bismuth oxides with layer lattices I. The structure type of $\text{CaNb}_2\text{Bi}_2\text{O}_9$. *Arkivkemi*, 1(54), 463-480.

Aurivillius, B. (1950). Mixed bismuth oxides with layer lattices. 2. Structure of $\text{Bi}_4\text{Ti}_3\text{O}_{12}$. *Arkiv for kemi*, 1(6), 499-512.

Aurivillius, B. (1951). Mixed oxides with layer lattices. 3. Structure of $\text{BaBi}_4\text{Ti}_4\text{O}_{15}$. *Arkiv for kemi*, 2(6), 519-527.

B.V. Rao, A.D.P. Rao, V.R. Reddy, (2013). Int. J. Innov. Res. Sci. Eng. Technol. 2 (7).

Babu, G. A., Hayakawa, Y., & Ravi, G. (2015). Microwave synthesis and magnetic investigations of surfactant assisted NiO nanostructures. *Materials Letters*, 149, 54-57.

Badr, A. M., Elshaikh, H. A., & Ashraf, I. M. (2011). Impacts of temperature and frequency on the dielectric properties for insight into the nature of the charge transports in the Tl_2S layered single crystals. *Journal of Modern Physics*, 2(01), 12.

Bai, Y., Cheng, Z. Y., Bharti, V., Xu, H. S., & Zhang, Q. M. (2000). High dielectric constant ceramic powder polymer composites. *Applied Physics Letters*, 76(25), 3804-3806.

Balamurugaraj, P., Suresh, S., Koteeswari, P., & Mani, P. (2013). Growth, optical, mechanical, dielectric and photoconductivity properties of l-proline succinate NLO single crystal. *Journal of Materials Physics and Chemistry*, 1(1), 4-8.

- Ball, C. J., Begg, B. D., Cookson, D. J., Thorogood, G. J., & Vance, E. R. (1998). Structures in the system CaTiO₃/SrTiO₃. *Journal of Solid State Chemistry*, 139(2), 238-247.
- Banerjee, S., Kim, D. I., Robinson, R. D., Herman, I. P., Mao, Y., & Wong, S. S. (2006). Observation of Fano asymmetry in Raman spectra of SrTiO₃ and Ca_xSr_{1-x}TiO₃ perovskite nanocubes. *Applied physics letters*, 89(22), 223130.
- Bassat, J. M., Burriel, M., Wahyudi, O., Castaing, R., Ceretti, M., Veber, P., Weill, I., Villesuzanne, A., Grenier, J.C., Paulus, W., & Kilner, J. A. (2013). Anisotropic oxygen diffusion properties in Pr₂NiO_{4+δ} and Nd₂NiO_{4+δ} single crystals. *The Journal of Physical Chemistry C*, 117(50), 26466-26472.
- Bhalla, A. S., Guo, R., & Roy, R. (2000). The perovskite structure—a review of its role in ceramic science and technology. *Materials Research Innovations*, 4(1), 3-26.
- Bibes, M., & Barthelemy, A. (2007). Oxide spintronics. *IEEE Transactions on Electron Devices*, 54(5), 1003-1023.
- Bielański, A., Dereń, J., & Haber, J. (1957). Electric conductivity and catalytic activity of semiconducting oxide catalysts. *Nature*, 179(4561), 668-669.
- Bochu, B., Deschizeaux, M. N., Joubert, J. C., Collomb, A., Chenavas, J., & Marezio, M. (1979). Synthèse et caractérisation d'une série de titanates péroowskites isotypes de [CaCu₃(Mn₄)O₁₂]. *Journal of Solid State Chemistry*, 29(2), 291-298.

- Boulahya, K., Gil, D. M., Hassan, M., Martin, S. G., & Amador, U. (2017). Structural and microstructural characterization and properties of new phases in the Nd–Sr–Co–(Fe/Mn)–O system as air-electrodes in SOFCs. *Dalton Transactions*, 46(4), 1283-1289.
- Bueno, P. R., Varela, J. A., & Longo, E. (2008). SnO₂, ZnO and related polycrystalline compound semiconductors: an overview and review on the voltage-dependent resistance (non-ohmic) feature. *Journal of the European Ceramic Society*, 28(3), 505-529.
- Burisch, M. (1984). Approaches to personality inventory construction: A comparison of merits. *American Psychologist*, 39(3), 214.
- Cabuk, S., Akkus, H., & Mamedov, A. M. (2007). Electronic and optical properties of KTaO₃: Ab initio calculation. *Physica B: Condensed Matter*, 394(1), 81-85.
- Cain, M. G., & Stewart, M. (2014). Losses in Piezoelectrics via Complex Resonance Analysis. In *Characterisation of Ferroelectric Bulk Materials and Thin Films* Springer Netherlands. 233-242.
- Camargo, P. H. C., Satyanarayana, K. G., & Wypych, F. (2009). Nanocomposites: synthesis, structure, properties and new application opportunities. *Materials Research*, 12(1), 1-39.
- Carrasco, J., Illas, F., Lopez, N., Kotomin, E. A., Zhukovskii, Y. F., Evarestov, R. A., Mastrikov, Y. A., Piskunov, S., & Maier, J. (2006). First-principles calculations of the atomic and electronic structure of F centers in the bulk and on the (001) surface of SrTiO₃. *Physical Review B*, 73(6), 064106.

- Chandler, C. D., Roger, C., & Hampden-Smith, M. J. (1993). Chemical aspects of solution routes to perovskite-phase mixed-metal oxides from metal-organic precursors. *Chemical Reviews*, 93(3), 1205-1241.
- Chaudhuri, A., & Mandal, K. (2012). Enhancement of ferromagnetic and dielectric properties of lanthanum doped bismuth ferrite nanostructures. *Materials Research Bulletin*, 47(4), 1057-1061.
- Choudhary, R. N. P., & Patri, S. K. (2009). Dielectric Materials, Introduction, research and applications, Nova Science Pub.
- Chu, L., Li, M., Wan, Z., Ding, L., Song, D., Dou, S., Chen., J., & Wang, Y. (2014). Morphology control and fabrication of multi-shelled NiO spheres by tuning the pH value via a hydrothermal process. *Cryst. Eng. Comm*, 16(48), 11096-11101.
- Cohen, M. H., Neaton, J. B., He, L., & Vanderbilt, D. (2003). Extrinsic models for the dielectric response of CaCu₃Ti₄O₁₂. *Journal of Applied physics*, 94(5), 3299-3306.
- Corder, S. P., & Corder, S. P. (1981). Error analysis and inter language Oxford: Oxford university press 198(1).
- Cummins, S. E., & Cross, L. E. (1968). Electrical and optical properties of ferroelectric Bi₄Ti₃O₁₂ single crystals. *Journal of Applied Physics*, 39(5), 2268-2274.
- Da Conceicao, L., Silva, A. M., Ribeiro, N. F., & Souza, M. M. (2011). Combustion synthesis of La_{0.7}Sr_{0.3}Co_{0.5}Fe_{0.5}O₃ (LSCF) porous materials for application as cathode in IT-SOFC. *Materials Research Bulletin*, 46(2), 308-314.

- Davies, P. K., Wu, H., Borisevich, A. Y., Molodetsky, I. E., & Farber, L. (2008). Crystal chemistry of complex perovskites: New cation-ordered dielectric oxides. *Annu. Rev. Mater. Res.*, 38, 369-401.
- Dawber, M., Rabe, K. M., & Scott, J. F. (2005). Physics of thin-film ferroelectric oxides. *Reviews of modern physics*, 77(4), 1083.
- Denisov, V. N., Mavrin, B. N., Podobedov, V. B., & Scott, J. F. (1983). Hyper-Raman spectra and frequency dependence of soft mode damping in SrTiO₃. *Journal of Raman spectroscopy*, 14(4), 276-283.
- Deschanvres, A., Raveau, B., & Tollemer, F. (1967). Substitution of copper for a divalent metal in perovskite-type titanates. *Bull. Soc. Chim. Fr*, 11, 4077-4078.
- Desu, S. B., & Vijay, D. P. (1995). Novel fatigue-free layered structure ferroelectric thin films. *Materials Science and Engineering: B*, 32(1-2), 75-81.
- Devi., R.S., Venkatesh, R., & Rajeshwari, S., (2014), Synthesis of Titanium Dioxide Nanoparticles by Sol-Gel Technique, International Journal of Innovative Research in Science, Engineering and Technology.
- Dion, M., Ganne, M., & Tournoux, M. (1981). Nouvelles familles de phases MIMII₂Nb₃O₁₀ à feuillets “perovskites”. *Materials Research Bulletin*, 16(11), 1429-1435.
- Domen, K., Yoshimura, J., Sekine, T., Tanaka, A., & Onishi, T. (1990). A novel series of photocatalysts with an ion-exchangeable layered structure of niobate. *Catalysis letters*, 4(4), 339-343.

- Dubey, A. K., Singh, P., Singh, S., Kumar, D., & Parkash, O. (2011). Charge compensation, electrical and dielectric behavior of lanthanum doped $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$. *Journal of Alloys and Compounds*, 509(9), 3899-3906.
- Ezhilvalavan, S., & Tseng, T. Y. (2000). Progress in the developments of $(\text{Ba}, \text{Sr})\text{TiO}_3$ (BST) thin films for Gigabit era DRAMs. *Materials Chemistry and Physics*, 65(3), 227-248.
- Fang, L., Shen, M., & Cao, W. (2004). Effects of postanneal conditions on the dielectric properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ thin films prepared on Pt/Ti/SiO₂/Si substrates. *Journal of applied physics*, 95(11), 6483-6485.
- Fang, L., Shen, M., & Li, Z. (2006). Effect of double-sided CaTiO_3 buffer layers on the electrical properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ films on Pt/Ti/ SiO₂/ Si substrates. *Journal of applied physics*, 100(10), 104101.
- Fang, P., Fan, H., Xi, Z., & Chen, W. (2012). Studies of structural and electrical properties on four-layers Aurivillius phase $\text{BaBi}_4\text{Ti}_4\text{O}_{15}$. *Solid State Communications*, 152(12), 979-983.
- Fang, T. T., & Liu, C. P. (2005). Evidence of the internal domains for inducing the anomalously high dielectric constant of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$. *Chemistry of Materials*, 17(20), 5167-5171.
- Fang, T. T., & Shiau, H. K. (2004). Mechanism for developing the boundary barrier layers of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$. *Journal of the American Ceramic Society*, 87(11), 2072-2079.

- Fang, T. T., Mei, L. T., & Ho, H. F. (2006). Effects of Cu stoichiometry on the microstructures, barrier-layer structures, electrical conduction, dielectric responses, and stability of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$. *Actamaterialia*, 54(10), 2867-2875.
- Ferrarelli, M. C., Adams, T. B., Feteira, A., Sinclair, D. C., & West, A. R. (2006). High intrinsic permittivity in $\text{Na}_{1/2}\text{Bi}_{1/2}\text{Cu}_3\text{Ti}_4\text{O}_{12}$. *Applied physics letters*, 89(21), 212904.
- Galasso, F. S. (2013). *Structure, properties and preparation of perovskite-type compounds: international series of monographs in solid state physics* (Vol. 5), Elsevier.
- Gautam, P., Khare, A., Sharma, S., Singh, N. B., & Mandal, K. D. (2016). Characterization of $\text{Bi}_{2/3}\text{Cu}_3\text{Ti}_4\text{O}_{12}$ ceramics synthesized by semi-wet route. *Progress in Natural Science: Materials International*, 26(6), 567-571.
- Gautam, P., Yadava, S. S., Khare, A., & Mandal, K. D. (2017). Dielectric and magnetic studies of $0.5\text{Bi}_{2/3}\text{Cu}_3\text{Ti}_4\text{O}_{12-0.5}$ - $\text{Bi}_3\text{LaTi}_3\text{O}_{12}$ nano-composite ceramic synthesized by semi-wet route. *Ceramics International*, 43(3), 3133-3139.
- Goldschmidt, V. M. (1926). Die gesetze der krystallochemie. *Naturwissenschaften*, 14(21), 477-485.
- Goodenough, D. J., Rossmann, K., & Lusted, L. B. (1974). Radiographic applications of receiver operating characteristic (ROC) curves. *Radiology*, 110(1), 89-95.
- Goudochnikov, P., & Bell, A. J. (2007). Correlations between transition temperature, tolerance factor and cohesive energy in 2^+ : 4^+ perovskites. *Journal of Physics: Condensed Matter*, 19(17), 176201.

- H.** M. Rosenberg, "The solid state", Third Edition, Oxford University press Inc., (1988).
- Haertling, G. H.** (1999). Ferroelectric ceramics: history and technology. *Journal of the American Ceramic Society*, 82(4), 797-818.
- Hamid, A. S., Uedono, A., Chikyow, T., Uwe, K., Mochizuki, K., & Kawaminami, S.** (2006). Vacancy-type defects and electronic structure of perovskite-oxide SrTiO_3 from positron annihilation. *physica status solidi (a)*, 203(2), 300-305.
- Hao, W., Zhang, J., Tan, Y., & Su, W.** (2009). Giant Dielectric-Permittivity Phenomena of Compositionally and Structurally $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ -Like Oxide Ceramics. *Journal of the American Ceramic Society*, 92(12), 2937-2943.
- Hardy, A., Mondelaers, D., Van Bael, M. K., Mullens, J., Van Poucke, L. C., Vanhoyland, G., & D'Haen, J.** (2004). Synthesis of $(\text{Bi},\text{La})_4\text{Ti}_3\text{O}_{12}$ by a new aqueous solution-gel route. *Journal of the European Ceramic Society*, 24(6), 905-909.
- He, F., He, Z., Xie, J., & Li, Y.** (2014). IR and Raman spectra properties of Bi_2O_3 - ZnO - B_2O_3 - BaO quaternary glass system. *American Journal of Analytical Chemistry*, 5(16), 1142.
- Heiland, G.** (1954). Zum Einfluß von adsorbiertem Sauerstoff auf die elektrische Leitfähigkeit von Zinkoxydkristallen. *Zeitschrift für Physik*, 138(3-4), 459-464.
- Homes, C. C., Vogt, T., Shapiro, S. M., Wakimoto, S., & Ramirez, A. P.** (2001). Optical response of high-dielectric-constant perovskite-related oxide. *Science*, 293(5530), 673-676.
- Hu, G. D., Cheng, X., Wu, W. B., & Yang, C. H.** (2007). Effects of Gd substitution on structure and ferroelectric properties of BiFeO_3 thin films prepared using metal organic

- decomposition. *Applied Physics Letters*, 91(23), 232909.
- Huang, X., Shin, T. H., Zhou, J., & Irvine, J. T. (2015). Hierarchically nanoporous La_{1.7}Ca_{0.3}CuO_{4-δ} and La_{1.7}Ca_{0.3}Ni_xCu_{1-x}O_{4-δ} (0.25≤ x≤ 0.75) as potential cathode materials for IT-SOFCs. *Journal of Materials Chemistry A*, 3(25), 13468-13475.
- Huijben, M., Rijnders, G., Blank, D. H., Bals, S., Van Aert, S., Verbeeck, J., Tendeloo, G.V., Brinkman, A., & Hilgenkamp, H. (2006). Electronically coupled complementary interfaces between perovskite band insulators. *Nature materials*, 5(7), 556-560.
- Huizar-Félix, A. M., Hernández, T., De la Parra, S., Ibarra, J., & Kharisov, B. (2012). Sol-gel based Pechini method synthesis and characterization of Sm_{1-x}Ca_xFeO₃ perovskite 0.1≤ x≤ 0.5. *Powder technology*, 229, 290-293.
- Inaguma, Y., Sohn, J. H., Kim, I. S., & Itoh, M. (1992). Quantum Paraelectricity in a Perovskite La_{1/2}Na_{1/2}TiO₃. *Journal of the Physical Society of Japan*, 61(10), 3831-3832.
- Jacobson, A. J., Johnson, J. W., & Lewandowski, J. T. (1985). Interlayer chemistry between thick transition-metal oxide layers: synthesis and intercalation reactions of K [Ca₂Nan₃NbnO_{3n+1}] (3. ltoreq. n. ltoreq. 7). *Inorganic Chemistry*, 24(23), 3727-3729.
- Jaffe, B. (2012). *Piezoelectric ceramics* (Vol. 3). Elsevier.
- Jie, J., Wang, G., Han, X., Yu, Q., Liao, Y., Li, G., & Hou, J. G. (2004). Indium-doped zinc oxide nanobelts. *Chemical Physics Letters*, 387(4), 466-470.

- Joanni, E., Savu, R., Bueno, P. R., Longo, E., & Varela, J. A. (2008). P-type semiconducting gas sensing behavior of nanoporous of sputtered $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ thin films. *Applied Physics Letters*, 92(13), 132110.
- Jonker, G. H. (1954). Semiconducting properties of mixed crystals with perovskite structure. *Physica*, 20(7-12), 1118-1122.
- Kato, S., Ogasawara, M., Sugai, M., & Nakata, S. (2004). Crystal structure and property of perovskite-type oxides containing ion vacancy. *Catalysis surveys from Asia*, 8(1), 27-34.
- Kestigian, M., Dickinson, J. G., & Ward, R. (1957). Ion-deficient phases in titanium and vanadium compounds of the perovskite type^{1,2}. *Journal of the American Chemical Society*, 79(21), 5598-5601.
- Khare, A., Yadava, S. S., Mandal, K. D., & Mukhopadhyay, N. K. (2016). Effect of sintering duration on the dielectric properties of $0.9\text{BaTiO}_{3-0.1}\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ nano composite synthesized by solid state route. *Microelectronic Engineering*, 164, 1-6.
- Kharton, V. V., Viskup, A. P., Kovalevsky, A. V., Naumovich, E. N., & Marques, F. M. B. (2001). Ionic transport in oxygen-hyper stoichiometric phases with K_2NiF_4 -type structure. *Solid State Ionics*, 143(3), 337-353.
- Khenata, R., Sahnoun, M., Baltache, H., Rerat, M., Rashek, A. H., Illes, N., & Bouhafs, B. (2005). First-principle calculations of structural, electronic and optical properties of BaTiO_3 and BaZrO_3 under hydrostatic pressure. *Solid state communications*, 136(2), 120-125.

- Kim, I. D., Rothschild, A., Hyodo, T., & Tuller, H. L. (2006). Microsphere templating as means of enhancing surface activity and gas sensitivity of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ thin films. *Nano letters*, 6(2), 193-198.
- Kim, J., Yin, X., Tsao, K. C., Fang, S., & Yang, H. (2014). $\text{Ca}_2\text{Mn}_2\text{O}_5$ as oxygen-deficient perovskite electrocatalyst for oxygen evolution reaction. *Journal of the American Chemical Society*, 136(42), 14646-14649.
- Koinuma, H. (2005). Chemistry and electronics of oxides from carbon dioxide to perovskite. *Thin Solid Films*, 486(1), 2-10.
- Kojima, S., Hushur, A., Jiang, F., Hamazaki, S., Takashige, M., Jang, M. S., & Shimada, S. (2001). Crystallization of amorphous bismuth titanate. *Journal of non-crystalline solids*, 293, 250-254.
- Koops, C. G. (1951). On the dispersion of resistivity and dielectric constant of some semiconductors at audio frequencies. *Physical Review*, 83(1), 121.
- Kretly, L. C., Almeida, A. F. L., De Oliveira, R. S., Sasaki, J. M., & Sombra, A. S. B. (2003). Electrical and optical properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ (CCTO) substrates for microwave devices and antennas. *Microwave and Optical Technology Letters*, 39(2), 145-150.
- Kretly, L. C., Almeida, A. F. L., Fechine, P. B. A., De Oliveira, R. S., & Sombra, A. S. B. (2004). Dielectric permittivity and loss of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ (CCTO) substrates for microwave devices and antennas. *Journal of Materials Science: Materials in Electronics*, 15(10), 657-663.

- Kumar, B. R., & Rao, T. S. (2012). AFM Studies on surface morphology, topography and texture of nano structured zinc aluminum oxide thin films. *Digest Journal of Nano materials and Bio structures*, 7(4), 1881-1889.
- Kumar, L., Mohanty, P., Shripathi, T., & Rath, C. (2009). Appearance of superparamagnetic phase below Curie temperature in cobalt chromite nanoparticles. *Nanoscience and Nanotechnology Letters*, 1(3), 199-203.
- Kuo, D. H., Chang, C. C., Su, T. Y., Wang, W. K., & Lin, B. Y. (2001). Dielectric behaviours of multi-doped BaTiO₃/epoxy composites. *Journal of the European Ceramic Society*, 21(9), 1171-1177.
- Lee, H. N., Visinoiu, A., Senz, S., Harnagea, C., Pignolet, A., Hesse, D., & Gösele, U. (2000). Structural and electrical anisotropy of (001)-(116)-, and (103)-oriented epitaxial SrBi₂Ta₂O₉ thin films on SrTiO₃ substrates grown by pulsed laser deposition. *Journal of Applied Physics*, 88(11), 6658-6664.
- Lee, K. T., Bierschenk, D. M., & Manthiram, A. (2006). Sr_{3-x}La_xFe_{2-y}Co_yO_{7-δ} (0.3 ≤ x ≤ 0.6 and 0 ≤ y ≤ 0.6) Intergrowth oxide cathodes for intermediate temperature solid oxide fuel cells. *Journal of The Electrochemical Society*, 153(7), A1255-A1260.
- Lei, S., Wang, C., Guo, D., Gao, X., Cheng, D., Zhou, J., Cheng, B., & Xiao, Y. (2014). Synthesis and magnetic properties of MNb₂O₆ (M= Fe, Co, Ni) nano particles. *RSC Advances*, 4(95), 52740-52748.
- Lettieri, J., Zurbuchen, M. A., Jia, Y., Schlom, D. G., Streiffer, S. K., & Hawley, M. E. (2000). Epitaxial growth of non-c-oriented SrBi₂Nb₂O₉ on (111) SrTiO₃. *Applied Physics*

Letters, 76(20), 2937-2939.

Lettieri, J., Zurbuchen, M. A., Jia, Y., Schlom, D. G., Streiffer, S. K., & Hawley, M. E. (2000). Epitaxial growth of non-c-oriented $\text{SrBi}_2\text{Nb}_2\text{O}_9$ on (111) SrTiO_3 . *Applied Physics Letters*, 76(20), 2937-2939.

Li, J. Y., Zhao, X. T., Li, S. T., & Alim, M. A. (2010). Intrinsic and extrinsic relaxation of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics: Effect of sintering. *Journal of Applied Physics*, 108(10), 104104.

Li, J., Cho, K., Wu, N., & Ignatiev, A. (2004). Correlation between dielectric properties and sintering temperatures of polycrystalline $\text{CaCu}_{\text{sub}3}\text{Ti}_{\text{sub}4}\text{O}_{\text{sub}12}$. *IEEE transactions on dielectrics and electrical insulation*, 11(3), 534-541.

Li, W., Xiong, Z. X., & Xue, H. (2014). Preparation and electrical properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ thin ceramic sheets via water-based tape casting. *无机材料学报*, 29(11).

Li, X., & Benedek, N. A. (2015). Enhancement of Ionic Transport in Complex Oxides through Soft Lattice Modes and Epitaxial Strain. *Chemistry of Materials*, 27(7), 2647-2652.

Lines, M. E., & Glass, A. M. (1977). *Principles and applications of ferroelectrics and related*.

Liu, J., Duan, C. G., Mei, W. N., Smith, R. W., & Hardy, J. R. (2005). Dielectric properties and Maxwell-Wagner relaxation of compounds $A\text{ Cu}_3\text{Ti}_4\text{O}_{12}$ ($A = \text{Ca, Bi}_{23}\text{Y}_{23}, \text{La}_{2/3}$). *Journal of applied Physics*, 98(9), 093703.

- Liu, J., Duan, C. G., Yin, W. G., Mei, W. N., Smith, R. W., & Hardy, J. R. (2004). Large dielectric constant and Maxwell-Wagner relaxation in $\text{Bi}_{2/3}\text{Cu}_3\text{Ti}_4\text{O}_{12}$. *Physical review B*, 70(14), 144106.
- Liu, J., Sui, Y., Duan, C. G., Mei, W. N., Smith, R. W., & Hardy, J. R. (2006). $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$: Low-temperature synthesis by pyrolysis of an organic solution. *Chemistry of materials*, 18(16), 3878-3882.
- Liu, W. L., Wang, X. Q., Tian, D., Xiao, C. L., Wei, Z. J., & Chen, S. H. (2010). Chemical reaction and crystalline procedure of bismuth titanate nanoparticles derived by metal organic decomposition technique. *Nano Science & Nano Technology: An Indian Journal*, 4(1).
- Liu, Z., Chao, X., Liang, P., Yang, Z., & Zhi, L. (2014). Differentiated electric behaviors of $\text{La}_{2/3}\text{Cu}_3\text{Ti}_4\text{O}_{12}$ ceramics prepared by different methods. *Journal of the American Ceramic Society*, 97(7), 2154-2163.
- Lopes, F. W. B., Arab, M., Macedo, H. P., de Souza, C. P., de Souza, J. F., & Gavarri, J. R. (2012). High temperature conduction and methane conversion capability of BaCeO_3 perovskite. *Powder technology*, 219, 186-192.
- Lunkenheimer, P., Bobnar, V., Pronin, A. V., Ritus, A. I., Volkov, A. A., & Loidl, A. (2002). Origin of apparent colossal dielectric constants. *Physical Review B*, 66(5), 052105.
- Lunkenheimer, P., Fichtl, R., Ebbinghaus, S. G., & Loidl, A. (2004). Nonintrinsic origin of the colossal dielectric constants in $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$. *Physical review B*, 70(17), 172102.
- Lutze, W., & Ewing, R. C. (1988). Radioactive waste forms for the future.

- Maaz, K., Mumtaz, A., Hasanain, S. K., & Bertino, M. F. (2010). Temperature dependent coercivity and magnetization of nickel ferrite nanoparticles. *Journal of Magnetism and Magnetic Materials*, 322(15), 2199-2202.
- Macedo, Z. S., Ferrari, C. R., & Hernandes, A. C. (2004). Impedance spectroscopy of $\text{Bi}_4\text{Ti}_3\text{O}_{12}$ ceramic produced by self-propagating high-temperature synthesis technique. *Journal of the European Ceramic Society*, 24(9), 2567-2574.
- Maensiri, S., Thongbai, P., & Yamwong, T. (2007). Giant dielectric permittivity observed in $\text{Ca Cu}_3\text{Ti}_4\text{O}_{12}$ (Li, Ti)-doped NiO composites. *Applied physics letters*, 90(20), 202908.
- Maksimov, E. G., Matsko, N. L., Ebert, S. V., & Magnitskaya, M. V. (2007). Some problems in the theory of perovskite ferroelectrics. *Ferroelectrics*, 354(1), 19-38.
- Mandal, K. D., Rai, A. K., Kumar, D., & Parkash, O. (2009). Dielectric properties of the $\text{Ca}_{1-x}\text{La}_x\text{Cu}_3\text{Ti}_{4-x}\text{Co}_x\text{O}_{12}$ system ($x= 0.10, 0.20$ and 0.30) synthesized by semi-wet route. *Journal of Alloys and Compounds*, 478(1), 771-776.
- Mao, Y., Park, T. J., & Wong, S. S. (2005). Synthesis of classes of ternary metal oxide nanostructures. *Chemical Communications*, (46), 5721-5735.
- Mao, Y., Park, T. J., Zhang, F., Zhou, H., & Wong, S. S. (2007). Environmentally friendly methodologies of nanostructure synthesis. *Small*, 3(7), 1122-1139.
- Mateu, J., Booth, J. C., & Moeckly, B. H. (2007). Nonlinear response of combined superconductor/ferroelectric devices: First experimental step. *IEEE Transactions on Applied Superconductivity*, 17(2), 942-945.

- Mazo, G. N., Kazakov, S. M., Kolchina, L. M., Morozov, A. V., Istomin, S. Y., Lyskov, N. V., Gippius, A.A., & Antipov, E. V. (2015). Thermal expansion behavior and high-temperature electrical conductivity of $A_{2-x}A_x'Cu_{1-y}Co_yO_{4\pm\delta}$ ($A = La, Pr$; $A' = Pr, Sr$) oxides with the K_2NiF_4 -type structure. *Journal of Alloys and Compounds*, 639, 381-386.
- Mendonça, E. C., Jesus, C. B. R., Folly, W. S. D., Meneses, C. T., Duque, J. G. S., & Coelho, A. A. (2012). Temperature dependence of coercive field of $ZnFe_2O_4$ nanoparticles. *Journal of Applied Physics*, 111(5), 053917.
- Mishra, Y. K., Kaps, S., Schuchardt, A., Paulowicz, I., Jin, X., Gedamu, D., & Adelung, R. (2014). Versatile fabrication of complex shaped metal oxide nano-microstructures and their interconnected networks for multifunctional applications. *KONA Powder and Particle Journal*, 31, 92-110.
- Moreira, M. L., Gurgel, M. F. C., Mambrini, G. P., Leite, E. R., Pizani, P. S., Varela, J. A., & Longo, E. (2008). Photoluminescence of barium titanate and barium zirconate in multilayer disordered thin films at room temperature. *The Journal of Physical Chemistry A*, 112(38), 8938-8942.
- Moure, A., Castro, A., & Pardo, L. (2009). Aurivillius-type ceramics, a class of high temperature piezoelectric materials: Drawbacks, advantages and trends. *Progress in Solid State Chemistry*, 37(1), 15-39.
- Murugesan, C., Sathyamoorthy, B., & Chandrasekaran, G. (2015). Structural, dielectric and magnetic properties of Gd substituted manganese ferrite nanoparticles. *Physica Scripta*, 90(8), 085809.

- Naik, K. S. (2014). *Sintering of Ceramic Materials Under Electric Field* (Doctoral dissertation, University of Trento).
- Nimat, R. K., Joshi, R. S., & Pawar, S. H. (2008). Substrate dependent structural and electrical properties of $\text{Bi}_2\text{Cu}_{0.1}\text{V}_{0.9}\text{O}_{5.35}$ solid electrolyte thin films. *Journal of Alloys and Compounds*, 466(1), 341-351.
- Norezan, I., Yahya, A. K., & Talari, M. K. (2012). Effect of $(\text{Ba}_{0.6}\text{Sr}_{0.4})\text{TiO}_3$ (BST) doping on dielectric properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ (CCTO). *Journal of Materials Science & Technology*, 28(12), 1137-1144.
- Ocwelwang, A. R., & Tichagwa, L. (2014). Synthesis and Characterisation of Ag and Nitrogen Doped TiO_2 Nanoparticles Supported on A Chitosan-Pvae Nanofibre Support.
- Ocwelwang, A. R., & Tichagwa, L. (2014). Synthesis and Characterisation of Ag and Nitrogen Doped TiO_2 Nano particles Supported on A Chitosan-Pvae Nano fibre Support. International Journal of Advanced Research in Chemical Science (IJARCS) 1, 28-37.
- Paris, E. C., Espinosa, J. W. M., de Lazaro, S., Lima, R. C., Joya, M. R., Pizani, P. S., Leite, E.R., Souza, A. G., Varela J. A., & Longo, E. (2007). Er^{3+} as marker for order-disorder determination in the PbTiO_3 system. *Chemical physics*, 335(1), 7-14.
- Park, B. H., Kang, B. S., Bu, S. D., Noh, T. W., Lee, J., & Jo, W. (1999). Lanthanum-substituted bismuth titanate for use in non-volatile memories. *Nature*, 401(6754), 682-684.

- Pathania, D., & Singh, D. (2009). A review on electrical properties of fiber reinforced polymer composites. *International journal of theoretical & applied sciences*, 1(2), 34-37.
- Patra, H., Rout, S. K., Pratihar, S. K., & Bhattacharya, S. (2011). Effect of process parameters on combined EDTA–citrate synthesis of $\text{Ba}_{0.5}\text{Sr}_{0.5}\text{Co}_{0.8}\text{Fe}_{0.2}\text{O}_{3-\delta}$ perovskite. *Powder technology*, 209(1), 98-104.
- Patrinoiu, G., Tudose, M., Calderón-Moreno, J. M., Birjega, R., Budrigeac, P., Ene, R., & Carp, O. (2012). A green chemical approach to the synthesis of photoluminescent ZnO hollow spheres with enhanced photocatalytic properties. *Journal of Solid State Chemistry*, 186, 17-22.
- Pavlović, N., Koval, V., Dusza, J., & Srđić, V. V. (2011). Effect of Ce and La substitution on dielectric properties of bismuth titanate ceramics. *Ceramics International*, 37(2), 487-492.
- Pomiro, F., Gil, D. M., Nassif, V., Paesano Jr, A., Gómez, M. I., Guimpel, J., Sanchez, R.D., & Carbonio, R. E. (2017). Weak ferromagnetism and superparamagnetic clusters coexistence in $\text{YFe}_{1-x}\text{Co}_x\text{O}_3$ ($0 \leq x \leq 1$) perovskites. *Materials Research Bulletin*, 94, 472-482.
- Ponpandian, N., Balaya, P., & Narayanasamy, A. (2002). Electrical conductivity and dielectric behaviour of nanocrystalline NiFe_2O_4 spinel. *Journal of Physics: Condensed Matter*, 14(12), 3221.
- Prakash, B. S., & Varma, K. B. R. (2007). Influence of sintering conditions and doping on the dielectric relaxation originating from the surface layer effects in $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics. *Journal of Physics and Chemistry of Solids*, 68(4), 490-502.

- Prakash, B. S., & Varma, K. B. R. (2007). The influence of the segregation of Cu-rich phase on the microstructural and impedance characteristics of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics. *Journal of materials science*, 42(17), 7467-7477.
- Pu, Y., Wu, H., Wei, J., & Xu, N. (2012). Preparation and positive temperature coefficient of resistivity behavior of $\text{Ba}_{0.95}\text{Ca}_{0.05}\text{TiO}_3-\text{BiYO}_3-\text{Na}_{0.5}\text{Bi}_{0.5}\text{TiO}_3$ ceramics. *Powder Technology*, 219, 244-248.
- R. M. Rose, L. A. Shepard, and J. Wulff, (1971). "The structure and properties of materials", Wiley Eastern private limited.
- R.D. Sharmila, R. Venckatesh, R. Sivaraj, Int. J. Innov. Res. Sci. Eng. Technol. 3 (1)(2014) 5206–15211.
- Rachna, S., Bhattacharyya, S., & Gupta, S. M. (2010). Correlating structure, dielectric and impedance studies with lanthanum-ion substitution in bismuth titanate. *Materials Science and Engineering: B*, 175(3), 207-212.
- Rae, A. D., Thompson, J. G., Withers, R. L., & Willis, A. C. (1990). Structure refinement of commensurately modulated bismuth titanate, $\text{Bi}_4\text{Ti}_3\text{O}_{12}$. *Acta Crystallographica Section B: Structural Science*, 46(4), 474-487.
- Rahmouni, H., Smari, M., Cherif, B., Dhahri, E., & Khirouni, K. (2015). Conduction mechanism, impedance spectroscopic investigation and dielectric behavior of $\text{La}_{0.5}\text{Ca}_{0.5-x}\text{Ag}_x\text{MnO}_3$ manganites with compositions below the concentration limit of silver solubility in perovskites ($0 \leq x \leq 0.2$). *Dalton Transactions*, 44(22), 10457-10466.

- Rai, A. K., Mandal, K. D., Kumar, D., & Parkash, O. (2009). Dielectric properties of lanthanum-doped $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ synthesized by semi-wet route. *Journal of Physics and Chemistry of Solids*, 70(5), 834-839.
- Rai, A. K., Mandal, K. D., Kumar, D., & Parkash, O. (2010). Characterization of nickel doped CCTO: $\text{CaCu}_{2.9}\text{Ni}_{0.1}\text{Ti}_4\text{O}_{12}$ and $\text{CaCu}_3\text{Ti}_{3.9}\text{Ni}_{0.1}\text{O}_{12}$ synthesized by semi-wet route. *Journal of Alloys and Compounds*, 491(1), 507-512.
- Rai, A. K., Mandal, K. D., Kumar, D., & Parkash, O. (2010). Dielectric properties of $\text{CaCu}_3\text{Ti}_{4-x}\text{Co}_x\text{O}_{12}$ ($x= 0.10, 0.20,$ and 0.30) synthesized by semi-wet route. *Materials Chemistry and Physics*, 122(1), 217-223.
- Ramirez, A. P., Subramanian, M. A., Gardel, M., Blumberg, G., Li, D., Vogt, T., & Shapiro, S. M. (2000). Giant dielectric constant response in a copper-titanate. *Solid State Communications*, 115(5), 217-220.
- Rath, C., & Mohanty, P. (2011). Magnetic phase transitions in cobalt chromite nanoparticles. *Journal of superconductivity and novel magnetism*, 24(1), 629-633.
- Rath, C., Anand, S., Das, R. P., Sahu, K. K., Kulkarni, S. D., Date, S. K., & Mishra, N. C. (2002). Dependence on cation distribution of particle size, lattice parameter, and magnetic properties in nanosize Mn-Zn ferrite. *Journal of Applied Physics*, 91(4), 2211-2215.
- Rath, C., Sahu, K. K., Anand, S., Date, S. K., Mishra, N. C., & Das, R. P. (1999). Preparation and characterization of nanosize Mn-Zn ferrite. *Journal of magnetism and magnetic materials*, 202(1), 77-84.

- Reddy, Y. V., Mergel, D., & Osswald, W. (2006). Impedance spectroscopy study of RuO₂/SrTiO₃ thin film capacitors prepared by radio-frequency magnetron sputtering. *Materials Science and Engineering: B*, 130(1), 237-245.
- Richerson, D. W. (2005). *Modern ceramic engineering: properties, processing, and use in design*. CRC press.
- Rooksby, H. P., White, E. A. D., & Langston, S. A. (1965). Perovskite-Type Rare-Earth Niobates and Tantalates. *Journal of the American Ceramic Society*, 48(9), 447-449.
- Roy, M., Bala, I., Barbar, S. K., Jangid, S., & Dave, P. (2011). Synthesis, structural and electrical properties of La and Nb modified Bi₄Ti₃O₁₂ ferroelectric ceramics. *Journal of Physics and Chemistry of Solids*, 72(11), 1347-1353.
- Ruddlesden, S. N., & Popper, P. (1957). New compounds of the K₂NiF₄ type. *Acta Crystallographica*, 10(8), 538-539.
- Ruddlesden, S. N., & Popper, P. (1958). The compound Sr₃Ti₂O₇ and its structure. *Acta Crystallographica*, 11(1), 54-55.
- Satyanarayana, K. G., Pai, B. C., Sukumaran, K., & Pillai, S. G. K. (1990). Fabrication and properties of lignocellulosic fiber-incorporated polyester composites. *Hand Book of Ceramic and Composite*, 1, 339-386.
- Scott, J. F. (1989). CA Pas de Araujo.". *Ferroelectric Memories" Science*, 246(4936), p1400.
- Segal, D. (1991). *Chemical synthesis of advanced ceramic materials* (Vol. 1). Cambridge University Press.

- Seron, D., Collado, C., Mateu, J., & O'Callaghan, J. M. (2006). Analysis and simulation of distributed non linearities in ferroelectrics and superconductors for microwave applications. *IEEE transactions on microwave theory and techniques*, 54(3), 1154-1160.
- Setter, N., Damjanovic, D., Eng, L., Fox, G., Gevorgian, S., Hong, S., Kingon, A., Kohlstedt, H., Park, N. Y., Stephenson, G. B., Stolitchnov, I., Taganstev, A. K., Taylor, D. V., Yamada, T., and StreifferS., (2006). Ferroelectric thin films: Review of materials, properties, and applications. *Journal of Applied Physics*, 100(5), 051606
- Simões, A. Z., Gonzalez, A. H. M., Cavalcante, L. S., Riccardi, C. S., Longo, E., & Varela, J. A. (2007). Ferroelectric characteristics of BiFeO₃ thin films prepared via a simple chemical solution deposition. *Journal of applied physics*, 101(7), 074108.
- Simões, A. Z., Pianno, R. F., Riccardi, C. S., Cavalcante, L. S., Longo, E., & Varela, J. A. (2008). Dielectric properties of pure and lanthanum modified bismuth titanate thin films. *Journal of Alloys and Compounds*, 454(1), 66-71.
- Simoes, A. Z., Quinelato, C., Ries, A., Stojanovic, B. D., Longo, E., & Varela, J. A. (2006). Preparation of lanthanum doped Bi₄Ti₃O₁₂ ceramics by the polymeric precursor method. *Materials chemistry and physics*, 98(2), 481-485.
- Simões, A. Z., Ramirez, M. A., Riccardi, C. S., Longo, E., & Varela, J. A. (2008). Effect of the microwave oven on structural, morphological and electrical properties of SrBi₄Ti₄O₁₅ thin films grown on Pt/Ti/SiO₂/Si substrates by a soft chemical method. *Materials Characterization*, 59(6), 675-680.

- Simões, A. Z., Riccardi, C. S., Ries, A., Ramirez, M. A., Longo, E., & Varela, J. A. (2008). Ferroelectric and piezoelectric properties of bismuth layered thin films grown on (100) Pt electrodes. *Journal of materials processing technology*, 196(1), 10-14.
- Sinclair, D. C., Adams, T. B., Morrison, F. D., & West, A. R. (2002). CaCu₃Ti₄O₁₂: one-step internal barrier layer capacitor. *Applied Physics Letters*, 80(12), 2153-2155.
- Singh, L., Kim, I. W., Sin, B. C., Ullah, A., Woo, S. K., & Lee, Y. (2015). Study of dielectric, AC-impedance, modulus properties of 0.5Bi_{0.5}Na_{0.5}TiO₃-0.5CaCu₃Ti₄O₁₂ nano-composite synthesized by a modified solid state method. *Materials Science in Semiconductor Processing*, 31, 386-396.
- Singh, L., Kim, I. W., Sin, B. C., Woo, S. K., Hyun, S. H., Mandal, K. D., & Lee, Y. (2015). Combustion synthesis of nano-crystalline Bi_{2/3}Cu₃Ti_{2.90}Fe_{0.10}O₁₂ using inexpensive TiO₂ raw material and its dielectric characterization. *Powder Technology*, 280, 256-265.
- Singh, L., Rai, U. S., & Mandal, K. D. (2011). Preparation and characterization of nanostructured CaCu_{2.90}Zn_{0.10}Ti₄O₁₂ ceramic. *Nanomaterials and nanotechnology*, 1, 20.
- Singh, L., Rai, U. S., Mandal, K. D., & Rai, A. K. (2013). Effect of processing routes on microstructure, electrical and dielectric behavior of Mg-doped CaCu₃Ti₄O₁₂ electro-ceramic. *Applied Physics A*, 112(4), 891-900.
- Singh, L., Rai, U. S., Mandal, K. D., & Singh, N. B. (2014). Progress in the growth of CaCu₃Ti₄O₁₂ and related functional dielectric perovskites. *Progress in Crystal Growth and Characterization of Materials*, 60(2), 15-62.

- Singh, L., Rai, U. S., Mandal, K. D., Sin, B. C., Lee, H. I., Chung, H., & Lee, Y. (2014). Comparative dielectric studies of nanostructured BaTiO₃, CaCu₃Ti₄O₁₂ and 0.5 BaTiO₃-0.5 CaCu₃Ti₄O₁₂ nano-composites synthesized by modified sol-gel and solid state methods. *Materials Characterization*, 96, 54-62.
- Singh, L., Rai, U. S., Mandal, K., Sin, B. C., Lee, S. I., & Lee, Y. (2014). Dielectric, AC-impedance, modulus studies on 0.5BaTiO₃-0.5CaCu₃Ti₄O₁₂ nano-composite ceramic synthesized by one-pot, glycine-assisted nitrate-gel route. *Ceramics International*, 40(7), 10073-10083.
- Singh, L., Rai, U. S., Rai, A. K., & Mandal, K. D. (2013). Sintering effects on dielectric properties of Zn-doped CaCu₃Ti₄O₁₂ ceramic synthesized by modified sol-gel route. *Electron. Mater. Lett.*, 9(1), 107-113.
- Singh, V. R., Garg, A., & Agrawal, D. C. (2008). Structural changes in chemical solution deposited lanthanum doped bismuth ferrite thin films. *Applied Physics Letters*, 92(15), 152905.
- Siriprapa, P., Watcharapasorn, A., & Jiansirisomboon, S. (2009). Electrical and Mechanical Characteristics of (Bi_{4-x}La_x)Ti₃O₁₂ Ceramics. *Ferroelectrics*, 382(1), 160-165.
- Song, K. W., & Lee, K. T. (2011). Characterization of NdSrCo_{1-x}Fe_xO_{4+δ} (0≤x≤1.0) intergrowth oxide cathode materials for intermediate temperature solid oxide fuel cells. *Ceramics International*, 37(2), 573-577.
- Stirling, W. G., & Currat, R. (1976). Experimental verification of the phonon dispersion curves of strontium titanate. *Journal of Physics C: Solid State Physics*, 9(19), L519.

- Subbarao, E. C. (1962). A family of ferroelectric bismuth compounds. *Journal of Physics and Chemistry of Solids*, 23(6), 665-676.
- Subramanian, M. A., & Sleight, A. W. (2002). ACu₃Ti₄O₁₂ and ACu₃Ru₄O₁₂ perovskites: high dielectric constants and valence degeneracy. *Solid State Sciences*, 4(3), 347-351.
- Subramanian, M. A., Li, D., Duan, N., Reisner, B. A., & Sleight, A. W. (2000). High dielectric constant in ACu₃Ti₄O₁₂ and ACu₃Ti₃ FeO₁₂ phases. *Journal of Solid State Chemistry*, 151(2), 323-325.
- Sutar, B. C., Das, P. R., & Choudhary, R. N. P. (2014). Synthesis and electrical properties of Sr (Bi_{0.5}V_{0.5})O₃ electroceramic. *Advanced Materials Letters*, 5(3), 131–137.
- Tachikawa, H. I. R. O. T. O., Iyama, T. E. T. S. U. J. I., & Hamabayashi, T. A. K. A. Y. U. K. I. (1997). Metal-ligand interactions of the Cu-NO complex at the ground and low-lying excited states: an ab initio MO study. *Electronic Journal of Theoretical Chemistry*, 2(1), 263-267.
- Takata, T., Furumi, Y., Shinohara, K., Tanaka, A., Hara, M., Kondo, J. N., & Domen, K. (1997). Photocatalytic decomposition of water on spontaneously hydrated layered perovskites. *Chemistry of Materials*, 9(5), 1063-1064.
- Tan, Y. Q., Zhang, J. L., Hao, W. T., Chen, G., Su, W. B., & Wang, C. L. (2010). Giant dielectric-permittivity property and relevant mechanism of Bi_{2/3}Cu₃Ti₄O₁₂ ceramics. *Materials Chemistry and Physics*, 124(2), 1100-1104.

- Thakur, S., Rai, R., Bdikin, I., & Valente, M. A. (2016). Impedance and Modulus Spectroscopy Characterization of Tb modified Bi_{0.8}A_{0.1}Pb_{0.1}Fe_{0.9}Ti_{0.1}O₃ Ceramics. *Materials Research*, 19(1), 1-8.
- Thongbai, P., Masingboon, C., Maensiri, S., Yamwong, T., Wongsaenmai, S., & Yimnirun, R. (2007). Giant dielectric behaviour of CaCu₃Ti₄O₁₂ subjected to post-sintering annealing and uniaxial stress. *Journal of Physics: Condensed Matter*, 19(23), 236208.
- Trubnikov, I. L., Svirskaya, S. N., Zubkov, A. A., & Toguleva, I. N. (2009). Possible ways to obtain materials based on bismuth titanate Bi₄Ti₃O₁₂. *Russian Journal of Applied Chemistry*, 82(11), 1911-1914.
- Ulrich, R. K., & Schaper, L. W. (Eds.). (2003). Integrated passive component technology (Vol. 55). Piscataway, NJ: IEEE press.
- Vehkämäki, M., Hatanpää, T., Kemell, M., Ritala, M., & Leskelä, M. (2006). Atomic layer deposition of ferroelectric bismuth titanate Bi₄Ti₃O₁₂ thin films. *Chemistry of materials*, 18(16), 3883-3888.
- Villegas, M., Caballero, A. C., Jardiel, T., Aragó, C., Maudes, J., & Caro, I. (2009). Evaluation of Piezoelectric Properties of Bi₄Ti₃O₁₂-Based Ceramics at High Temperature. *Ferroelectrics*, 393(1), 44-53.
- Vogt, H., & Uwe, H. (1984). Hyper-Raman scattering from the incipient ferroelectric KTaO₃. *Physical Review B*, 29(2), 1030.

- Volanti, D. P., Cavalcante, L. S., Paris, E. C., Simões, A. Z., Keyson, D., Longo, V. M., de Figueiredo, A.T., Longo, E., Varela, J. A., De Vicente, F. S., & Hernandes, A. C. (2007). Photoluminescent behavior of $\text{SrBi}_2\text{Nb}_2\text{O}_9$ powders explained by means of $\beta\text{-Bi}_2\text{O}_3$ phase. *Applied physics letters*, 90(26), 261913.
- Wagner, K. W. (1913). Zurtheorie der unvollkommenendielektrika. *Annalen der Physik*, 345(5), 817-855.
- Wang, C. C., & Zhang, L. W. (2006). Oxygen-vacancy-related dielectric anomaly in $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$: Post-sintering annealing studies. *Physical Review B*, 74(2), 024106.
- Wang, Y. X., Zhong, W. L., Wang, C. L., & Zhang, P. L. (2001). First-principles study on the tendency to ferroelectricity of CaTiO_3 . *Solid state communications*, 117(8), 461-464.
- Warangkanagool, C., & Rujijanagul, G. (2012). Improvement in dielectric and mechanical performance of $\text{CaCu}_{3.1}\text{Ti}_4\text{O}_{12.1}$ by addition of Al_2O_3 nanoparticles. *Nanoscale research letters*, 7(1), 68.
- Warren, W. L., Dimos, D., Tuttle, B. A., Pike, G. E., Schwartz, R. W., Clews, P. J., & McIntyre, D. C. (1995). Polarization suppression in $\text{Pb}(\text{Zr},\text{Ti})\text{O}_3$ thin films. *Journal of applied physics*, 77(12), 6695-6702.
- Whangbo, M. H., & Subramanian, M. A. (2006). Structural model of planar defects in $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ exhibiting a giant dielectric constant. *Chemistry of materials*, 18(14), 3257-3260.

- Wu, L., Zhu, Y., Park, S., Shapiro, S., Shirane, G., & Tafto, J. (2005). Defect structure of the high-dielectric-constant perovskite $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$. *Physical Review B*, 71(1), 014118.
- Yadava, S. S., Khare, A., Gautam, P., Kumar, A., & Mandal, K. D. (2017). Dielectric, ferroelectric and magnetic study of iron doped hexagonal $\text{Ba}_4 \text{YMn}_3\text{O}_{11.5-\delta}$ (BYMO) and its dependence on temperature as well as frequency. *New Journal of Chemistry*, 41(11), 4611-4617.
- Yadava, S. S., Singh, L., Sharma, S., Mandal, K. D., & Singh, N. B. (2016). Effect of temperature on the dielectric and ferroelectric properties of a nanocrystalline hexagonal $\text{Ba}_4 \text{YMn}_3\text{O}_{11.5-\delta}$ ceramic synthesized by a chemical route. *RSC Advances*, 6(72), 68247-68253.
- Yang, L., Chao, X., Liang, P., Wei, L., & Yang, Z. (2015). Electrical properties and high-temperature dielectric relaxation behaviors of $\text{Na}_x\text{Bi}_{(2-x)/3}\text{Cu}_3\text{Ti}_4\text{O}_{12}$ ceramics. *Materials Research Bulletin*, 64, 216-222.
- Yang, X., Qu, N., Wang, H., Huang, B., & Wei, J. (2006). A study of La-doped $\text{Bi}_2\text{Ti}_2\text{O}_7$ nanocrystals prepared by chemical solution deposition technique. *Materials Letters*, 60(23), 2886-2888.
- Yang, Y., Sun, Y., & Jiang, Y. (2006). Structure and photocatalytic property of perovskite and perovskite-related compounds. *Materials Chemistry and Physics*, 96(2), 234-239.
- Yang, Z., Liang, P., Yang, L., Shi, P., Chao, X., & Yang, Z. (2015). Synthesis, dielectric properties of $\text{Bi}_{2/3}\text{Cu}_3\text{Ti}_4\text{O}_{12}$ ceramics by the sol-gel method. *Journal of Materials Science: Materials in Electronics*, 26(3), 1959-1968.

- Yoshimura, J., Ebina, Y., Kondo, J., Domen, K., & Tanaka, A. (1993). Visible light-induced photocatalytic behavior of a layered perovskite-type rubidium lead niobate, $\text{RbPb}_2\text{Nb}_3\text{O}_{10}$. *The Journal of Physical Chemistry*, 97(9), 1970-1973.
- Yu, H., Liu, H., Hao, H., Luo, D., & Cao, M. (2008). Dielectric properties of $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$ ceramics modified by SrTiO_3 . *Materials Letters*, 62(8), 1353-1355.
- Yu, H., Liu, H., Luo, D., & Cao, M. (2008). Microwave synthesis of high dielectric constant $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$. *Journal of materials processing technology*, 208(1), 145-148.
- Zhang, D., Zhu, J., Zhang, N., Liu, T., Chen, L., Liu, X., Ma, R., Zhang, H., & Qiu, G. (2015). Controllable fabrication and magnetic properties of double-shell cobalt oxides hollow particles. *Scientific reports*, 5.
- Zhu, Y., Zheng, J. C., Wu, L., Frenkel, A. I., Hanson, J., Northrup, P., & Ku, W. (2007). Nanoscale disorder in $\text{CaCu}_3\text{Ti}_4\text{O}_{12}$: a new route to the enhanced dielectric response. *Physical review letters*, 99(3), 037602.