

List of Figures

3.1	(a,b) . Variation of the phase velocity, V_E of the elastic mode wave with frequency, ω	71
3.2	(a,b) . Variation of the phase velocity, V_T of the thermal mode wave with frequency, ω	72
3.3	(a,b) . Variation of the specific loss, SP_E of the elastic mode wave with frequency, ω	73
3.4	(a,b) . Variation of the specific loss, SP_T of the thermal mode wave with frequency, ω	73
3.5	(a,b) . Variation of the penetration depth, δ_E of the elastic mode wave with frequency, ω	75
3.6	(a,b) . Variation of the penetration depth, δ_T of the thermal mode wave with frequency, ω	75
3.7	(a,b) .Variation of the amplitude coefficient factor of the thermodynamic temperature, M_T for the thermal mode wave with frequency, ω	77
3.8	(a,b) . Variation of the phase shift, Ψ_T of the thermodynamic temperature for the thermal mode wave with frequency, ω	78
4.1	(a) .Variation of u vs. r under TGL model for different values of t and K_1 , (b) .Variation of u vs. r for $K_1 = -0.5$ and $t = 0.3$ under different models	96

4.2	(a).Variation of ϕ vs. r under TGL model for different values of t and K_1 , (b).Variation of ϕ vs. r for $K_1 = -0.5$ and $t = 0.3$ under different modes	97
4.3	(a).Variation of θ vs. r under TGL model for different values of t and K_1 , (b).Variation of θ vs. r for $K_1 = -0.5$ and $t = 0.3$ under different models	98
4.4	(a).Variation of σ_{rr} vs. r under TGL model for different values of t and K_1 , (b).Variation of σ_{rr} vs. r for $K_1 = -0.5$ and $t = 0.3$ under different models	99
4.5	(a).Variation of $\sigma_{\varphi\varphi}$ vs. r under TGL model for different values of t and K_1 , (b).Variation of $\sigma_{\varphi\varphi}$ vs. r for $K_1 = -0.5$ and $t = 0.3$ under different models	100
5.1	(a).Variation of displacement u vs. x at $t = 0.1$, (b). Variation of displacement u vs. x at $t = 0.7$ and (c). Variation of displacement u vs. x at $t = 1.2$	117
5.2	(a).Variation of temperature θ vs. x at $t = 0.1$, (b). Variation of temperature θ vs. x at $t = 0.7$ and (c). Variation of temperature θ vs. x at $t = 1.2$	119
5.3	(a).Variation of stress σ_{xx} vs. x at $t = 0.1$, (b). Variation of stress σ_{xx} vs. x at $t = 0.7$ and (c). Variation of stress σ_{xx} vs. x at $t = 1.2$	121

6.1	(a). Variation of displacement, u versus r for the Case-I,	
	(b). Variation of temperature, θ versus r for the Case-I,	
	(c). Variation of radial stress, σ_{rr} versus r for the Case-I	
	and (d). Variation of tangential stress, $\sigma_{\varphi\varphi}$ versus r for the	
	Case-I	136
6.2	(a). Variation of displacement, u versus r for the Case-II,	
	(b). Variation of temperature, θ versus r for the Case-II,	
	(c). Variation of radial stress, σ_{rr} versus r for the Case-II	
	and (d). Variation of tangential stress, $\sigma_{\varphi\varphi}$ versus r for the	
	Case-II	138
6.3	(a). Variation of displacement, u versus r for the Case-III,	
	(b). Variation of temperature, θ versus r for the Case-III,	
	(c). Variation of radial stress, σ_{rr} versus r for the Case-III	
	and (d). Variation of tangential stress, $\sigma_{\varphi\varphi}$ versus r for the	
	Case-III	140
7.1	Variation of volume fraction of the constituents of function-	
	ally graded material	150
7.2	Graphical representation of base elements and nodes of finite	
	element method	154
7.3	Variation of displacement, u vs. r at $t = 0.3$ for different	
	values of n	160
7.4	Variation of temperature, θ vs. r at $t = 0.3$ for different	
	values of n	160